

**PLC01-6****LOW CAPACITANCE TVS ARRAY****APPLICATIONS**

- ✓ T1/E1 Line Cards
- ✓ ISDN Telecom Equipment
- ✓ xDSL, USB, SCSI & Ethernet Interfaces
- ✓ Cellular Base Stations
- ✓ Data & Bus Lines for FCC Part 68 Applications

IEC COMPATIBILITY (EN61000-4)



- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns
- ✓ 61000-4-5 (Surge): 48A, 8/20μs, L3(Line-Gnd), L4(Line-Line) & L1(Power)

FEATURES

- ✓ **ESD PROTECTION > 40 kilovolts**
- ✓ 1,500 Watts Peak Pulse Power per Line (tp=10/1000μs)
- ✓ Low Clamping Voltage
- ✓ 100A (10/1000μs) per Bellcore 1089(Intra-Building)
- ✓ 200A (10/160μs) per FCC Part 68
- ✓ Bidirectional Configuration
- ✓ Protects 1 Line

MECHANICAL CHARACTERISTICS

- ✓ Molded JEDEC SO-16 (Wide Body) Package
- ✓ Weight 0.15 grams (Approximate)
- ✓ Flammability rating UL 94V-0
- ✓ 16mm Tape and Reel Per EIA Standard 481
- ✓ Marking: Logo, Part Number, Date Code & Pin One Defined By Dot on Top of Package

**PIN CONFIGURATION**

DEVICE CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (td = 10/1000μs) - See Figure 1	P _{PP}	1,500	Watts
Operating Temperature	T _J	-55°C to 150°C	°C
Storage Temperature	T _{STG}	-55°C to 150°C	°C




ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified						
PART NUMBER (See Note 1)	RATED STAND-OFF VOLTAGE V _{WM} VOLTS	MINIMUM BREAKDOWN VOLTAGE @ 1mA V _(BR) VOLTS	MAXIMUM CLAMPING VOLTAGE (See Note 2) @ I _P = 100A V _C VOLTS	MAXIMUM CLAMPING VOLTAGE (See Note 3) @ I _P = 200A V _C	MAXIMUM LEAKAGE CURRENT @V _{WM} I _D μA	TYPICAL CAPACITANCE @0V, 1 MHz C pF
PLC01-6	6.0	8.0	15.0	16.0	25	50

Note 1: Electrical characteristics apply from pins 13-16 to 1-4 and 5-8 to 9-12; see circuit diagram.


Note 2: V_C tested at 10/1000μs impulse waveform.

Note 3: 10/160μs impulse waveform per FCC Part 68.

GRAPHS



PACKAGE OUTLINE & DIMENSIONS



COPYRIGHT © ProTek Devices 2003

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices

2929 South Fair Lane, Tempe, AZ 85282
Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: sales@protekdevices.com

Web Site: www.protekdevices.com