

 Select Your Country/Region

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

APC Performance SurgeArrest 11 Outlet with Tel2/Splitter, Coax and Ethernet Protection

Complete Surge Protection For High Performance Computers & Electronics

Includes: 6ft Gold Plated Coaxial Cable, 6ft High Speed Internet Cable, 6ft Network Cable, User Manual

Part Number : **PF11VNT3**



[Compare Models](#)



[Email Technical Specifications](#)



[Printer Friendly](#)

Additional Information

[Product Overview](#)

[User Manual & Installation Guides](#)

[Product Distribution](#)



[\[+\] More Images](#)

Technical Specifications

Output

Number of Outlets	11
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P 
Maximum Line Current per phase	15A
Cord Length	10 feet (3.05 meters)

Surge Protection and Filtering

Surge energy rating	2030 Joules
eP Joule Rating	3400
EMI/RFI Noise rejection (100 kHz to 10 mHz)	70 dB
Peak Current Normal Mode	20 kAmps
Peak Current Common Mode	60 kAmps
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line),RJ45 10/100 Base-T Ethernet protection,Co-axial Video / Cable protection
Data Lines Protected (multi-line only)	--

Features:

- i 180 degree Rotating Cord Retainer
- i Adjustable Cable Management
- i Always on Outlets
- i Cable Line Protection
- i Catastrophic Event Protection
- i Coax Protection
- i Cord Management
- i Data-line Protection
- i Fail Safe Mode
- i IEEE let-through rating and UL 1449 compliance
- i Lightning and Surge Protection
- i Noise Filtering
- i Phone Line Splitter
- i Plug Activated Safety Shutters
- i Right Angle Plug
- i Status Indicator LED's
- i Surge Protection
- i Transformer Block Spacing

Let Through Voltage Rating	< 40
----------------------------	------

 Physical

Net Weight	2.45 lbs. (1.11 kg)
Maximum Height	12.50 inches (318 mm)
Maximum Width	5.75 inches (146 mm)
Maximum depth	1.50 inches (38 mm)
Shipping Weight	3.45 lbs. (1.57 kg)
Shipping Height	14.00 inches (356 mm)
Shipping Width	9.50 inches (241 mm)
Shipping Depth	2.13 inches (54 mm)
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	27 X 10.2 X 16 inches
Master Carton Weight	40.00 lbs.
SCC Codes	1073130419990 5
Color	Charcoal
Units per Pallet	288.00

 Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-50000 feet (0-15000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

 Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V