



- Clamp ties are used to attach a bundle to another surface such as a control panel wall or ceiling using another fastener.
- The design allows for bundling before or after screwing clamp in place.

Part Number:	PLC4H-S25-L0
Product Family:	<i>Pan-Ty</i> ® Clamp Ties - Weather Resistant
Product Line:	Clamp Cable Ties
RoHS Compliancy Status:	Compliant
Part Description:	Clamp Tie, 15.1", Light-Heavy cross section
Product Type:	Cable Ties
Material:	Weather Resistant Nylon 6.6
Color:	Black
CSA Certified:	No
UL Listed (File #E56854):	No
UL Recognized (File #E56854):	No
Length (In.):	15.1
Length (mm):	384

Width (In.):	.300
Width (mm):	7.6
Boss Height (In.):	.265
Boss Height (mm):	6.7
Boss Width (In.):	.500
Boss Width (mm):	12.7
CE Compliant:	Yes
Cross Section:	Light-Heavy
Locking Style:	Locking
Material Flammability Rating:	UL94V-2
Max. Bundle Diameter (In.):	4.00
Max. Bundle Diameter (mm):	102
Max. Continuous Use Temperature:	185°F (85°C)
Metric Screw Size:	M6
Min. Loop Tensile Strength (Lbs.):	120
Min. Loop Tensile Strength (N):	534
Nominal Hole Diameter (In.):	.260
Nominal Hole Diameter (mm):	6.6
Screw Size:	1/4

Std. Pkg. UOM:	PK
Thickness (In.):	.075
Thickness (mm):	1.9
Tool:	GTH, GS4H, GS4EH, PTH, STH2, ST3EH
UOM:	PC
Std. Pkg. Qty.:	50
Min. Order Qty.:	50