

[Search](#)
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Panelmount Surge Protection Device 240/120V 160KA

High quality TVSS for datacenters, industrial facilities and commercial buildings.

Includes: Front Panel Sticker(s), User Manual

Part Number : **PMP4**

 [Compare Models](#)
 [Email Technical Specifications](#)
 [Printer Friendly](#)


[+] More Images

Additional Information

[Product Overview](#)
[User Manual & Installation Guides](#)
[Product Distribution](#)

Technical Specifications

Input

Nominal Input Voltage	120V,230V
Input Frequency	50/60 Hz
Input Connections	Hard Wire 3-wire (2PH + G)

Surge Protection and Filtering

Surge energy rating	4080 Joules
EMI/RFI Noise rejection (100 kHz to 10 mHz)	50 dB
Peak Current Normal Mode	160 (/PH) kAmps
Peak Current Common Mode	160 kAmps
NM Surge Response Time (ns)	1 ns

Physical

Net Weight	22.00 lbs. (10.00 kg)
Maximum Height	12.00 inches (305 mm)
Maximum Width	12.00 inches (305 mm)
Maximum depth	6.25 inches (159 mm)
Shipping Weight	25.00 lbs. (11.36 kg)
Shipping Height	17.50 inches (445 mm)
Shipping Width	16.00 inches (406 mm)
Shipping Depth	10.25 inches (260 mm)
SCC Codes	10731304019968
Color	Grey

Features:

- i Audible Alarms
- i Catastrophic Event Protection
- i Lightning and Surge Protection
- i Low Z bussbars
- i NEMA 1 enclosure
- i Patented thermal overload protection
- i Protection working indicator
- i Remote monitoring capability
- i Replaceable surge protection modules
- i Status Indicator LED's

 Environmental

Operating Environment	-40 - 60 °C (-40 - 140 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-55 - 60 °C (-67 - 140 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-10000 feet (0-3000 meters)

 Conformance

Regulatory Approvals	UL 1283,UL 1449,cUL Listed
Standard Warranty	5 year repair or replace
UL 1449 TVSS Rating	400 V

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)