

[Search](#)
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Panelmount Surge Protection Device 240/120V 160KA w/Disconnect

High quality TVSS for datacenters, industrial facilities and commercial buildings.

Includes: Front Panel Sticker(s), User Manual

Part Number : **PMP4D**

 [Compare Models](#)
 [Email Technical Specifications](#)
 [Printer Friendly](#)


[+] More Images

Additional Information

[Product Overview](#)
[User Manual & Installation Guides](#)
[Product Distribution](#)

Technical Specifications

Input

Nominal Input Voltage	120V,230V
Input Frequency	50/60 Hz
Input Connections	Hard Wire 3-wire (2PH + G)

Surge Protection and Filtering

Surge energy rating	4080 Joules
EMI/RFI Noise rejection (100 kHz to 10 mHz)	50 dB
Peak Current Normal Mode	160 (/PH) kAmps
Peak Current Common Mode	160 kAmps
NM Surge Response Time (ns)	1 ns

Physical

Net Weight	29.00 lbs. (13.18 kg)
Maximum Height	16.00 inches (406 mm)
Maximum Width	14.00 inches (356 mm)
Maximum depth	6.00 inches (152 mm)
Shipping Weight	32.00 lbs. (14.55 kg)
Shipping Height	21.00 inches (533 mm)
Shipping Width	17.25 inches (438 mm)
Shipping Depth	11.50 inches (292 mm)
SCC Codes	10731304019975
Color	Grey

Features:

- i Audible Alarms
- i Catastrophic Event Protection
- i Lightning and Surge Protection
- i Low Z bussbars
- i Manual disconnect switch
- i NEMA 1 enclosure
- i Patented thermal overload protection
- i Protection working indicator
- i Remote monitoring capability
- i Replaceable surge protection modules
- i Status Indicator LED's

 Environmental

Operating Environment	-40 - 60 °C (-40 - 140 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-55 - 60 °C (-67 - 140 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-10000 feet (0-3000 meters)

 Conformance

Regulatory Approvals	UL 1283,UL 1449,cUL Listed
Standard Warranty	5 year repair or replace
UL 1449 TVSS Rating	400 V