

APC PROFESSIONAL SURGEARREST 8 OUTLET W/TEL&COAX 120V

Reliable Surge Protection for Home or Office Computers and Electronic Equipment.

Includes: 1.8 Meter Tel Cable (2), 60 cm Coaxial Cable, User Manual

Part Number : **PRO8TV**

-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)

Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



[\[+\] More Images](#)

Technical Specifications

Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)

Input Connections	NEMA 5-15P
-------------------	------------



Maximum Line Current per phase	15A
--------------------------------	-----

Features:

- Always on Outlets
- Cable Line Protection
- Catastrophic Event Protection
- Data-line Protection
- Lightning and Surge Protection
- Protection working indicator
- Right Angle Plug
- Site wiring fault indicator
- Transformer Block Spacing

Surge Protection and Filtering

Surge energy rating	320 Joules
eP Joule Rating	1760
EMI/RFI Noise rejection (100 kHz to 10 mHz)	60 dB
Peak Current Normal Mode	13 kAmps
Peak Current Common Mode	13 kAmps
Dateline protection	RJ-11 Modem/Fax/DSL protection (two wire single line), Co-axial Video / Cable protection
Data Lines Protected (multi-line only)	1
Let Through Voltage Rating	< 85

Physical

Net Weight	2.20 lbs. (1.00 kg)
Maximum Height	1.75 inches (44 mm)
Maximum Width	8.00 inches (203 mm)
Maximum depth	5.75 inches (146 mm)
Shipping Weight	2.50 lbs. (1.14 kg)
Shipping Height	2.00 inches (51 mm)
Shipping Width	13.75 inches (349 mm)
Shipping Depth	6.25 inches (159 mm)
Master Carton Units	12.00
Master Carton Weight	31.90 lbs.
SCC Codes	1073130400083 6
Color	Beige
Units per Pallet	600.00

 Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

 Conformance

Regulatory Approvals	CSA,UL 497B,UL 1283,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V