

PS-602-HG

- Versatile power distribution strip
- 6 hospital-grade outlets and hospital-grade plug
- 1.5 ft. cord
- 15A resettable circuit breaker
- UL, cUL approved



DESCRIPTION

Tripp Lite's PS-602-HG power strip offers 15-amp capacity AC power distribution in a rugged, all-metal outlet strip for 120-volt applications. Features 6 hospital-grade receptacles, 1.5 foot power cord and built-in 15-amp resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA5-15PHG hospital-grade plug and 6 NEMA5-15RHG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60 Hz, 15A

FORMAT: all-metal corded multi-outlet strip

KEY BUYING POINTS

- 6 NEMA 5-15RHG hospital-grade receptacles
- Rugged all-metal housing withstands years of use without breakage
- 1.5-foot AC cord with integrated, molded hospital-grade NEMA 5-15PHG plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60 Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

TYPICAL APPLICATIONS

- AC power distribution with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

PACKAGE INCLUDES

- PS-602-HG Power Strip
- User manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	6- outlet power strip with hospital-grade plug and outlets, 1.5 ft. cord

Voltage compatibility:	120V AC
Frequency compatibility:	50/60 Hz
OUTPUT	
Outlet quantity / type:	6 NEMA 15-5RHG
Outlet orientation:	Single row of 6
Overload protection:	15 amp circuit breaker
INPUT	
Input connection type:	NEMA 5-15PHG input plug
Input cord length (ft.):	1.5
Input cord length (m):	0.46
Recommended electrical service:	15A, 120V
LEDS ALARMS & SWITCHES	
Switches:	no
PHYSICAL	
Shipping weight (lbs):	3.1
Shipping weight (kg):	1.4
Unit weight (lbs):	2
Unit weight (kg):	0.91
Unit Dimensions (HWD/in):	1.5 x 13.75 x 2.5
Unit Dimensions (HWD/cm):	3.8 x 34.9 x 6.4
Material of construction:	Metal
Integrated keyhole mounting tabs:	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Housing color:	White
Receptacle color:	White
AC line cord color:	White
CERTIFICATIONS	
UL1363 (Power Tap):	UL1363 (Series Number: AGIB12015SL)
cUL / CSA (Canada):	cUL (Series Number: AGIB12015SL)
WARRANTY	
Product warranty:	Lifetime

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.