#### **PS-606-HG**

- Versatile power distribution strip
- 6 hospital-grade outlets and hospital-grade plug
- 6-ft. cord

- 15A resettable circuit breaker
- UL, cUL approved



## **DESCRIPTION**

Tripp Lite's PS-606-HG power strip offers 15 amp capacity AC power distribution in a rugged, all-metal outlet strip for 120 volt applications. Features 6 hospital-grade receptacles, 6 foot power cord and built-in 15 amp resettable circuit breaker. Switchless design prevents accidental shutoff. Optional use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA5-15PHG hospital-grade plug and 6 NEMA5-15RHG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60 Hz, 15A

FORMAT: all-metal corded multi outlet strip

#### **KEY BUYING POINTS**

- 6 NEMA 5-15RHG hospital-grade receptacles
- Rugged all-metal housing withstands years of use without breakage
- 6 foot AC cord with integrated, molded hospital-grade NEMA 5-15PHG plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60 Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

## TYPICAL APPLICATIONS

• AC power distribution with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

# **PACKAGE INCLUDES**

- PS-606-HG Power Strip
- User manual with warranty information

## **COMPLETE SPECIFICATIONS**

SYSTEM OVERVIEW	
System overview:	6 outlet power strip with hospital grade plug and outlets, 6 ft. cord

Voltage compatibility:	120V AC
Frequency compatibility:	50/60 Hz
OUTPUT	
Outlet quantity / type:	6 NEMA 15-5RHG
Outlet orientation:	Single row of 6
Overload protection:	15 amp circuit breaker
INPUT	
Input connection type:	NEMA 5-15PHG hospital grade input plug
Input cord length (ft.):	6
Input cord length (m):	1.83
Recommended electrical service:	15A, 120V
LEDS ALARMS & SWITCHES	
Switches:	No power switch
PHYSICAL	
Shipping weight (lbs):	3.5
Shipping weight (kg):	1.6
Unit weight (lbs):	2.4
Unit weight (kg):	1.1
Unit Dimensions (HWD/in):	1.5 x 13.75 x 2.5
Unit Dimensions (HWD/cm):	3.8 x 34.9 x 6.4
Material of construction:	Metal
Integrated keyhole mounting tabs:	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Housing color:	White
Receptacle color:	White
AC line cord color:	White
CERTIFICATIONS	
UL1363 (Power Tap):	UL1363 (Series Number: AGIB12015SL)
cUL / CSA (Canada):	cUL (Series Number: AGIB12015SL)
WARRANTY	
Product warranty:	Lifetime

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.