

International
IRF Rectifier


80RIA SERIES

PHASE CONTROL THYRISTORS

Stud Version

Features

- Hermetic glass-metal seal
- International standard case TO-209AC (TO-94)




Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

Major Ratings and Characteristics

Parameters	80RIA	Unit
$I_{T(AV)}$	80	A
@ T_C	85	°C
$I_{T(RMS)}$	125	A
I_{TSM} @ 50Hz	1900	A
@ 60Hz	1990	A
I^2t @ 50Hz	18	KA ² s
@ 60Hz	16	KA ² s
V_{DRM}/V_{RRM}	400 to 1200	V
t_q typical	110	µs
T_J	- 40 to 125	°C



80RIA Series

Bulletin I25201 rev. B 03/03

International
IR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM} , max. repetitive peak and off-state voltage V	V_{RSM} , maximum non-repetitive peak voltage V	I_{DRM}/I_{RRM} max. @ $T_J = 125^\circ\text{C}$ mA
80RIA	40	400	500	15
	80	800	900	
	120	1200	1300	

On-state Conduction

Parameter		80RIA	Units	Conditions			
I _{T(AV)}	Max. average on-state current @ Case temperature	80	A	180° conduction, half sine wave			
		85	°C				
I _{T(RMS)}	Max. RMS on-state current	125	A	DC @ 75°C case temperature			
I _{TSM}	Max. peak, one-cycle non-repetitive surge current	1900	A	t = 10ms	No voltage	Sinusoidal half wave, Initial T _J = T _J max.	
		t = 8.3ms		reapplied			
		1600		t = 10ms	100% V _{RRM}		
		1675		t = 8.3ms	reapplied		
I ² t	Maximum I ² t for fusing	18	KA ² s	t = 10ms	No voltage		
		16		t = 8.3ms	reapplied		
		12.7		t = 10ms	100% V _{RRM}		
		11.7		t = 8.3ms	reapplied		
I ² √t	Maximum I ² √t for fusing	180.5	KA ² √s	t = 0.1 to 10ms, no voltage reapplied			
V _{T(TO)1}	Low level value of threshold voltage	0.99	V	(16.7% × π × I _{T(AV)} < I < π × I _{T(AV)}), T _J = T _J max.			
V _{T(TO)2}	High level value of threshold voltage	1.13		(I > π × I _{T(AV)}), T _J = T _J max.			
r _{t1}	Low level value of on-state slope resistance	2.29	mΩ	(16.7% × π × I _{T(AV)} < I < π × I _{T(AV)}), T _J = T _J max.			
r _{t2}	High level value of on-state slope resistance	1.84		(I > π × I _{T(AV)}), T _J = T _J max.			
V _{TM}	Max. on-state voltage	1.60	V	I _{pk} = 250A, T _J = 25°C t _p = 10ms sine pulse			
I _H	Maximum holding current	200	mA	T _J = 25°C, anode supply 12V resistive load			
I _L	Typical latching current	400					

Switching

Parameter	80RIA	Units	Conditions
di/dt Max. non-repetitive rate of rise of turned-on current	300	A/ μ s	$T_J = 125^\circ\text{C}$, $V_d = \text{rated } V_{\text{DRM}}$, $I_{\text{TM}} = 2 \times di/dt$ snubber 0.2 μ F, 15 Ω , Gate pulse: 20V, 65 Ω , $t_p = 6\mu\text{s}$, $t_r = 0.5\mu\text{s}$ Per JEDEC Standard RS-397, 5.2.2.6.
t_d Typical delay time	1	μ s	Gate pulse: 10V, 15 Ω source, $t_p = 6\mu\text{s}$, $t_r = 0.1\mu\text{s}$, $V_d = \text{rated } V_{\text{DRM}}$, $I_{\text{TM}} = 50\text{Adc}$, $T_J = 25^\circ\text{C}$.
t_q Typical turn-off time	110		$I_{\text{TM}} = 50\text{A}$, $T_J = T_J \text{ max}$, $di/dt = -5\text{A}/\mu\text{s min.}$, $V_R = 50\text{V}$, $dv/dt = 20\text{V}/\mu\text{s}$, Gate bias: 0V 25 Ω , $t_p = 500\mu\text{s}$

Blocking

Parameter	80RIA	Units	Conditions
dv/dt Maximum critical rate of rise of off-state voltage	500	V/ μ s	$T_J = 125^\circ\text{C}$ exponential to 67% rated V_{DRM}
I_{RRM} Max. peak reverse and off-state leakage current I_{DRM}	15	mA	$T_J = 125^\circ\text{C}$ rated $V_{\text{DRM}}/V_{\text{RRM}}$ applied

Triggering

Parameter	80RIA	Units	Conditions
P_{GM} Maximum peak gate power	12	W	$T_J = T_J \text{ max}$, $t_p \leq 5\text{ms}$
$P_{\text{G(AV)}}$ Maximum average gate power	3		$T_J = T_J \text{ max}$, $f = 50\text{Hz}$, $d\% = 50$
I_{GM} Max. peak positive gate current	3	A	$T_J = T_J \text{ max}$, $t_p \leq 5\text{ms}$
$+V_{\text{GM}}$ Maximum peak positive gate voltage	20	V	$T_J = T_J \text{ max}$, $t_p \leq 5\text{ms}$
$-V_{\text{GM}}$ Maximum peak negative gate voltage	10		
I_{GT} Max. DC gate current required to trigger	270	mA	$T_J = -40^\circ\text{C}$
	120		$T_J = 25^\circ\text{C}$
	60		$T_J = 125^\circ\text{C}$
V_{GT} Max. DC gate voltage required to trigger	3.5	V	$T_J = -40^\circ\text{C}$
	2.5		$T_J = 25^\circ\text{C}$
	1.5		$T_J = 125^\circ\text{C}$
I_{GD} DC gate current not to trigger	6	mA	$T_J = T_J \text{ max}$
V_{GD} DC gate voltage not to trigger	0.25	V	

Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 6V anode-to-cathode applied

Max. gate current/ voltage not to trigger is the max. value which will not trigger any unit with rated V_{DRM} anode-to-cathode applied

80RIA Series

Bulletin I25201 rev. B 03/03

International
IRF Rectifier

Thermal and Mechanical Specification

Parameter	80RIA	Units	Conditions
T _J Max. operating temperature range	-40 to 125	°C	
T _{stg} Max. storage temperature range	-40 to 150		
R _{thJC} Max. thermal resistance, junction to case	0.30	K/W	DC operation
R _{thCS} Max. thermal resistance, case to heatsink	0.1		Mounting surface, smooth, flat and greased
T Mounting torque, ± 10%	15.5 (137)	Nm	Non lubricated threads
	14 (120)	(lbf-in)	Lubricated threads
wt Approximate weight	130	g	
Case style	TO-209AC(TO-94)		See Outline Table

ΔR_{thJ-C} Conduction

(The following table shows the increment of thermal resistance R_{thJ-C} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.042	0.030	K/W	T _J = T _J max.
120°	0.050	0.052		
90°	0.064	0.070		
60°	0.095	0.100		
30°	0.164	0.165		

Ordering Information Table

Device Code

- 1** - $I_{TAV} \times 10A$
- 2** - 0 = Eyelet terminals (Gate and Auxiliary Cathode Leads)
1 = Fast - on terminals (Gate and Auxiliary Cathode Leads)
- 3** - RIA = Essential part number
- 4** - Voltage code: Code $\times 10 = V_{RRM}$ (See Voltage Rating Table)
- 5** - None = Stud base 1/2"-20UNF- 2A threads

NOTE: For Metric Device M12 x 1.75 E6 Contact factory

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics




Fig. 9 - Gate Characteristics

80RIA Series

Bulletin I25201 rev. B 03/03

International
IOR Rectifier

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 03/03

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com