

RTV Silicones

[One Part](#)
[Two Part](#)
[Primers](#)
[Selection Guides](#)

ALL MG PRODUCTS ▾

[Accessories](#)
[Adhesives](#)
[Brushes](#)
[Cleaners / Degreasers](#)
[Contact Cleaners](#)
[Desoldering Braid](#)
[Dusters & Circuit Coolers](#)
[EMI / RFI Shielding](#)
[Epoxyes](#)
[Flux and Flux Remover](#)
[Glass & Screen Cleaners](#)
[Lubricants](#)
[Potting & Encapsulating](#)
[Protective Coatings](#)
[Pens](#)
[Prototyping Materials](#)
[RTV Silicones](#)
[Specialized Cleaners](#)
[Swabs](#)
[Thermal Management](#)
[Thermally Conductive Adhesives](#)
[Wipes](#)

RTV Silicones by

2-Part Potting/Encapsulating Compound RTV615

[▶ STOCKED ITEM](#)
[▶ BUY NOW](#)

Primary Characteristics

▶ **Optically Clear**

▶ Easily pourable

▶ **Addition cure**

▶ **Primer** required

▶ FDA Approved

Use for:

▶ Solar cell potting

▶ Optical instruments

▶ Applications requiring

visual identification of

potted assemblies

▶ Food applications

Excellent for potting solar cells for maximum light transmission and electronic assemblies where component identification is desirable. This two part silicone is supplied with a curing agent. [Primer](#) required. Cures at room temperature. Has low viscosity allowing easy flow in and around complex parts, providing excellent electrical insulation and shock resistance. Clarity permits visual inspection for easy identification and repair of encapsulated parts. Excellent retention of elastomeric properties at temperatures up to 204°C (400°F). Will cure in deep sections or enclosed assemblies without exotherm and with low shrinkage. Can be used in food contact applications where FDA 21 CFR 177.2600 regulations apply.

Available Sizes

Catalog Number	Sizes Available	Description
RTV615-1P	1 pint	1 lb kit
RTV615-1G	1 gallon	10 lbs. kit
RTV615-5G	5 gallon	44 lbs. kit
RTV615 requires a primer. Visit our primer guide for details.		

Specifications

Use	Adhesive Sealant
Special Feature	High tensile strength Optically Clear
Standards	FDA 21CFR 177.2600
Cross Reference	RTV615
Uncured Properties	
Consistency	Easily pourable
Color	Optical clear
Specific Gravity	1.05
Tack Free Time	4 hours
Cure Through Time	6 - 7 days @ 25°C 15 min @ 150°C

Quick Links

- ▶ [MSDS](#)
- ▶ [Catalyst options/MSDS](#)
- ▶ [Primer options/MSDS](#)
- ▶ [Specifications](#)
- ▶ [Available Sizes](#)
- ▶ [Handling & Safety](#)
- ▶ [Application](#)
- ▶ [Surface Preparation](#)
- ▶ [Warranty](#)

Related products:

-  [RTV103 Black](#)
-  [RTV108 Translucent](#)
-  [RTV109 Aluminum](#)

Find by Product Number



Resources

- [What are RTV Silicones? >](#)
- [Application Guide >](#)
- [Product Data Spreadsheet >](#)

Find by Application

- [General Purpose >](#)
- [Aerospace >](#)
- [Marine >](#)
- [High Performance Assembly >](#)
- [Electronics >](#)
- [Thermal Conductivity >](#)
- [High Temperature >](#)
- [Low Temperature >](#)



Useful Temp. Range	-60°C to 205°C (-75°F to 400°F)
Cured Properties - MECHANICAL	
Hardness	44 (Shore A)
Tensile Strength	6.37 MPa (920 psi)
Elongation	120%
Cured Properties - ELECTRICAL	
Volume Resistivity	1.8×10^{15} ohm · cm
Dielectric Strength	19.7 kV/mm
	500 V/mil
Dielectric Constant	2.7 @ 1000 Hz
Cured Properties - THERMAL	
Thermal Conductivity	0.19 W/m · °K
Brittle Point	-60°C (-75°F)
Thermal Expansion	27×10^{-5} (°C) ⁻¹
Other	
Viscosity (@ 25°C)	4,000 cps
Mix Ratio (by weight)	10 : 1
Pot Life	4 hours
Index of Refraction	1.406

[Return to top](#) ^