

# Fuse Blocks, Holders and Accessories

Class J POWR-SAFE Holders

NEW



Littelfuse POWR-SAFE “Dead Front” fuseholders provide optimum protection to personnel. An integral DIN-Rail adapter system allows fuse holders to be mounted on 35mm DIN-Rail without the use of tools or special parts. Indicating and non-indicating versions are available in 1, 2, or 3 poles for Class J fuses.

## SPECIFICATIONS

**Voltage Rating:** 600 VAC

**Interrupting Rating:** 200 kA

**Ampere Rating:** 30 and 60 amperes

**Terminal Type:** Pressure plate

**Suggested Torque:** 30A – 35 inch-pounds  
60A – 45 inch-pounds

**Wire Range:** #2 – #14CU

**Material:** Thermo-plastic

**Flammability Rating:** 94V0

**Approvals:** UL Listed  
CSA Certified  
IEC Type IP20 Protection  
CE

## FEATURES/BENEFITS

- Meets “Dead Front” requirements and IEC Type IP20 protection.
- Mountable on 35mm DIN-Rail.
- Blown fuse identification (Indicating versions only).
- Easy installation and removal of fuses. No special fuse pullers or tools required.
- UL listed for branch circuit protection.
- Ventilated design for cooler operation.

## ORDERING INFORMATION

| Littelfuse Catalog No. | Littelfuse System No. | No. of Poles | Pack Qty. | Voltage Rating | Ampere Rating | Options    |
|------------------------|-----------------------|--------------|-----------|----------------|---------------|------------|
| LPSJ30-1               | LPSJ301.Z             | 1            | 6         | 600V           | 30A           | —          |
| LPSJ30-2               | LPSJ302.Z             | 2            | 3         | 600V           | 30A           | —          |
| LPSJ30-3               | LPSJ303.Z             | 3            | 2         | 600V           | 30A           | —          |
| LPSJ30-1ID             | LPSJ301.ZXID          | 1            | 6         | 600V           | 30A           | Indicating |
| LPSJ30-2ID             | LPSJ302.ZXID          | 2            | 3         | 600V           | 30A           | Indicating |
| LPSJ30-3ID             | LPSJ303.ZXID          | 3            | 2         | 600V           | 30A           | Indicating |
| LPSJ60-1               | LPSJ601.Z             | 1            | 6         | 600V           | 60A           | —          |
| LPSJ60-2               | LPSJ602.Z             | 2            | 3         | 600V           | 60A           | —          |
| LPSJ60-3               | LPSJ603.Z             | 3            | 2         | 600V           | 60A           | —          |
| LPSJ60-1ID             | LPSJ601.ZXID          | 1            | 6         | 600V           | 60A           | Indicating |
| LPSJ60-2ID             | LPSJ602.ZXID          | 2            | 3         | 600V           | 60A           | Indicating |
| LPSJ60-3ID             | LPSJ603.ZXID          | 3            | 2         | 600V           | 60A           | Indicating |

Contact Littelfuse for dimensions.

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)