



November 1999  
Revised March 2005

## 74LVT2245 • 74LVTH2245

# Low Voltage Octal Bidirectional Transceiver with 3-STATE Inputs/Outputs and 25Ω Series Resistors in the B Port Outputs

## General Description

The LVT2245 and LVTH2245 contain eight non-inverting bidirectional buffers with 3-STATE outputs and are intended for bus-oriented applications. The Transmit/Receive (T/R) input determines the direction of data flow through the bidirectional transceiver. Transmit (active-HIGH) enables data from A Ports to B Ports; Receive (active-LOW) enables data from B Ports to A Ports. The Output Enable input, when HIGH, disables both A and B Ports by placing them in a high impedance state. The equivalent 25Ω-series resistor in the B Port helps reduce output overshoot and undershoot.

The LVTH2245 data inputs include bushold, eliminating the need for external pull-up resistors to hold unused inputs.

These transceivers are designed for low voltage (3.3V)  $V_{CC}$  applications, but with the capability to provide a TTL interface to a 5V environment. The LVT2245 and LVTH2245 are fabricated with an advanced BiCMOS technology to achieve high speed operation similar to 5V ABT while maintaining low power dissipation.

## Features

- Input and output interface capability to systems at 5V  $V_{CC}$
- Equivalent 25Ω series resistor on B Port outputs
- Bushold data inputs eliminate the need for external pull-up resistors to hold unused inputs (74LVTH2245), also available without bushold feature (74LVT2245)
- Live insertion/extraction permitted
- Power Up/Down high impedance provides glitch-free bus loading
- Outputs source/sink -12 mA/+12 mA on B Port, -32 mA/+64 mA on A Port
- Latch-up performance exceeds 500 mA
- ESD performance:  
Human-body model > 2000V  
Machine model > 200V  
Charged-device model > 1000V

## Ordering Code:



| Order Number               | Package Number | Package Description                                                                 |
|----------------------------|----------------|-------------------------------------------------------------------------------------|
| 74LVT2245WM                | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide          |
| 74LVT2245SJ                | M20D           | Pb-Free 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74LVT2245MSA               | MSA20          | 20-Lead Shrink Small Outline Package (SSOP), JEDEC MO-150, 5.3mm Wide               |
| 74LVT2245MTC               | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide         |
| 74LVT2245MTCX_NL (Note 1)  | MTC20          | Pb-Free 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| 74LVTH2245WM               | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide          |
| 74LVTH2245SJ               | M20D           | Pb-Free 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74LVTH2245MSA              | MSA20          | 20-Lead Shrink Small Outline Package (SSOP), JEDEC MO-150, 5.3mm Wide               |
| 74LVTH2245MTC              | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide         |
| 74LVTH2245MTCX_NL (Note 1) | MTC20          | Pb-Free 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code.  
Pb-Free package per JEDEC J-STD-020B.


**Note 1:** "\_NL" indicates Pb-Free package (per JEDEC J-STD-020B). Device available in Tape and Reel only.

74LVT2245 • 74LVTH2245 Low Voltage Octal Bidirectional Transceiver with 3-STATE Inputs/Outputs and 25Ω Series Resistors in the B Port Outputs

Logic Symbols



Connection Diagram



Pin Descriptions

| Pin Names        | Description                      |
|------------------|----------------------------------|
| $\overline{OE}$  | Output Enable Input              |
| $T/\overline{R}$ | Transmit/Receive Input           |
| $A_0-A_7$        | Side A Inputs or 3-STATE Outputs |
| $B_0-B_7$        | Side B Inputs or 3-STATE Outputs |

Truth Table

| Inputs          |                  | Outputs             |
|-----------------|------------------|---------------------|
| $\overline{OE}$ | $T/\overline{R}$ |                     |
| L               | L                | Bus B Data to Bus A |
| L               | H                | Bus A Data to Bus B |
| H               | X                | HIGH-Z State        |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial

**Absolute Maximum Ratings**(Note 2)

| Symbol    | Parameter                        | Value        | Conditions                           | Units |
|-----------|----------------------------------|--------------|--------------------------------------|-------|
| $V_{CC}$  | Supply Voltage                   | −0.5 to +4.6 |                                      | V     |
| $V_I$     | DC Input Voltage                 | −0.5 to +7.0 |                                      | V     |
| $V_O$     | Output Voltage                   | −0.5 to +7.0 | Output in 3-STATE                    | V     |
|           |                                  | −0.5 to +7.0 | Output in HIGH or LOW State (Note 3) |       |
| $I_{IK}$  | DC Input Diode Current           | −50          | $V_I < GND$                          | mA    |
| $I_{OK}$  | DC Output Diode Current          | −50          | $V_O < GND$                          | mA    |
| $I_O$     | DC Output Current                | 64           | $V_O > V_{CC}$ Output at HIGH State  | mA    |
|           |                                  | 128          | $V_O > V_{CC}$ Output at LOW State   |       |
| $I_{CC}$  | DC Supply Current per Supply Pin | ±64          |                                      | mA    |
| $I_{GND}$ | DC Ground Current per Ground Pin | ±128         |                                      | mA    |
| $T_{STG}$ | Storage Temperature              | −65 to +150  |                                      | °C    |

**Recommended Operating Conditions**

| Symbol              | Parameter                                               | Min | Max        | Units |
|---------------------|---------------------------------------------------------|-----|------------|-------|
| $V_{CC}$            | Supply Voltage                                          | 2.7 | 3.6        | V     |
| $V_I$               | Input Voltage                                           | 0   | 5.5        | V     |
| $I_{OH}$            | HIGH-Level Output Current                               |     | A Port −32 | mA    |
|                     |                                                         |     | B Port −12 |       |
| $I_{OL}$            | LOW-Level Output Current                                |     | A Port 64  | mA    |
|                     |                                                         |     | B Port 12  |       |
| $T_A$               | Free Air Operating Temperature                          | −40 | +85        | °C    |
| $\Delta t/\Delta V$ | Input Edge Rate, $V_{IN} = 0.8V-2.0V$ , $V_{CC} = 3.0V$ | 0   | 10         | ns/V  |

**Note 2:** Absolute Maximum continuous ratings are those values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute maximum rated conditions is not implied.

**Note 3:**  $I_O$  Absolute Maximum Rating must be observed.

## DC Electrical Characteristics

| Symbol                           | Parameter                                           | V <sub>CC</sub><br>(V) | T <sub>A</sub> = -40°C to +85°C |                      | Units | Conditions                                                                    |
|----------------------------------|-----------------------------------------------------|------------------------|---------------------------------|----------------------|-------|-------------------------------------------------------------------------------|
|                                  |                                                     |                        | Min                             | Max                  |       |                                                                               |
| V <sub>IK</sub>                  | Input Clamp Diode Voltage                           | 2.7                    |                                 | -1.2                 | V     | I <sub>I</sub> = -18 mA                                                       |
| V <sub>IH</sub>                  | Input HIGH Voltage                                  | 2.7–3.6                | 2.0                             |                      | V     | V <sub>O</sub> ≤ 0.1V or                                                      |
| V <sub>IL</sub>                  | Input LOW Voltage                                   | 2.7–3.6                |                                 | 0.8                  | V     | V <sub>O</sub> ≥ V <sub>CC</sub> - 0.1V                                       |
| V <sub>OH</sub>                  | Output HIGH Voltage                                 | A Port                 | 2.7                             | 2.4                  | V     | I <sub>OH</sub> = -8 mA                                                       |
|                                  |                                                     |                        | 3.0                             | 2.0                  |       | I <sub>OH</sub> = -32 mA                                                      |
|                                  |                                                     | B Port                 | 3.0                             | 2.0                  | V     | I <sub>OH</sub> = -12 mA                                                      |
|                                  |                                                     |                        | 2.7–3.6                         | V <sub>CC</sub> -0.2 | V     | I <sub>OH</sub> = -100 μA                                                     |
| V <sub>OL</sub>                  | Output LOW Voltage                                  | A Port                 | 2.7                             | 0.5                  | V     | I <sub>OL</sub> = 24 mA                                                       |
|                                  |                                                     |                        | 3.0                             | 0.4                  |       | I <sub>OL</sub> = 16 mA                                                       |
|                                  |                                                     |                        | 3.0                             | 0.5                  |       | I <sub>OL</sub> = 32 mA                                                       |
|                                  |                                                     |                        | 3.0                             | 0.55                 |       | I <sub>OL</sub> = 64 mA                                                       |
|                                  |                                                     | B Port                 | 3.0                             | 0.8                  | V     | I <sub>OL</sub> = 12 mA                                                       |
|                                  |                                                     |                        | 2.7                             | 0.2                  | V     | I <sub>OL</sub> = 100 μA                                                      |
| I <sub>I(HOLD)</sub><br>(Note 4) | Bushold Input Minimum Drive                         | 3.0                    | 75                              |                      | μA    | V <sub>I</sub> = 0.8V                                                         |
|                                  |                                                     |                        | -75                             |                      |       | V <sub>I</sub> = 2.0V                                                         |
| I <sub>I(OD)</sub><br>(Note 4)   | Bushold Input Over-Drive<br>Current to Change State | 3.0                    | 500                             |                      | μA    | (Note 5)                                                                      |
|                                  |                                                     |                        | -500                            |                      |       | (Note 6)                                                                      |
| I <sub>I</sub>                   | Input Current                                       | Control Pins           | 3.6                             | 10                   | μA    | V <sub>I</sub> = 5.5V                                                         |
|                                  |                                                     |                        | 3.6                             | ±1                   |       | V <sub>I</sub> = 0V or V <sub>CC</sub>                                        |
|                                  |                                                     | Data Pins              | 3.6                             | -5                   |       | V <sub>I</sub> = 0V                                                           |
|                                  |                                                     |                        |                                 | 1                    |       | V <sub>I</sub> = V <sub>CC</sub>                                              |
| I <sub>OFF</sub>                 | Power Off Leakage Current                           | 0                      |                                 | ±100                 | μA    | 0V ≤ V <sub>I</sub> or V <sub>O</sub> ≤ 5.5V                                  |
| I <sub>PUPD</sub>                | Power Up/Down<br>3-STATE Current                    | 0–1.5V                 |                                 | ±100                 | μA    | V <sub>O</sub> = 0.5V to 3.0V<br>V <sub>I</sub> = GND or V <sub>CC</sub>      |
| I <sub>OZL</sub>                 | 3-STATE Output Leakage Current                      | 3.6                    |                                 | -5                   | μA    | V <sub>O</sub> = 0.5V                                                         |
| I <sub>OZL</sub> (Note 4)        | 3-STATE Output Leakage Current                      | 3.6                    |                                 | -5                   | μA    | V <sub>O</sub> = 0.0V                                                         |
| I <sub>OZH</sub>                 | 3-STATE Output Leakage Current                      | 3.6                    |                                 | 5                    | μA    | V <sub>O</sub> = 3.0V                                                         |
| I <sub>OZH</sub> (Note 4)        | 3-STATE Output Leakage Current                      | 3.6                    |                                 | 5                    | μA    | V <sub>O</sub> = 3.6V                                                         |
| I <sub>OZH</sub> <sup>+</sup>    | 3-STATE Output Leakage Current                      | 3.6                    |                                 | 10                   | μA    | V <sub>CC</sub> < V <sub>O</sub> ≤ 5.5V                                       |
| I <sub>CCH</sub>                 | Power Supply Current                                | 3.6                    |                                 | 0.19                 | mA    | Outputs High                                                                  |
| I <sub>CCL</sub>                 | Power Supply Current                                | 3.6                    |                                 | 5                    | mA    | Outputs Low                                                                   |
| I <sub>CCZ</sub>                 | Power Supply Current                                | 3.6                    |                                 | 0.19                 | mA    | Outputs Disabled                                                              |
| I <sub>CCZ</sub> <sup>+</sup>    | Power Supply Current                                | 3.6                    |                                 | 0.19                 | mA    | V <sub>CC</sub> ≤ V <sub>O</sub> ≤ 5.5V,<br>Outputs Disabled                  |
| ΔI <sub>CC</sub>                 | Increase in Power Supply Current<br>(Note 7)        | 3.6                    |                                 | 0.2                  | mA    | One Input at V <sub>CC</sub> - 0.6V<br>Other Inputs at V <sub>CC</sub> or GND |

**Note 4:** Applies to Bushold versions only (74LVTH2245).

**Note 5:** An external driver must source at least the specified current to switch from LOW-to-HIGH.

**Note 6:** An external driver must sink at least the specified current to switch from HIGH-to-LOW.

**Note 7:** This is the increase in supply current for each input that is at the specified voltage level rather than V<sub>CC</sub> or GND.

## Dynamic Switching Characteristics (Note 8)

| Symbol           | Parameter                                    | V <sub>CC</sub><br>(V) | T <sub>A</sub> = 25°C |      |     | Units | Conditions<br>C <sub>L</sub> = 50 pF, R <sub>L</sub> = 500Ω |
|------------------|----------------------------------------------|------------------------|-----------------------|------|-----|-------|-------------------------------------------------------------|
|                  |                                              |                        | Min                   | Typ  | Max |       |                                                             |
| V <sub>OLP</sub> | Quiet Output Maximum Dynamic V <sub>OL</sub> | 3.3                    |                       | 0.8  |     | V     | (Note 9)                                                    |
| V <sub>OLV</sub> | Quiet Output Minimum Dynamic V <sub>OL</sub> | 3.3                    |                       | -0.8 |     | V     | (Note 9)                                                    |

**Note 8:** Characterized in SOIC package. Guaranteed parameter, but not tested.

**Note 9:** Max number of outputs defined as (n). n-1 data inputs are driven 0V to 3V. Output under test held LOW.

## AC Electrical Characteristics

| Symbol            | Parameter                                 | T <sub>A</sub> = -40°C to +85°C<br>C <sub>L</sub> = 50 pF, R <sub>L</sub> = 500Ω |     |                        |     | Units |
|-------------------|-------------------------------------------|----------------------------------------------------------------------------------|-----|------------------------|-----|-------|
|                   |                                           | V <sub>CC</sub> = 3.3V ± 0.3V                                                    |     | V <sub>CC</sub> = 2.7V |     |       |
|                   |                                           | Min                                                                              | Max | Min                    | Max |       |
| t <sub>PLH</sub>  | Propagation Delay Data to B Port Output   | 1.2                                                                              | 4.4 | 1.2                    | 5.1 | ns    |
| t <sub>PHL</sub>  |                                           | 1.2                                                                              | 4.4 | 1.2                    | 5.1 |       |
| t <sub>PLH</sub>  | Propagation Delay Data to A Port Output   | 1.2                                                                              | 3.6 | 1.2                    | 4.0 | ns    |
| t <sub>PHL</sub>  |                                           | 1.2                                                                              | 3.5 | 1.2                    | 4.0 |       |
| t <sub>PZH</sub>  | Output Enable Time for B Port Output      | 1.3                                                                              | 6.2 | 1.3                    | 7.3 | ns    |
| t <sub>PZL</sub>  |                                           | 1.7                                                                              | 6.2 | 1.7                    | 7.3 |       |
| t <sub>PZH</sub>  | Output Enable Time for A Port Output      | 1.3                                                                              | 5.5 | 1.3                    | 7.1 | ns    |
| t <sub>PZL</sub>  |                                           | 1.7                                                                              | 5.7 | 1.7                    | 6.7 |       |
| t <sub>PHZ</sub>  | Output Disable Time for B Port Output     | 2.0                                                                              | 5.9 | 2.0                    | 6.5 | ns    |
| t <sub>PLZ</sub>  |                                           | 2.0                                                                              | 5.4 | 2.0                    | 5.7 |       |
| t <sub>PHZ</sub>  | Output Disable Time for A Port Output     | 2.0                                                                              | 5.9 | 2.0                    | 6.5 | ns    |
| t <sub>PLZ</sub>  |                                           | 2.0                                                                              | 5.0 | 2.0                    | 5.1 |       |
| t <sub>OSHL</sub> | A Port Output to Output Skew<br>(Note 10) |                                                                                  | 1.0 |                        | 1.0 | ns    |
| t <sub>OSLH</sub> |                                           |                                                                                  |     |                        |     |       |
| t <sub>OSHL</sub> | B Port Output to Output Skew<br>(Note 10) |                                                                                  | 1.0 |                        | 1.0 | ns    |
| t <sub>OSLH</sub> |                                           |                                                                                  |     |                        |     |       |


**Note 10:** Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW ( $t_{OSHL}$ ) or LOW-to-HIGH ( $t_{OSLH}$ ).

## Capacitance (Note 11)

| Symbol    | Parameter                | Conditions                                   | Typical | Units |
|-----------|--------------------------|----------------------------------------------|---------|-------|
| $C_{IN}$  | Input Capacitance        | $V_{CC} = 0V, V_I = 0V \text{ or } V_{CC}$   | 4       | pF    |
| $C_{I/O}$ | Input/Output Capacitance | $V_{CC} = 3.0V, V_O = 0V \text{ or } V_{CC}$ | 8       | pF    |




**Note 11:** Capacitance is measured at frequency  $f = 1\text{ MHz}$ , per MIL-STD-883, Method 3012.

# Physical Dimensions inches (millimeters) unless otherwise noted





20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  
Package Number M20B

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS




**NOTES:**

- CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.



M20DRevB1

**Pb-Free 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D**






# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS

## NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.



MTC20REV D1

**20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide Package Number MTC20**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)