

Smart Pro Expandable Tower UPS System

Intelligent, line-interactive network power management system



Cisco
Compatible

Cisco Systems
Technology
Developer
Partner

Model #: SMART3000VS

- ▶ 3000VA line interactive tower UPS system
- ▶ Enhanced communication ports (2 USB / 2 DB9), free PowerAlert software and cabling, slot for SNMP/Web card
- ▶ Corrects brownouts and overvoltages from 79 to 147V
- ▶ 3 load banks, 10 outlets (5-15, 5-20, L5-30)
- ▶ Expandable runtime with optional BP48V18
- ▶ \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Enterprise Assistance

E-mail us your critical extended run application requirements for large kVA and extended run UPS Systems and we will research the ideal solution and provide a custom configuration.

[Contact a Tripp Lite Product Specialist](#)

DESCRIPTION

Tripp Lite's SMART 3000VS intelligent, line interactive UPS with expandable runtime protects server, networking and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Small footprint, tower UPS system occupies only 106 square inches of floorspace with a height of only 14.25 inches. Large capacity 3000 VA / 2250 watt rated UPS system offers 4 minutes runtime at full load and 14 minutes at half load during power failures. Runtime is expandable with optional BP48V18 external battery packs. Line interactive voltage regulation corrects brownouts as low as 79V and overvoltages as high as 147V to fully regulated 120V nominal output for smooth continuous operation of connected equipment. Includes a total of 10 outlets, 3 of which can be individually powered off and back on via software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for more critical loads. Includes slot for internal SNMPWEBCARD, plus 2 DB9 and 2 USB enhanced monitoring ports for unattended shutdown, remote control and monitoring of UPS system and power data. Ships in attractive gray color scheme. Compatible with Tripp Lite's PowerAlert and Watchdog service software. 2 year warranty. \$250,000 connected equipment insurance.

KEY BUYING POINTS

- 3000VA / 2250 watt output capacity accommodates a variety of server, networking and telecom devices
- High power density 3kVA UPS system occupies only 106 square inches of floorspace with a height of only 14.25 inches
- Compatible with North American 120V / 60 Hz power as found in the USA, Canada and Mexico
- Offers 4 minutes runtime with a full load of 3000VA and 14 minutes with a half load of 1500VA
- Supports extended runtime operation with optional BP48V18 battery packs
- Line interactive voltage regulation corrects severe brownouts and overvoltages from 79 to 147v back to normal 120v levels without using battery power
- 10 total outlets (7 NEMA5-15R; 2 NEMA5-15/20R; 1 L5-30R)
- Includes NEMA L5-30P locking 30 amp input plug connection; includes user installable NEMA 5-20P replacement plug to enable connection to a 20A circuit
- Notification of system status via 5 LEDs and multi-function audible alarms
- Included PowerAlert Software provides e-mail notification of power problems and the simultaneous automatic unattended shutdown of multiple servers
- 4 built-in communications ports (2-DB9, 2-USB) for remote monitoring and unattended shutdown
- Slot for SNMP/web card (part#: SNMPWEBCARD) and environmental sensor (part#: ENVIROSENSE) for remote communications in large IP environments
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again
- Communication ports support on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status messaging. Interface supports timed inverter

- shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment
- 3 individual customized load management receptacles can be individually powered off and back on again via software interface to reboot remote equipment or perform "load shedding" of less critical loads to extend battery runtime for the most critical equipment
- Built-in Emergency Power Off (EPO) interface supports emergency shutoff in large facilities
- Hot-swappable / user replaceable batteries allow on-site battery replacement through the front panel without powering off connected equipment or removing the UPS from the rack
- UPS battery set ships fully assembled and ready for use, no time consuming, connection of individual internal batteries by user is necessary
- UL (USA), cUL (Canada), NOM (Mexico), FCC Class A
- \$250,000 Ultimate Lifetime Insurance. No warranty cards required for coverage!
- 2 year manufacturer's product warranty

TYPICAL APPLICATIONS

- Ideal for protection of sensitive electronics in any application calling for upright tower UPS protection. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems.

OPTIONS & ACCESSORIES

- External battery pack: [BP48V18](#)
- SNMP accessories: [SNMPWEBCARD](#), [ENVIROSENSE](#)
- Watchdog software: [WATCHDOGSW](#)
- USB Hubs-accessories: [U202-004-R](#), [U205-004-R](#), [U022-010](#)
- Dataline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Circuit Tester: [CT120](#)
- Power distribution: [PDU1220](#), [PS7224-20](#), [PDU2430](#)
- Extended warranties: 3 Year [WEXT3-2200-3000](#), 5 Year [WEXT5-2200-3000](#)

PACKAGE INCLUDES

- SMART 3000VS UPS System, PowerAlert Software and cabling, Warranty information, Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

Line interactive tower UPS protects internetworking and telecommunications equipment from blackouts, brownouts, overvoltages, surges and line noise. Maintains AC output during blackouts and continuously corrects brownouts and overvoltages from 75 to 147 volts back to normal 120V levels. Supports enhanced monitoring of UPS and line power conditions via two USB and two DB9 serial ports, included PowerAlert monitoring software and complete cabling. Includes three individually controllable output load banks. SNMP compatible. Runtime is expandable with optional BP48V18 battery packs.

Voltage compatibility: 120V AC

Frequency compatibility: 60 Hz

OUTPUT

Output volt amp capacity (VA): 3000

Output watt capacity (watts): 2250

Output nominal voltage: 120V AC

Output voltage regulation: LINE MODE: Sine wave line voltage 120V (-18% / +8%), BATTERY MODE: PWM sine wave output 120V +/-5%

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output

	regulated to 60Hz +/-0.5Hz
Outlet quantity / type:	7 NEMA 5-15R, 2 NEMA 5-20R and 1 NEMA L5-30R
Customized load management receptacles:	3 individually controllable outlets support load shedding and remote reboot on demand of locked network devices. Controllable via PowerAlert software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices.
Overload protection:	Via 30A input breaker and 2 15A output breakers

INPUT

Maximum input amps:	24 amps
Input connection type:	NEMA L5-30P
Input cord length:	8 ft.
Recommended electrical service:	120V 30A

BATTERY

Full load runtime:	4 minutes (add 1 BP48V18 for 20 minutes)
Half load runtime:	14 minutes (add 1 BP48V18 for 45 minutes)
Expandable battery runtime:	Supports extended runtime with optional BP48V18 external battery pack (multi-pack compatible)
DC system voltage:	48 VDC
Typical battery lifespan:	3-6 years, depending on usage
Battery recharge rate:	2-4 hours to 90%
Replacement Battery Cartridge:	RBC54

VOLTAGE REGULATION

Voltage regulation description:	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 79V and overvoltages to 147V
Overvoltage correction:	Input voltages between 128 and 147VAC are reduced by 12%
Direct pass through:	Input voltages between 105 and 127VAC are passed on to connected equipment unchanged
Brownout correction:	Input voltages between 95 and 104VAC are boosted by 12%
Severe brownout correction:	Input voltages between 79 and 94VAC are boosted by 24%

LEDS ALARMS & SWITCHES

Front panel LEDs:	Includes 5 front panel LEDs to indicate BATTERY CHARGE LEVEL, AC LINE POWER STATUS, VOLTAGE REGULATION STATUS, UPS LOAD LEVEL and BATTERY LOW / REPLACE information
Alarms:	3 function audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)
Switches:	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions. Also includes rear panel CHARGE LEVEL switch.

SURGE / NOISE SUPPRESSION

AC surge suppression:	480 joules
AC suppression response time:	Instantaneous
EMI / RFI AC noise suppression:	Yes

PHYSICAL

Shipping weight (lbs):	66
Shipping weight (kg):	30
Unit weight (lbs):	59
Unit weight (kg):	26.8

Unit Dimensions (HWD/in):	14.25 x 9.25 x 12
Unit Dimensions (HWD/cm):	36.2 x 23.5 x 30.5
Shipping Dimensions (HWD/in):	16 x 14.75 x 19.75
Shipping Dimensions (HWD/cm):	40.6 x 37.5 x 50.2
Material of construction:	Polycarbonate
Form factors supported:	Tower
Cooling method:	Built-in cooling fan
Battery Access:	Battery access door enables user battery replacement, hot-swappable battery replacement supported

ENVIRONMENTAL

Operating Temperature:	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing

COMMUNICATIONS

Network monitoring port:	Includes 4 built-in monitoring ports, 2-USB & 2-DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status messaging. Interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment. Supports individual reboot of selected items connected to load management receptacles and load shedding to increase battery runtime for the most critical loads. Compatible with Tripp Lite's PowerAlert and Watchdog service software.
Software and cabling included:	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Ships with 2 USB and 2 DB9 serial cables
SNMP compatibility:	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories
WatchDog compatibility:	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	79V (resets to line power as voltage increases to 82V)
High voltage transfer to battery power:	147V (resets to line power as voltage decreases to 143V)

CERTIFICATIONS

Certifications:	UL1778 (USA), cUL (Canada), FCC Class A (emissions), NOM (Mexico)
------------------------	-------------------------------------------------------------------

WARRANTY

Optional coverage:	3 year, 5 year, next day and on-site warranty coverage available for select opportunities - contact Tripp Lite for more information
Product warranty:	2 year product warranty
Connected equipment insurance (USA and Canada Only):	\$250,000 connected equipment insurance (USA / Canada only)

SPECIAL FEATURES

EPO port:	Includes RJ11 EPO (emergency power off) port and interconnection cable
Appearance:	Attractive gray tower UPS

BATTERY PACK ACCESSORY (optional)

Battery Pack Accessory (optional):	BP48V18
-------------------------------------------	---------

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.