

SS7619-15

- ▶ 24 outlets
- ▶ 15-ft. cord
- ▶ 72-in. length

- ▶ 450-joule rating



DESCRIPTION

The SS7619-15 6-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 24 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 6-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

KEY BUYING POINTS

- Long 6-ft./72-in. strip offers convenient power distribution and surge suppression in equipment racks, computer rooms, workbenches, raceways and more
- Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Adjustable mounting clips support installation in a variety of applications
- UL1363/1449—400V (USA), cUL (Canada)
- 15A power handling capacity with circuit breaker
- 450-joule AC surge suppression
- 15-ft. AC line cord

TYPICAL APPLICATIONS

- Offers outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

PACKAGE INCLUDES

- SS7619-15 Power Strip / Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:	6-ft. power strip with AC surge suppression and 15A resettable circuit breaker
Voltage compatibility:	120 VAC
Frequency compatibility:	50/60 Hz

OUTPUT

Output volt amp capacity (amps):	15A
Output watt capacity (watts):	1800
Outlet quantity / type:	24 NEMA 5-15R output receptacles
Outlet spacing:	2.795-in. (center to center)

INPUT

Input connection type:	NEMA 5-15P input plug
Input cord length (ft.):	15
Input cord length (m):	4.6
Input cord gauge, type:	14 gauge, SJT
Recommended electrical service:	120V 15A

LEDS ALARMS & SWITCHES

Switches:	Lighted two-position power switch controls power to all outlets
Locking switch cover:	Transparent locking switch cover prevents accidental shutoff

AC SURGE / NOISE SUPPRESSION

AC suppression joule rating:	450 joules
UL1499 let through rating:	400V—UL Verified

PHYSICAL

Unit Dimensions (HWD/in):	1.5 x 1.5 x 72 (6-ft. length)
Unit Dimensions (HWD/cm):	3.8 x 3.8 x 182.9
Material of construction:	Metal
Mounting accessories included:	Set of adjustable mounting clamps
Housing color:	Gray
Receptacle color:	Black
AC line cord color:	Black

CERTIFICATIONS

UL1449 1998 Rev. (AC Suppression):	UL1449
UL1363 (Power Tap):	UL1363
cUL / CSA (Canada):	cUL

WARRANTY

Product warranty:	Lifetime
-------------------	----------

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.