

Surge Suppressor

State of the art protection for every application



Model #: SPIKESTIK

- ▶ 6 right-angle outlets/6 ft. cord
- ▶ 360 joule rating

DESCRIPTION

The SPIKESTIK Surge Suppressor from Tripp Lite has 6 right-angle outlets and a 6-ft. cord. The unit has 360 joules of surge energy absorption to handle the strongest surges.

KEY BUYING POINTS

- 6 right-angle outlets
- 6-ft. cord
- Surge energy absorption: 360 joules; 27,000 amps
- 15 amp circuit breaker
- EMI/RFI noise filtering
- Keyhole supports for wall mounting
- Lifetime product warranty

TYPICAL APPLICATIONS

- Personal computers, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals, audio/visual devices, and more.

PACKAGE INCLUDES

- SPIKESTIK Surge Suppressor
- Child Safety Covers
- Instruction manual and Warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:	Personal computers, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals, audio/visual devices, and more.
Voltage compatibility:	120 VAC
Frequency compatibility:	50/60 Hz

OUTPUT

Output volt amp capacity (amps):	15
Output watt capacity (watts):	1800
Outlet quantity / type:	6 NEMA 5-15R
Transformer accomodation:	Holds up to 3 large transformer plugs

INPUT

Input connection type:	NEMA 5-15P input plug
Input cord length (ft.):	6 ft.
Input cord length (m):	1.8
Recommended electrical service:	120V,15A

LEDS ALARMS & SWITCHES

Switches:	Two position on/off power switch
-----------	----------------------------------

AC SURGE / NOISE SUPPRESSION

Protection modes:	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating:	360 joules
Clamping voltage (RMS):	150V
AC suppression response time:	< 1 ns
AC suppression surge current rating:	27,000 amps
UL1499 let through rating:	330V - UL Verified
Immunity:	Conforms to IEE 587 / ANSI C62.41

PHYSICAL

Unit Dimensions (HWD/in):	1.5 x 2.5 x 10
Unit Dimensions (HWD/cm):	3.8 x 6.4 x 25.4
Material of construction:	Plastic
Housing color:	Gray
Receptacle color:	Gray
AC line cord color:	Gray

CERTIFICATIONS

UL1449 1998 Rev. (AC Suppression):	UL1449
UL1363 (Power Tap):	UL1363
cUL / CSA (Canada):	cUL
Approvals:	Exceeds IEEE 587 category A&B specifications

WARRANTY

Product warranty:	Lifetime
-------------------	----------

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.