

SmartOnline Expandable Rack / Tower UPS System

Online, double-conversion protection for mission critical applications



Model #: SU5000RT3U

- ▶ 5000VA online 7U rack / tower UPS (3U Power Module + 2U Transformer Module + 2U Battery Pack)
- ▶ Enhanced serial communications ports, SNMP/Web card slot and EPO jack
- ▶ Maintains 208V - PLUS 120V output +/-2% during brownouts to 156 and overvoltages to 276V
- ▶ Expandable runtime with optional external battery packs
- ▶ \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Enterprise Assistance

E-mail us your critical extended run application requirements for large kVA and extended run UPS Systems and we will research the ideal solution and provide a custom configuration.

[Contact a Tripp Lite Product Specialist](#)

DESCRIPTION

Tripp Lite 5kVA Smart Online RM UPS. 5000VA on-line, double-conversion UPS for server, network and telecommunications equipment. Maintains battery-derived AC output during blackouts with active, full-time power conditioning. Fault-tolerant auto-bypass prevents unexpected service interruptions during overload or internal fault conditions. 3U power module, 2U transformer module and 2U battery pack install in 7 rack spaces. Full-time sine wave output within 2% of selectable 208V and simultaneous 120V AC. Corrects brownouts to 156V and overvoltages to 276V. Frequency regulation locks output power to 50/60Hz (+/-0.2%). Expandable runtime with optional rackmount external battery packs. Dual-conversion UPS converts raw input from AC to DC, then back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Network-grade AC surge and noise suppression. Network management interfaces include 2 DB9 ports and SNMPWEBCARD slot. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces. Includes PowerAlert monitoring software and complete cabling. Emergency Power Off (EPO) interface. Front panel LEDs and LCD readout with scroll controls support visual monitoring of all major UPS functions. Audible alarm. Self test. 4-post rackmount accessories included; 2-9USTAND and 2POSTRMKITWM accessories available. L6-30P plug-in connection; built-in output receptacles include two L6-30R, two L6-20R and twelve 5-15/20R. Power Distribution Unit (PDU) options supported. Field-replaceable, hot-swappable external battery packs. Attractive all-black color scheme. 2-year warranty and \$250,000 connected equipment insurance; extended warranty and service contracts available.

KEY BUYING POINTS

- True online, double-conversion UPS provides pure, full-time sine wave AC output free of surges, voltage fluctuations and line noise
- 5000VA / 3500 watt output power capacity with dual high / low voltage output compatible with 200-240V and 120V applications simultaneously
- 3U power module, 2U transformer module and 2U battery pack installs in any 19 inch rack enclosure using only 7 rack spaces
- Dual conversion UPS actively converts raw input from AC to DC, then back to perfect sine wave AC output with enhanced protection

from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types

- Provides perfectly regulated, sine wave output power free of line noise, transient surges and frequency variation for the most efficient operation of critical servers, networking and telecommunications equipment
- Accepts input voltages between 156 and 276, regulating output within 2% of 208 - plus 120V nominal voltage
- Supports connected equipment during blackouts for 20/8 minutes at half/full load levels, runtime is further expandable with optional external battery packs
- Network interfaces support simultaneous communications via 2 DB9 ports and SNMPWEBCARD slot
- Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, plus any number of additional servers over IP
- Communications ports support on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, AC line frequency, timed inverter shutoff, activate self-test and output power control
- Built-in Emergency Power Off (EPO) interface with cable
- Includes 17 built-in output receptacles (3 L6-30R w/one L6-30R used for transformer connection, 2 L6-20R, 12 NEMA 5-15/20R)
- L6-30P input plug-in connection
- Front panel LEDs and LCD readout with scroll button enables visual confirmation of all major UPS functions and current site electrical conditions
- Front panel switches enable power on/off control, self-test and alarm cancel functions
- Included adjustable mounting rails support installation in 4 post 19 inch rack enclosures, optional 2POSTRMKITWM supports 2 post rackmount installation
- UPS ships fully assembled in full compliance with DOT regulations, no time consuming connection of internal batteries by user is required
- Fault-tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
- 2 year manufacturer's product warranty, \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

TYPICAL APPLICATIONS

- Ideal for protection of sensitive electronics in any application calling for upright tower or 19 inch rackmount UPS protection. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems

OPTIONS & ACCESSORIES

- SNMP accessories: [SNMPWEBCARD](#), [ENVIROSENSE](#)
- AS400/iSeries Shutdown Cable Kit: [AS400 CABLE KIT](#)
- External battery pack: [BP240V10RT3U](#)
- Tower Stands: [2-9USTAND](#)
- Dataline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Two Post Rackmount Kit: [2POSTRMKITWM](#) (3 required)
- Extended warranties: 3 Year [WEXT3-5000](#), 5 Year [WEXT5-5000](#)

PACKAGE INCLUDES

- SU5000RT3U system includes one 3U power module, one 2U step-down isolation transformer module and one 2U external battery module
- PowerAlert UPS management software and complete cabling
- Mounting hardware to support each module in 4-post rackmount enclosures
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:	Online, double conversion rack / tower UPS
Voltage compatibility:	208V AC

Frequency compatibility:	50/60Hz
OUTPUT	
Output volt amp capacity (VA):	5000
Output watt capacity (watts):	3500
Output nominal voltage:	208V & 120V AC
Output voltage regulation:	Maintains pure sine wave output at all times, regulated within 2% of selected nominal output voltage, less than 5% total harmonic distortion
Output frequency regulation:	Regulates line frequency to 50/60Hz +/- 0.05Hz
Outlet quantity / type:	2 NEMA L6-30R, 2 NEMA L6-20R, 12 NEMA 5-15/20R
Overload protection:	Resettable circuit breaker
INPUT	
Maximum input amps:	24A 208V / 21A 240V
Input connection type:	NEMA L6-30P
Input cord length:	10 ft / 3 m
Recommended electrical service:	30A
BATTERY	
Full load runtime:	8 minutes (5000VA / 3500 watts)
Half load runtime:	20 minutes (2500VA / 1750 watts)
Expandable battery runtime:	Yes, with optional BP240V10RT3U external battery packs
DC system voltage:	240V DC
Typical battery lifespan:	4-6 years, depending on usage
Battery recharge rate:	2-4 hours to 90%
VOLTAGE REGULATION	
Voltage regulation description:	On-line, double-conversion process give this UPS the ability to maintain output voltage within +/-2% of selected nominal voltage at all times
Overvoltage correction:	Maintains continuous operation without using battery power during overvoltages to 276V AC, regulating output within 2% of selected nominal
Brownout correction:	Maintains continuous operation without using battery power during brownout / undervoltage conditions to 156VAC, regulating output within 2% of selected nominal
LEDS ALARMS & SWITCHES	
Front panel LEDs:	6 LED DISPLAY: line power, bypass, inverter, charger, output AC and battery operation. SELECTABLE LCD DISPLAY: input/output voltage, Hz, battery voltage and charge level and detailed warnings regarding all major UPS functions
Alarms:	Multi-function audible alarm offers notification of UPS start, backup operation, low battery, overload, UPS fault, inverter fault, DC bus fault, overtemperature, remote shutdown, shutdown imminent and shutdown complete
Switches:	Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions
PHYSICAL	
Shipping weight (lbs):	256
Shipping weight (kg):	117
Unit weight (lbs):	Power Module (42 lb), Transformer Module (57 lb), Battery Module (92 lb)
Unit weight (kg):	Power Module (20 kg), Transformer Module (26 kg), Battery Module (42 kg)
Unit Dimensions (HWD/in):	Power Module (5.25 x 17.5 x 26 in), Transformer Module (3.5 x 17.5 x 21 in), Battery Module (3.5 x 17.5 x 22.5 in)
Unit Dimensions (HWD/cm):	Power Module (13.3 x 44.5 x 66 cm), Transformer Module (8.9 x 44.5 x 53.3 cm), Battery

	Module (8.9 x 44.5 x 57.2 cm)
Material of construction:	Steel
Form factors supported:	Rack (7U)
Cooling method:	Built-in cooling fan
Battery Access:	User replaceable, hot swappable external battery pack

ENVIRONMENTAL

Operating Temperature:	+32 to +104 degrees Fahrenheit, 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit, -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing

COMMUNICATIONS

Network monitoring port:	Includes 2 built-in DB9 monitoring ports (1-RS232 / 1-contact closure)
Software and cabling included:	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Cabling included.
SNMP compatibility:	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode:	Zero, online UPS continuously converts incoming AC to DC, then back to AC. When line power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power.
Low voltage transfer to battery power:	Maintains continuous operation during undervoltages as low as 156VAC. Below this point, output is maintained utilizing battery reserves.
High voltage transfer to battery power:	Maintains continuous operation during overvoltages to 276VAC. Above this point, output is maintained utilizing battery reserves.

CERTIFICATIONS

Certifications:	UL1778 (USA), cUL (Canada), Class A (Emissions), CE, NOM (Mexico), GOST, SASO
------------------------	---

WARRANTY

Product warranty:	2 year product warranty
Connected equipment insurance (USA and Canada Only):	\$250,000 connected equipment insurance (USA and Canada only)
Optional coverage:	3 year, 5 year, next day and on-site warranty coverage available for select opportunities - contact Tripp Lite

SPECIAL FEATURES

EPO port:	Includes dedicated EPO (emergency power off) interface and cabling
Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive black steel rackmount housing

BATTERY PACK ACCESSORY (optional)

Battery Pack Accessory (optional):	BP240V10RT3U (optional)
---	-------------------------

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.