

## APC Smart-UPS 750VA USB & Serial RM 2U 120V

APC Smart-UPS, 750VA/480W, Input 120V/Output 120V, Interface Port DB-9 RS-232, SmartSlot, USB, Rack Height 2 U

Includes: CD with software, Rack Mounting Brackets, Rack Mounting support rails, Smart UPS signalling RS-232 cable, USB cable, User Manual

Part Number : **SUA750RM2U**

[Configure Now](#)

-  [Compare Models](#)
-  [Runtime Chart](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)

### Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



[\[+\] More Images](#)

## Technical Specifications

- ☐ [Output](#)
- ☐ [Input](#)
- ☐ [Batteries & Runtime](#)
- ☐ [Communications & Management](#)
- ☐ [Surge Protection and Filtering](#)
- ☐ [Physical](#)
- ☐ [Environmental](#)
- ☐ [Conformance](#)

### Options:

- [Automatic Transfer Switches](#)
- [Interface Connections](#)
- [Management Devices](#)
- [Rack Power Distribution](#)
- [Replacement Battery Cartridges](#)
- [Services](#)
- [Software](#)

### Features:

- Disconnected battery notification
- Front-access servicing
- USB connectivity

**General Features:**

- Adjustable voltage sensitivity
- Adjustable voltage-transfer points
- Audible alarms
- Automatic restart of loads after UPS shutdown
- Automatic self-test
- Boost and Trim Automatic Voltage Regulation (AVR)
- Cold-start capable
- Generator compatible
- Hot-swappable batteries
- Intelligent battery management
- LED status indicators
- Network manageable
- Power conditioning
- Predictive failure notification
- Resettable circuit breakers
- Safety-agency approved
- Serial Connectivity
- SmartSlot
- Temperature-compensated battery charging

[more details....](#)

**Topology:** Line Interactive

---

[Copyright](#) © American Power Conversion Corp., all rights reserved

---

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)