

VISHAY

SUD25N15-52

Vishay Siliconix

N-Channel 150-V (D-S) 175°C MOSFET

PRODUCT SUMMARY

V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
150	0.052 @ $V_{GS} = 10$ V	25
	0.060 @ $V_{GS} = 6$ V	23


FEATURES

- TrenchFET® Power MOSFET
- 175°C Junction Temperature
- PWM Optimized
- 100% R_g Tested

APPLICATIONS

- Primary Side Switch

TO-252




Top View

Drain Connected to Tab

Ordering Information:

SUD25N15-52

SUD25N15-52—E3 (Lead Free)



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	150	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$) ^b	I_D	25	A
		14.5	
Pulsed Drain Current	I_{DM}	50	
Continuous Source Current (Diode Conduction)	I_S	25	
Avalanche Current	I_{AR}	25	mJ
Repetitive Avalanche Energy (Duty Cycle $\leq 1\%$)	E_{AR}	31	
Maximum Power Dissipation	P_D	136 ^b	W
		3 ^a	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typical	Maximum	Unit
Junction-to-Ambient ^a	R_{thJA}	15	18	$^\circ\text{C/W}$
		40	50	
Junction-to-Case (Drain)	R_{thJC}	0.85	1.1	

Notes:

^a Surface Mounted on 1" x 1" FR4 Board.^b See SOA curve for voltage derating.

SUD25N15-52

Vishay Siliconix









SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ ^a	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 μA	150			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	2		4	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			± 100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 150 V, V _{GS} = 0 V			1	μA
		V _{DS} = 150 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 150 V, V _{GS} = 0 V, T _J = 175 °C			250	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	50			A
Drain-Source On-State Resistance ^b	r _{DS(on)}	V _{GS} = 10 V, I _D = 5 A		0.042	0.052	Ω
		V _{GS} = 10 V, I _D = 5 A, T _J = 125 °C			0.109	
		V _{GS} = 10 V, I _D = 5 A, T _J = 175 °C			0.145	
		V _{GS} = 6 V, I _D = 5 A		0.047	0.060	
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 25 A		40		S
Dynamic ^a						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, F = 1 MHz		1725		pF
Output Capacitance	C _{oss}			216		
Reverse Transfer Capacitance	C _{rss}			100		
Total Gate Charge ^c	Q _g	V _{DS} = 75 V, V _{GS} = 10 V, I _D = 25 A		33	40	nC
Gate-Source Charge ^c	Q _{gs}			9		
Gate-Drain Charge ^c	Q _{gd}			12		
Gate Resistance	R _g		1		3	Ω
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 50 V, R _L = 3 Ω I _D ≅ 25 A, V _{GEN} = 10 V, R _g = 2.5 Ω		15	25	ns
Rise Time ^c	t _r			70	100	
Turn-Off Delay Time ^c	t _{d(off)}			25	40	
Fall Time ^c	t _f			60	40	
Source-Drain Diode Ratings and Characteristic (T _C = 25 °C)						
Pulsed Current	I _{SM}				50	A
Diode Forward Voltage ^b	V _{SD}	I _F = 25 A, V _{GS} = 0 V		0.9	1.5	V
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 25 A, di/dt = 100 A/μs		95	140	ns

Notes

- Guaranteed by design, not subject to production testing.
- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Independent of operating temperature.



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





SUD25N15-52

Vishay Siliconix



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



THERMAL RATINGS

