




P-Channel 30-V (D-S), 150°C MOSFET

PRODUCT SUMMARY


V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A) ^a
-30	0.010 @ $V_{GS} = -10$ V	-15
	0.018 @ $V_{GS} = -4.5$ V	-12

TrenchFET[®]
Power MOSFETs

Top View

Order Number:
SUD45P03-10

Drain Connected to Tab



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ^b	$T_A = 25^\circ\text{C}$	I_D	-15	A
	$T_A = 100^\circ\text{C}$		-8	
Pulsed Drain Current		I_{DM}	-100	
Continuous Source Current (Diode Conduction)		I_S	-15	
Maximum Power Dissipation ^b	$T_C = 25^\circ\text{C}$	P_D	70	W
	$T_A = 25^\circ\text{C}$		4 ^b	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^b	R_{thJA}		30	$^\circ\text{C/W}$
Maximum Junction-to-Case	R_{thJC}		1.8	

Notes







- a. Calculated Rating for $T_A = 25^\circ\text{C}$, for comparison purposes only. This cannot be used as continuous rating (see Absolute Maximum Ratings and Typical Characteristics).
- b. Surface Mounted on FR4 Board, $t \leq 10$ sec.








SPECIFICATIONS (T _J = 25°C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-1.0			
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 20 V			± 100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -30 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -30 V, V _{GS} = 0 V, T _J = 125°C			-50	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -5 V, V _{GS} = -10 V	-50			A
		V _{DS} = -5 V, V _{GS} = -4.5 V	-20			
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = -10 V, I _D = -15 A			0.010	Ω
		V _{GS} = -10 V, I _D = -15 A, T _J = 125°C			0.015	
		V _{GS} = -4.5 V, I _D = -15 A			0.018	
Forward Transconductance ^a	g _{fs}	V _{DS} = -15 V, I _D = -15 A	20			S
Dynamic ^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = -25 V, f = 1 MHz		6000		pF
Output Capacitance	C _{oss}			1100		
Reverse Transfer Capacitance	C _{rss}			700		
Total Gate Charge ^c	Q _g	V _{DS} = -15 V, V _{GS} = -10 V, I _D = -45 A		90	150	nC
Gate-Source Charge ^c	Q _{gs}			20		
Gate-Drain Charge ^c	Q _{gd}			16		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = -15 V, R _L = 0.33 Ω I _D ≅ -45 A, V _{GEN} = -10 V, R _G = 2.4 Ω		15	25	ns
Rise Time ^c	t _r			375	550	
Turn-Off Delay Time ^c	t _{d(off)}			100	200	
Fall Time ^c	t _f			140	250	
Source-Drain Diode Ratings and Characteristic (T _C = 25°C)						
Pulsed Current	I _{SM}				100	A
Diode Forward Voltage ^a	V _{SD}	I _F = -45 A, V _{GS} = 0 V		1.0	1.5	V
Source-Drain Reverse Recovery Time	t _{rr}	I _F = -45 A, di/dt = 100 A/μs		55	100	ns

Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.
c. Independent of operating temperature.

**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)**

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

THERMAL RATINGS




Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.