



Cable Management Accessories

HellermannTyton manufactures a full line of quality cable ties in a wide variety of materials, colors, styles and sizes. Used to bundle and secure wire and cable, these cable ties are engineered and manufactured for maximum performance and quality.

HellermannTyton offers many options of cable ties. Whether the application demands extra strength, mounting, releasable, identification features or more, HellermannTyton has the cable tie to fit the requirement.



Standard Cable Ties

Standard cable ties include varying strengths and lengths for each individual application.

U.S. Patent Numbers 3,127,648 – 3,486,201



Product Selection

Part Number	Color	Government Designation	Min. Tensile Unlocking Strength	Max. Bundle Diameter In. (mm)	Approx. Length In. (mm)	Approx. Width In. (mm)	Pkg. Qty.	Installation Tools
T18S9C2*	Natural	MS3367-4	18 lbs.	5/8" (15.9)	3-3/8" (85.7)	.08" (2.0)	100	TWT1, MK7, MK7P
T18S0C2*	Black							MK3P
T18S9M4*	Natural	MS3367-4	18 lbs.	5/8" (15.9)	3-3/8" (85.7)	.08" (2.0)	1000	TWT1, MK7, MK7P
T18S0M4*	Black							MK3P
T18R9C2*	Natural	MS3367-4	18 lbs.	3/4" (19.0)	4" (101.6)	.10" (2.5)	100	TWT1, MK7, MK7P
T18R0C2*	Black							MK9, MK3P
T18R9M4*	Natural	MS3367-4	18 lbs.	3/4" (19.0)	4" (101.6)	.10" (2.5)	1000	TWT1, MK7, MK7P
T18R0M4*	Black							MK9, MK3P
T18I9C2***	Natural	MS3367-4	18 lbs.	1-1/4" (31.8)	5-2/3" (143.9)	.10" (2.5)	100	TWT1, MK7, MK7P
T18I0C2***	Black							MK9, MK3P
T18I9M4***	Natural	MS3367-4	18 lbs.	1-1/4" (31.8)	5-2/3" (143.9)	.10" (2.5)	1000	TWT1, MK7, MK7P
T18I0M4***	Black							MK9, MK3P
T18L9C2***	Natural	MS3367-4	18 lbs.	2" (50.8)	8" (203.2)	.10" (2.5)	100	TWT1, MK7, MK7P
T18L0C2***	Black							MK9, MK3P
T18L9M4***	Natural	MS3367-4	18 lbs.	2" (50.8)	8" (203.2)	.10" (2.5)	1000	TWT1, MK7, MK7P
T18L0M4***	Black							MK9, MK3P
T30R9C2*	Natural	MS3367-5	30 lbs.	1-1/4" (31.8)	6" (152.4)	.14" (3.6)	100	TWT1, MK7, MK7P
T30R0C2*	Black							MK9, MK3P
T30R9M4*	Natural	MS3367-5	30 lbs.	1-1/4" (31.8)	6" (152.4)	.14" (3.6)	1000	TWT1, MK7, MK7P
T30R0M4*	Black							MK9, MK3P
T30M9C2	Natural		30 lbs.	2" (50.8)	8" (203.2)	.14" (3.6)	100	TWT1, MK7, MK7P
T30M0C2	Black							MK9, MK3P
T30M9M4	Natural		30 lbs.	2" (50.8)	8" (203.2)	.14" (3.6)	1000	TWT1, MK7, MK7P
T30M0M4	Black							MK9, MK3P
T30I9C2	Natural		30 lbs.	3" (76.2)	11-3/4" (298.5)	.14" (3.8)	100	TWT1, MK7, MK7P
T30I0C2	Black							MK9, MK3P
T30I9M4	Natural		30 lbs.	3" (76.2)	11-3/4" (298.5)	.14" (3.8)	1000	TWT1, MK7, MK7P
T30I0M4	Black							MK9, MK3P
T30L9C2	Natural		30 lbs.	4" (101.6)	14-1/4" (362)	.15" (3.8)	100	TWT1, MK7, MK7P
T30L0C2	Black							MK9, MK3P
T30L9M4	Natural		30 lbs.	4" (101.6)	14-1/4" (362)	.15" (3.8)	1000	TWT1, MK7, MK7P
T30L0M4	Black							MK9, MK3P
T40R9C2*	Natural		40 lbs.	2" (50.8)	8-1/2" (215.9)	.15" (3.8)	100	TWT1, MK7, MK7P
T40R0C2*	Black							MK9, MK3P
T40R9M4*	Natural		40 lbs.	2" (50.8)	8-1/2" (215.9)	.15" (3.8)	1000	TWT1, MK7, MK7P
T40R0M4*	Black							MK9, MK3P
T40I9C2*	Natural		40 lbs.	3" (76.2)	11-1/2" (292.1)	.15" (3.8)	100	TWT1, MK7, MK7P
T40I0C2*	Black							MK9, MK3P
T40I9M4*	Natural		40 lbs.	3" (76.2)	11-1/2" (292.1)	.15" (3.8)	1000	TWT1, MK7, MK7P
T40I0M4*	Black							MK9, MK3P

Note: *AS23190E (formerly Mil-S-23190E) (Type I Class 1). ***HellermannTyton QPL23190 Listed as exceeding the tensile strength of length and meeting MS3367 (Type I Class 1). Contact HellermannTyton for other colors. Note: The official reference to the military specification is now SAE-AS23190 and SAE-AS3367.

