





Discrete POWER & Signal Technologies

## 2N4400



## MMBT4400



### NPN General Purpose Amplifier

This device is designed for use as general purpose amplifiers and switches requiring collector currents to 500 mA. Sourced from Process 19. See PN2222A for characteristics.

#### Absolute Maximum Ratings\* TA = 25°C unless otherwise noted

| Symbol         | Parameter  | Value       | Units |
|----------------|--|-------------|-------|
| $V_{CE0}$      | Collector-Emitter Voltage                        | 40          | V     |
| $V_{CB0}$      | Collector-Base Voltage                           | 60          | V     |
| $V_{EB0}$      | Emitter-Base Voltage                             | 6.0         | V     |
| $I_C$          | Collector Current - Continuous                   | 1.0         | A     |
| $T_J, T_{stg}$ | Operating and Storage Junction Temperature Range | -55 to +150 | °C    |

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

**NOTES:**

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

#### Thermal Characteristics TA = 25°C unless otherwise noted

| Symbol          | Characteristic                          | Max    |           | Units |
|-----------------|---|--------|-----------|-------|
|                 |   | 2N4400 | *MMBT4400 |       |
| $P_D$           | Total Device Dissipation                | 625    | 350       | mW    |
|                 | Derate above 25°C                       | 5.0    | 2.8       | mW/°C |
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case    | 83.3   |           | °C/W  |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 200    | 357       | °C/W  |

# NPN General Purpose Amplifier

(continued)

## Electrical Characteristics

TA = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Max | Units |
|--------|-----------|-----------------|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-------|

### OFF CHARACTERISTICS

|               |                                      |   |     |     |               |
|---------------|--------------------------------------|---|-----|-----|---------------|
| $V_{(BR)CEO}$ | Collector-Emitter Breakdown Voltage* | $I_C = 1.0 \text{ mA}, I_B = 0$                 | 40  |     | V             |
| $V_{(BR)CBO}$ | Collector-Base Breakdown Voltage     | $I_C = 100 \text{ } \mu\text{A}, I_E = 0$       | 60  |     | V             |
| $V_{(BR)EBO}$ | Emitter-Base Breakdown Voltage       | $I_E = 100 \text{ } \mu\text{A}, I_C = 0$       | 6.0 |     | V             |
| $I_{CEX}$     | Collector Cutoff Current             | $V_{CE} = 35 \text{ V}, V_{EB} = 0.4 \text{ V}$ |     | 0.1 | $\mu\text{A}$ |
| $I_{BL}$      | Emitter Cutoff Current               | $V_{CE} = 35 \text{ V}, V_{EB} = 0.4 \text{ V}$ |     | 0.1 | $\mu\text{A}$ |

### ON CHARACTERISTICS\*

|               |                                      |   |                      |              |   |
|---------------|--------------------------------------|---|----------------------|--------------|---|
| $h_{FE}$      | DC Current Gain                      | $V_{CE} = 1.0 \text{ V}, I_C = 1.0 \text{ mA}$<br>$V_{CE} = 1.0 \text{ V}, I_C = 10 \text{ mA}$<br>$V_{CE} = 1.0 \text{ V}, I_C = 150 \text{ mA}$<br>$V_{CE} = 2.0 \text{ V}, I_C = 500 \text{ mA}$ | 20<br>40<br>50<br>20 | 150          |   |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage | $I_C = 150 \text{ mA}, I_B = 15 \text{ mA}$<br>$I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$  |                      | 0.40<br>0.75 | V |
| $V_{BE(sat)}$ | Base-Emitter Saturation Voltage      | $I_C = 150 \text{ mA}, I_B = 15 \text{ mA}$<br>$I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$  | 0.75                 | 0.95<br>1.2  | V |

### SMALL SIGNAL CHARACTERISTICS

|          |                           |   |     |     |                  |
|----------|---------------------------|---|-----|-----|------------------|
| $C_{ob}$ | Output Capacitance        | $V_{CB} = 5.0 \text{ V}, f = 140 \text{ kHz}$                           |     | 6.5 | pF               |
| $C_{ib}$ | Input Capacitance         | $V_{EB} = 0.5 \text{ V}, f = 140 \text{ kHz}$                           |     | 30  | pF               |
| $h_{fe}$ | Small-Signal Current Gain | $I_C = 20 \text{ mA}, V_{CE} = 10 \text{ V},$<br>$f = 100 \text{ MHz}$  | 2.0 |     |                  |
| $h_{fe}$ | Small-Signal Current Gain | $V_{CE} = 10 \text{ V}, I_C = 1.0 \text{ mA},$<br>$f = 1.0 \text{ kHz}$ | 20  | 250 |                  |
| $h_{ie}$ | Input Impedance           | $f = 1.0 \text{ kHz}$   | 0.5 | 7.5 | $\text{K}\Omega$ |
| $h_{re}$ | Voltage Feedback Ratio    |   | 0.1 | 8.0 | $\times 10^{-4}$ |
| $h_{oe}$ | Output Admittance         |   | 1.0 | 30  | $\mu\text{mhos}$ |

### SWITCHING CHARACTERISTICS

|       |              |   |  |     |    |
|-------|--------------|---|--|-----|----|
| $t_d$ | Delay Time   | $V_{CC} = 30 \text{ V}, I_C = 150 \text{ mA},$        |  | 15  | ns |
| $t_r$ | Rise Time    | $I_{B1} = 15 \text{ mA}, V_{BE(off)} = 0.0 \text{ V}$ |  | 20  | ns |
| $t_s$ | Storage Time | $V_{CC} = 30 \text{ V}, I_C = 150 \text{ mA}$         |  | 225 | ns |
| $t_f$ | Fall Time    | $I_{B1} = I_{B2} = 15 \text{ mA}$                     |  | 30  | ns |

\*Pulse Test: Pulse Width  $\leq 300 \text{ } \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$

2N4400 / MMBT4400

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)