

找PDF  
pdf.dzsc.com

REVISIONS

| LTR | DESCRIPTION        | E.C.N. | DATE     | BY/APP'D |
|-----|--------------------|--------|----------|----------|
| L   | REVISE AND REDRAW. | 09484  | 01/19/93 | DEG/     |

Technical drawing of a TO-220 package showing top, side, and end views with dimensions in inches and millimeters.

Top View Dimensions:

- Overall Width: .330-.350 [8.38-8.89]
- Lead Width: .240-.260 [6.10-6.60]
- Lead Spacing: .100-.120 [2.54-3.05]
- Lead Thickness: .060-.075 TYP [1.52-1.91]
- Lead Angle: 4°-5°
- Lead Length: .400<sup>+.015</sup>-.005 [10.16<sup>0.38</sup>]
- Lead Width: .388<sup>+.015</sup>-.005 [9.86<sup>0.38</sup>]
- Lead Thickness: .045-.055 TYP [1.14-1.40]
- Lead Angle: 0°-6°
- Lead Length: .175-.185 [4.45-4.70]
- Lead Width: .048-.052 [1.22-1.32]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .190-.210 [4.83-5.33]
- Lead Width: .048-.055 TYP [1.22-1.40]
- Lead Thickness: .027-.037 TYP [0.69-0.94]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [2.67<sup>0.25</sup>]
- Lead Width: .015<sup>+.007</sup>-.001 [0.38<sup>0.18</sup>]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .130-.160 TYP [3.30-4.06]
- Lead Width: .045-.055 TYP [1.14-1.40]
- Lead Thickness: .001-.007 TYP [0.25-.178]
- Lead Angle: 7°
- Lead Length: .105<sup>+.010</sup>-.015 [