

# Protect It! Surge Suppressor

State-of-the-art protection for every application



## Model #: TLP1008TEL

- ▶ 10 outlets / 8-ft. cord
- ▶ 2395 joule rating
- ▶ 1 in/2 out tel/modem surge protection
- ▶ 5 transformer spaces
- ▶ \$150,000 Ultimate Lifetime Insurance (USA & Canada only)

## DESCRIPTION

Tripp Lite's TLP1008TEL offers economical AC surge suppression for protection of workstations, PCs, telecom systems, home electronics and other sensitive equipment. The TLP1008TEL features 10 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs to warn of suppressor damage. The unit has a surge suppression rating of 2395 joules to shield equipment from line noise and the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. \$150,000 Ultimate Lifetime Insurance (USA & Canada only)

PLUG / OUTLETS: Input: NEMA5-15P / Output: 10 NEMA5-15R / 8-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 5 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping / 2395 joules / 330V UL1449

## KEY BUYING POINTS

- 10 outlets with integrated child safety covers
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment — built-in splitter protects two devices sharing a single line; 6-ft. telephone cord included
- Surge suppression rating: 2395 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
- Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
- Can accommodate up to 5 transformers without blocking remaining outlets
- \$150,000 Ultimate Lifetime Insurance (USA & Canada only) covers connected equipment
- Keyhole supports for wall mounting
- Failsafe shutdown mode
- Lighted power switch
- Lifetime product warranty

## TYPICAL APPLICATIONS

- Ideal for home computers, TV/VCR/DVD players, stereos and other important electrical equipment

## PACKAGE INCLUDES

- TLP1008TEL surge suppressor
- 6-ft. RJ11 telephone cord
- Instruction manual with warranty information

## COMPLETE SPECIFICATIONS

### SYSTEM OVERVIEW

**System overview:** TLP1008TEL surge suppression strip includes 10 AC outlets, 8-foot AC cord, single-line phone suppression, 2395 joule protection level, diagnostic LEDs, lifetime warranty and \$150,000 connected equipment insurance

**Voltage compatibility:** 120 V AC

**Frequency compatibility:** 50/60 Hz

### OUTPUT

**Output volt amp capacity (amps):** 15A

**Output watt capacity (watts):** 1800W

**Outlet quantity / type:** 10 NEMA 5-15R

**Outlet orientation:** Two rows of outlets, including 5 widely spaced for transformers

**Outlet safety covers:** Includes built-in sliding outlet safety covers

**Transformer accomodation:** Supports 5 large transformer plug accessories without covering remaining outlets, accepts up to 8 transformers total

**Overload protection:** 15A resettable circuit breaker

### INPUT

**Input connection type:** NEMA 5-15P

**Input cord length (ft.):** 8 ft.

**Input cord length (m):** 2.4

**Input plug features:** Space-saving right angle input plug

**Input cord gauge, type:** 14 gauge, SJT

**Recommended electrical service:** 120V,15A

### LEDS ALARMS & SWITCHES

**Diagnostic LEDs:** Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status

**Switches:** Two-position on/off power switch

### AC SURGE / NOISE SUPPRESSION

**Protection modes:** Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression

**AC suppression joule rating:** 2395 joules

**Clamping voltage (RMS):** 150V

**AC suppression response time:** < 1 ns

**UL1499 let through rating:** 330V - UL Verified

**EMI / RFI filtering:** Up to 40dB

### DATALINE SURGE SUPPRESSION

**TEL / Modem line protection:** 1 line (1 input jack and 2 output jacks)

### PHYSICAL

**Unit weight (lbs):** 1.4

**Unit weight (kg):** 0.6

**Unit Dimensions (HWD/in):** 11.6 x 5 x 1.9

<b>Unit Dimensions (HWD/cm):</b>	29.5 x 12.7 x 4.8
<b>Shipping Dimensions (HWD/in):</b>	14.75 x 7.75 x 2
<b>Shipping Dimensions (HWD/cm):</b>	37.5 x 19.7 x 5.1
<b>Material of construction:</b>	Plastic
<b>Integrated keyhole mounting tabs:</b>	Keyhole mounting tabs enable wall mounting
<b>Housing color:</b>	Metallic silver
<b>AC line cord color:</b>	Black

**CERTIFICATIONS**

<b>UL1449 1998 Rev. (AC Suppression):</b>	UL1449
<b>UL1363 (Power Tap):</b>	UL1363
<b>UL497A (Communications):</b>	UL497A
<b>FCC Part 68 (Communications):</b>	FCC Part 68
<b>cUL / CSA (Canada):</b>	cUL
<b>Industry Canada (Communications):</b>	Industry Canada
<b>Approvals:</b>	Exceeds IEEE 587 category A&B specifications

**WARRANTY**

<b>Product warranty:</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only):</b>	\$150,000

*The policy of Tripp Lite is one of continuous improvement.  
Specifications are subject to change without notice.  
Therefore, your product may vary slightly from what is currently listed.*



**Tripp Lite World Headquarters**  
1111 W. 35th Street  
Chicago, IL 60609 USA

**Customer Support**  
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.