

Protect It! Surge Suppressor

State-of-the-art protection for every application



Model #: TLP808TELT

- ▶ 8 outlets / 8-ft. cord
- ▶ 3500 joule rating
- ▶ Coaxial surge protection
- ▶ Modem/fax surge protection
- ▶ \$150,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's TLP808TELT surge suppressor has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 3500 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment. \$150,000 Ultimate Lifetime Insurance (USA & Canada only).

KEY BUYING POINTS

- 8 outlets with integrated child safety covers; charcoal gray housing
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment; 6-ft. coax cable included
- Surge suppression rating: 3500 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$150,000 Ultimate Lifetime Insurance (USA & Canada only)
- Diagnostic LEDs indicate protection present & ground present
- Audible alarm notifies user when the unit is damaged and needs to be replaced
- Keyhole supports for wall mounting
- Lighted power switch
- Lifetime product warranty

TYPICAL APPLICATIONS

- Ideal for home computers, TV/VCR/DVD players, stereos and other important electrical equipment

PACKAGE INCLUDES

- TLP808TEL
- 6-ft. telephone cord
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

TLP808TELT surge suppression strip includes 8 AC outlets, 8 foot AC cord, single line phone suppression, coax line surge suppression, 3500 joule protection level, diagnostic

	LEDs, 3 dedicated transformer outlets, lifetime warranty and \$150,000 connected equipment insurance
Voltage compatibility:	120 VAC
Frequency compatibility:	50/60 Hz

OUTPUT

Output volt amp capacity (amps):	15
Output watt capacity (watts):	1800
Outlet quantity / type:	8 x NEMA 5-15R
Outlet orientation:	Single row of 5, plus a second row of 3 for transformer accommodation
Outlet safety covers:	Includes built-in sliding outlet safety covers
Transformer accomodation:	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total

INPUT

Input connection type:	NEMA 5-15P
Input cord length (ft.):	8
Input cord length (m):	2.4
Input plug features:	Space-saving right angle input plug
Input cord gauge, type:	14 gauge, SJT
Recommended electrical service:	120V 15A

LEDS ALARMS & SWITCHES

Diagnostic LEDs:	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Alarms:	Audible alarm sounds to indicate damage to suppression components
Switches:	Combination AC circuit breaker and 2 position red illuminated on/off power switch

AC SURGE / NOISE SUPPRESSION

Protection modes:	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating:	3500 joules
Clamping voltage (RMS):	150V
AC suppression response time:	< 1 ns
UL1499 let through rating:	330V - UL Verified
EMI / RFI filtering:	Up to 40 dB

DATALINE SURGE SUPPRESSION

TEL / Modem line protection:	Includes single line phone suppression via built-in RJ11 connectors, includes cable (260V clamping, 120 joules, center 2 wires protected. 1 input jack and 2 output jacks)
Coax line protection:	Includes coax line surge suppression via built-in Type F coax jacks, includes coax cable

PHYSICAL

Shipping weight (lbs):	2.5
Shipping weight (kg):	1.1
Unit weight (lbs):	1.6
Unit weight (kg):	0.7
Unit Dimensions (HWD/in):	1.6 x 9.25 x 4.25
Unit Dimensions (HWD/cm):	4.1 x 23.5 x 10.8
Shipping Dimensions (HWD/in):	2.5 x 14.75 x 8.75
Shipping Dimensions (HWD/cm):	6.4 x 37.5 x 22.2

Material of construction:	Plastic
Integrated keyhole mounting tabs:	Keyhole mounting tabs enable wall mounting
Housing color:	Attractive dark grey color scheme
AC line cord color:	Gray

CERTIFICATIONS

UL1449 1998 Rev. (AC Suppression):	UL1449
UL1363 (Power Tap):	UL1363
UL497A (Communications):	UL497A
FCC Part 68 (Communications):	FCC Part 68
cUL / CSA (Canada):	cUL
Industry Canada (Communications):	Industry Canada
Approvals:	Exceeds IEEE 587 category A&B specifications

WARRANTY

Product warranty:	Lifetime
Connected equipment insurance (USA and Canada Only):	\$150,000
Data recovery warranty:	Included

SPECIAL FEATURES

Additional Information:	Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line
--------------------------------	---

When you order today, you will receive the updated new version of these surge suppressors, however, they may be in packaging that still reflects the old specifications for joule and insurance amounts. In some cases the packaging you receive may have a sticker indicating these upgrades. This is simply due to an excess supply of existing packaging. Tripp Lite's ongoing commitment to having large quantities of product in stock at all times requires us to maintain large quantities of packaging. We are using this supply up as quickly as possible and are in the process of transitioning to new packaging. The timing will vary by product.

Please bear with us during this period of transition and rest assured that Protect It! Surge Suppressors are among the finest surge protection products available. If you want to know if your Protect It! Surge Suppressor offers the latest joule ratings and/or insurance amounts, refer to the date code on the back of your unit. If it was manufactured after 1/7/02 it is an upgraded version. For additional questions feel free to contact our Technical support hotline at (773) 869-1234 or email techsupport@tripplite.com.

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.