



NEC's L, S-BAND 4W SPDT SWITCH

UPG2009TB

FEATURES

- **LOW INSERTION LOSS:**
0.25 dB TYP. @ $V_{cont1/2} = 2.8$ V/0 V, $f = 1.0$ GHz
0.30 dB TYP. @ $V_{cont1/2} = 2.8$ V/0 V, $f = 2.0$ GHz
- **HIGH ISOLATION:**
28 dB TYP. @ $V_{cont1/2} = 2.8$ V/0 V, $f = 2.0$ GHz
- **POWER HANDLING:**
 P_{in} (0.1dB) = 34 dBm TYP. @ $V_{cont1/2} = 2.8$ V/0 V, $f = 1.0$ GHz
 P_{in} (1.0dB) = 36 dBm TYP. @ $V_{cont1/2} = 2.8$ V/0 V, $f = 1.0$ GHz
- **6-PIN SUPER MINIMOLD PACKAGE (2.0 × 1.25 × 0.9 mm)**

DESCRIPTION

NEC's UPG2009TB is a L, S-band SPDT (Single Pole Double Throw) GaAs FET switch for digital cellular or cordless telephone application. The device can operate from 500 MHz to 2.5 GHz, with low insertion loss and high isolation.

APPLICATIONS

- L-band digital cellular or cordless telephone
- Bluetooth™, W-LAN and WLL
- Short Range Wireless


ORDERING INFORMATION

Part Number	Package	Marking	Supplying Form
UPG2009TB-E3-A	6-pin super minimold	G2U	• Embossed tape 8 mm wide • Pin 1, 2, 3 face the perforation side of the tape • Qty 3 kpcs/reel

Remark To order evaluation samples, contact your nearby sales office.
Part number for sample order: UPG2009TB

Caution Observe precautions when handling because these devices are sensitive to electrostatic discharge.

PIN CONNECTIONS



Pin No.	Pin Name
1	OUT1
2	GND
3	OUT2
4	VCont2
5	IN
6	VCont1

ABSOLUTE MAXIMUM RATINGS (TA = 25°C, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Control Voltage 1, 2	Vcont1, 2	−6.0 to +6.0 Note1	V
Input Power	Pin	+36	dBm
Total Power Dissipation	Ptot	0.15	W
Operating Ambient Temperature	TA	−45 to +85	°C
Storage Temperature	Tstg	−55 to +150	°C

Note | Vcont1 - Vcont2 | ≤ 6.0 V

RECOMMENDED OPERATING RANGE (TA = 25°C)

Parameter	Symbol	MIN.	TYP.	MAX.	Unit
Control Voltage (High)	Vcont (H)	+2.7	+2.8	+3.0	V
Control Voltage (Low)	Vcont (L)	−0.2	0	+0.2	V

ELECTRICAL CHARACTERISTICS

($T_A = +25^{\circ}\text{C}$, $V_{\text{cont}1} = 2.8\text{ V}$, $V_{\text{cont}2} = 0\text{ V}$ or $V_{\text{cont}1} = 0\text{ V}$, $V_{\text{cont}2} = 2.8$, $Z_o = 50\ \Omega$, off chip DC blocking capacitors value; 56 pF, unless otherwise specified)


Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
Insertion Loss	L_{INS}	$f = 0.5\text{ to }1.0\text{ GHz}$	–	0.25	0.45	dB
		$f = 2.0\text{ GHz}$	–	0.30	0.50	dB
		$f = 2.5\text{ GHz}$	–	0.40	–	dB
Isolation	ISL	$f = 0.5\text{ to }2.0\text{ GHz}$	24	28	–	dB
		$f = 2.5\text{ GHz}$	–	25	–	dB
Input Return Loss	RL_{in}	$f = 0.5\text{ to }2.5\text{ GHz}$	15	20	–	dB
Output Return Loss	RL_{out}	$f = 0.5\text{ to }2.5\text{ GHz}$	15	20	–	dB
Input Power at 0.1 dB Compression Point Note	$P_{\text{in}(0.1\text{ dB})}$	$f = 1.0\text{ GHz}$, $V_{\text{cont}} = 2.8\text{ V}/0\text{ V}$	32.5	34	–	dBm
2nd Harmonics	$2f_0$	$f = 1.0\text{ GHz}$, $V_{\text{cont}} = 2.8\text{ V}/0\text{ V}$, $P_{\text{in}} = 30.5\text{ dBm}$	65	75	–	dBc
3rd Harmonics	$3f_0$	$f = 1.0\text{ GHz}$, $V_{\text{cont}} = 2.8\text{ V}/0\text{ V}$, $P_{\text{in}} = 30.5\text{ dBm}$	65	75	–	dBc
Switching Speed	t_{sw}		–	150	–	ns
Control Current	I_{cont}	$V_{\text{cont}} = 2.8\text{ V}/0\text{ V}$, RF Non	–	1	50	μA

Note $P_{\text{in}}(0.1\text{ dB})$ is the measured input power level when the insertion loss increases 0.1 dB more than that of linear range. All other characteristics are measured in linear range.


Caution It is necessary to use DC blocking capacitors with the device.

The value of DC blocking capacitors should be chosen to accommodate the frequency of operation, bandwidth, switching speed and the condition with actual board of your system. The range of recommended DC blocking capacitor value is less than 100 pF.

EVALUATION CIRCUIT ($V_{cont1} = 2.8\text{ V}$, $V_{cont2} = 0\text{ V}$ or $V_{cont2} = 0\text{ V}$, $V_{cont1} = 2.8\text{ V}$, off chip DC blocking capacitors value $C1 = 56\text{ pF}$, $C2 = 1\text{ 000 pF}$ (Bypass), using NEC standard evaluation board)



EVALUATION BOARD




TRUTH TABLE

Vcont1	Vcont2	IN-OUT1	IN-OUT2
Low	High	OFF	ON
High	Low	ON	OFF


TYPICAL CHARACTERISTICS

(TA = +25°C Vcont1/2 = 2.8 V/0 V, Pin = 0 dBm, OUT2 side is 50 Ω termination)


INPUT RETURN LOSS vs. FREQUENCY




ISOLATION vs. FREQUENCY



INSERTION LOSS vs. FREQUENCY



OUTPUT RETURN LOSS vs. FREQUENCY




Caution These characteristics values include the losses of the NEC evaluation board.

Remark The graphs indicate nominal characteristics.


TYPICAL CHARACTERISTICS

($f = 2\text{ GHz}$, OUT2 side is $50\ \Omega$ termination)


RELATION BETWEEN CONTROL
VOLTAGE OF INSERTION LOSS



RELATION BETWEEN CONTROL
VOLTAGE OF 2nd HARMONICS




RELATION BETWEEN CONTROL
VOLTAGE OF 3rd HARMONICS



Remark The graphs indicate nominal characteristics.

PACKAGE DIMENSIONS

6-PIN SUPER MINIMOLD (UNIT: mm)



RECOMMENDED SOLDERING CONDITIONS

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

Soldering Method	Soldering Conditions		Condition Symbol
Infrared Reflow	Peak temperature (package surface temperature)	: 260°C or below	IR260
	Time at peak temperature	: 10 seconds or less	
	Time at temperature of 220°C or higher	: 60 seconds or less	
	Preheating time at 120 to 180°C	: 120±30 seconds	
	Maximum number of reflow processes	: 3 times	
	Maximum chlorine content of rosin flux (% mass)	: 0.2%(Wt.) or below	
VPS	Peak temperature (package surface temperature)	: 215°C or below	VP215
	Time at temperature of 200°C or higher	: 25 to 40 seconds	
	Preheating time at 120 to 150°C	: 30 to 60 seconds	
	Maximum number of reflow processes	: 3 times	
	Maximum chlorine content of rosin flux (% mass)	: 0.2%(Wt.) or below	
Wave Soldering	Peak temperature (molten solder temperature)	: 260°C or below	WS260
	Time at peak temperature	: 10 seconds or less	
	Preheating temperature (package surface temperature)	: 120°C or below	
	Maximum number of flow processes	: 1 time	
	Maximum chlorine content of rosin flux (% mass)	: 0.2%(Wt.) or below	
Partial Heating	Peak temperature (pin temperature)	: 350°C or below	HS350
	Soldering time (per side of device)	: 3 seconds or less	
	Maximum chlorine content of rosin flux (% mass)	: 0.2%(Wt.) or below	

Caution Do not use different soldering methods together (except for partial heating).

Life Support Applications

These NEC products are not intended for use in life support devices, appliances, or systems where the malfunction of these products can reasonably be expected to result in personal injury. The customers of CEL using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CEL for all damages resulting from such improper use or sale.

CEL California Eastern Laboratories, Your source for NEC RF, Microwave, Optoelectronic, and Fiber Optic Semiconductor Devices.

4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • FAX (408) 988-0279 • www.cel.com

DATA SUBJECT TO CHANGE WITHOUT NOTICE

11/11/2004

NEC

A Business Partner of NEC Compound Semiconductor Devices, Ltd.

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL's understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

Restricted Substance per RoHS	Concentration Limit per RoHS (values are not yet fixed)	Concentration contained in CEL devices	
		-A	-AZ
Lead (Pb)	< 1000 PPM	Not Detected	(*)
Mercury	< 1000 PPM	Not Detected	
Cadmium	< 100 PPM	Not Detected	
Hexavalent Chromium	< 1000 PPM	Not Detected	
PBB	< 1000 PPM	Not Detected	
PBDE	< 1000 PPM	Not Detected	

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

Important Information and Disclaimer: Information provided by CEL on its website or in other communications concerning the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall CEL's liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.

See CEL Terms and Conditions for additional clarification of warranties and liability.