




## 74LVQ273

### OCTAL D-TYPE FLIP FLOP WITH CLEAR

- HIGH SPEED:  
 $f_{MAX} = 150 \text{ MHz (TYP.) at } V_{CC} = 3.3\text{V}$
- COMPATIBLE WITH TTL OUTPUT
- LOW POWER DISSIPATION:  
 $I_{CC} = 4 \mu\text{A (MAX.) at } T_A = 25^\circ\text{C}$
- LOW NOISE:  
 $V_{OLP} = 0.4 \text{ V (TYP.) at } V_{CC} = 3.3\text{V}$
- $75\Omega$  TRANSMISSION LINE DRIVING CAPABILITY
- SYMMETRICAL OUTPUT IMPEDANCE:  
 $|I_{OH}| = I_{OL} = 12 \text{ mA (MIN)}$
- PCI BUS LEVELS GUARANTEED AT 24mA
- BALANCED PROPAGATION DELAYS:  
 $t_{PLH} \cong t_{PHL}$
- OPERATING VOLTAGE RANGE:  
 $V_{CC} \text{ (OPR)} = 2\text{V to } 3.6\text{V (1.2V Data Retention)}$
- PIN AND FUNCTION COMPATIBLE WITH 74 SERIES 273
- IMPROVED LATCH-UP IMMUNITY

#### DESCRIPTION

The LVQ273 is a low voltage CMOS OCTAL D-TYPE FLIP FLOP WITH CLEAR fabricated with sub-micron silicon gate and double-layer metal wiring C<sup>2</sup>MOS technology. It is ideal for low power and low noise 3.3V applications.




Information signals applied to D inputs are transferred to the Q outputs on the positive going edge of the clock pulse.

When the CLEAR inputs is held low, the Q outputs are held low independently of the other inputs.

It has better speed performance at 3.3V than 5V LS-TTL family combined with the true CMOS low power consumption.


All inputs and outputs are equipped with protection circuits against static discharge, giving them 2KV ESD immunity and transient excess voltage.

#### PIN CONNECTION AND IEC LOGIC SYMBOLS



74LVQ273

INPUT AND OUTPUT EQUIVALENT CIRCUIT



PIN DESCRIPTION


| PIN No                     | SYMBOL                    | NAME AND FUNCTION                         |
|----------------------------|---------------------------|-------------------------------------------|
| 1                          | $\overline{\text{CLEAR}}$ | Asynchronous Master Reset (Active LOW)    |
| 2, 5, 6, 9, 12, 15, 16, 19 | Q0 to Q7                  | Flip-Flop Outputs                         |
| 3, 4, 7, 8, 13, 14, 17, 18 | D0 to D7                  | Data Inputs                               |
| 11                         | CLOCK                     | Clock Input (LOW-to-HIGH, Edge-Triggered) |
| 10                         | GND                       | Ground (0V)                               |
| 20                         | V <sub>CC</sub>           | Positive Supply Voltage                   |

TRUTH TABLE

| INPUTS                    |   |       | OUTPUTS        | FUNCTION  |
|---------------------------|---|-------|----------------|-----------|
| $\overline{\text{CLEAR}}$ | D | CLOCK | Q              |           |
| L                         | X | X     | L              | CLEAR     |
| H                         | L |       | L              |           |
| H                         | H |       | H              |           |
| H                         | X |       | Q <sub>n</sub> | NO CHANGE |

X: Don't Care

LOGIC DIAGRAM



This logic diagram has not be used to esimate propagation delays

**ABSOLUTE MAXIMUM RATINGS**

| Symbol                | Parameter                     | Value                  | Unit |
|-----------------------|-------------------------------|------------------------|------|
| $V_{CC}$              | Supply Voltage                | -0.5 to +7             | V    |
| $V_I$                 | DC Input Voltage              | -0.5 to $V_{CC} + 0.5$ | V    |
| $V_O$                 | DC Output Voltage             | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{IK}$              | DC Input Diode Current        | $\pm 20$               | mA   |
| $I_{OK}$              | DC Output Diode Current       | $\pm 20$               | mA   |
| $I_O$                 | DC Output Current             | $\pm 50$               | mA   |
| $I_{CC}$ or $I_{GND}$ | DC $V_{CC}$ or Ground Current | $\pm 400$              | mA   |
| $T_{stg}$             | Storage Temperature           | -65 to +150            | °C   |
| $T_L$                 | Lead Temperature (10 sec)     | 300                    | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied.

**RECOMMENDED OPERATING CONDITIONS**

| Symbol   | Parameter                                           | Value         | Unit |
|----------|-----------------------------------------------------|---------------|------|
| $V_{CC}$ | Supply Voltage (note 1)                             | 2 to 3.6      | V    |
| $V_I$    | Input Voltage                                       | 0 to $V_{CC}$ | V    |
| $V_O$    | Output Voltage                                      | 0 to $V_{CC}$ | V    |
| $T_{op}$ | Operating Temperature:                              | -40 to +85    | °C   |
| dt/dv    | Input Rise and Fall Time ( $V_{CC} = 3V$ ) (note 2) | 0 to 10       | ns/V |

1) Truth Table guaranteed: 1.2V to 3.6V

2)  $V_{IN}$  from 0.8V to 2V

## DC SPECIFICATIONS

| Symbol           | Parameter                          | Test Conditions        |                                                                    |                        | Value                  |       |      |              |      | Unit |
|------------------|------------------------------------|------------------------|--------------------------------------------------------------------|------------------------|------------------------|-------|------|--------------|------|------|
|                  |                                    | V <sub>CC</sub><br>(V) |                                                                    |                        | T <sub>A</sub> = 25 °C |       |      | -40 to 85 °C |      |      |
|                  |                                    |                        |                                                                    |                        | Min.                   | Typ.  | Max. | Min.         | Max. |      |
| V <sub>IH</sub>  | High Level Input Voltage           | 3.0 to 3.6             |                                                                    |                        | 2.0                    |       |      | 2.0          |      | V    |
| V <sub>IL</sub>  | Low Level Input Voltage            |                        |                                                                    |                        |                        |       | 0.8  |              | 0.8  | V    |
| V <sub>OH</sub>  | High Level Output Voltage          | 3.0                    | V <sub>I</sub> <sup>(*)</sup> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>O</sub> =-50 μA | 2.9                    | 2.99  |      | 2.9          |      | V    |
|                  |                                    |                        |                                                                    | I <sub>O</sub> =-12 mA | 2.58                   |       |      | 2.48         |      |      |
|                  |                                    |                        |                                                                    | I <sub>O</sub> =-24 mA |                        |       |      | 2.2          |      |      |
| V <sub>OL</sub>  | Low Level Output Voltage           | 3.0                    | V <sub>I</sub> <sup>(*)</sup> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>O</sub> =50 μA  |                        | 0.002 | 0.1  |              | 0.1  | V    |
|                  |                                    |                        |                                                                    | I <sub>O</sub> =12 mA  |                        | 0     | 0.36 |              | 0.44 |      |
|                  |                                    |                        |                                                                    | I <sub>O</sub> =24 mA  |                        |       |      |              | 0.55 |      |
| I <sub>I</sub>   | Input Leakage Current              | 3.6                    | V <sub>I</sub> = V <sub>CC</sub> or GND                            |                        |                        |       | ±0.1 |              | ±1   | μA   |
| I <sub>CC</sub>  | Quiescent Supply Current           | 3.6                    | V <sub>I</sub> = V <sub>CC</sub> or GND                            |                        |                        |       | 4    |              | 40   | μA   |
| I <sub>OLD</sub> | Dynamic Output Current (note 1, 2) | 3.6                    | V <sub>OLD</sub> = 0.8 V max                                       |                        |                        |       |      | 36           |      | mA   |
| I <sub>OHD</sub> |                                    |                        | V <sub>OHD</sub> = 2 V min                                         |                        |                        |       |      | -25          |      | mA   |

1) Maximum test duration 2ms, one output loaded at time

2) Incident wave switching is guaranteed on transmission lines with impedances as low as 50 Ω.

(\*) All outputs loaded.

## DYNAMIC SWITCHING CHARACTERISTICS

| Symbol           | Parameter                              | Test Conditions        |                        | Value                  |      |      |              |      | Unit |
|------------------|----------------------------------------|------------------------|------------------------|------------------------|------|------|--------------|------|------|
|                  |                                        | V <sub>CC</sub><br>(V) |                        | T <sub>A</sub> = 25 °C |      |      | -40 to 85 °C |      |      |
|                  |                                        |                        |                        | Min.                   | Typ. | Max. | Min.         | Max. |      |
| V <sub>OLP</sub> | Dynamic Low Voltage                    | 3.3                    | C <sub>L</sub> = 50 pF |                        | 0.4  | 0.8  |              |      | V    |
| V <sub>OLV</sub> | Quiet Output (note 1, 2)               |                        |                        | -0.8                   | -0.5 |      |              |      |      |
| V <sub>IHD</sub> | Dynamic High Voltage Input (note 1, 3) | 3.3                    |                        |                        |      | 2    |              |      |      |
| V <sub>ILD</sub> | Dynamic Low Voltage Input (note 1, 3)  | 3.3                    |                        | 0.8                    |      |      |              |      |      |

1) Worst case package

2) Max number of outputs defined as (n). Data inputs are driven 0V to 3.3V, (n-1) outputs switching and one output at GND

3) max number of data inputs (n) switching. (n-1) switching 0V to 3.3V. Inputs under test switching: 3.3V to threshold (V<sub>ILD</sub>), 0V to threshold (V<sub>IHD</sub>). f=1MHz

**AC ELECTRICAL CHARACTERISTICS** ( $C_L = 50$  pF,  $R_L = 500$   $\Omega$ , Input  $t_r = t_f = 3$  ns)

| Symbol                                 | Parameter                                 | Test Condition            |  | Value                  |              |              |              |              | Unit |
|----------------------------------------|-------------------------------------------|---------------------------|--|------------------------|--------------|--------------|--------------|--------------|------|
|                                        |                                           | V <sub>CC</sub><br>(V)    |  | T <sub>A</sub> = 25 °C |              |              | -40 to 85 °C |              |      |
|                                        |                                           |                           |  | Min.                   | Typ.         | Max.         | Min.         | Max.         |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation Delay Time<br>CK to Q         | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 7.5<br>6.0   | 17.0<br>12.0 |              | 20.0<br>14.0 | ns   |
| t <sub>PHL</sub>                       | Propagation Delay Time<br>CLR to Q        | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 10.0<br>9.0  | 18.0<br>13.0 |              | 20.0<br>14.0 | ns   |
| t <sub>w(L)</sub>                      | CLR pulse Width, LOW                      | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 2.5<br>2.0   | 7.0<br>5.5   |              | 8.5<br>6.0   | ns   |
| t <sub>w</sub>                         | CK pulse Width                            | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 2.0<br>1.5   | 7.0<br>5.5   |              | 8.5<br>6.0   | ns   |
| t <sub>sL</sub><br>t <sub>sH</sub>     | Setup Time D to CK<br>HIGH or LOW         | 2.7<br>3.3 <sup>(*)</sup> |  |                        | -0.4<br>-0.3 | 6.5<br>5.0   |              | 8.5<br>6.0   | ns   |
| t <sub>hL</sub><br>t <sub>hH</sub>     | Hold Time D to CK<br>HIGH or LOW          | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 0.4<br>0.3   | 3.0<br>2.0   |              | 3.5<br>2.5   | ns   |
| t <sub>REM</sub>                       | Recovery Time CLR to<br>CK                | 2.7<br>3.3 <sup>(*)</sup> |  |                        | -0.1<br>0.0  | 5.0<br>4.0   |              | 6.5<br>4.5   | ns   |
| f <sub>MAX</sub>                       | Maximum Clock<br>Frequency                | 2.7<br>3.3 <sup>(*)</sup> |  | 60<br>90               | 150<br>190   |              | 50<br>70     |              | MHz  |
| t <sub>OSLH</sub><br>t <sub>OSHL</sub> | Output to Output Skew<br>Time (note 1, 2) | 2.7<br>3.3 <sup>(*)</sup> |  |                        | 0.5<br>0.5   | 1.0<br>1.0   |              | 1.5<br>1.5   | ns   |

1) Skew is defined as the absolute value of the difference between the actual propagation delay for any two outputs of the same device switching in the same direction, either HIGH or LOW ( $t_{OSLH} = |t_{PLHm} - t_{PLHn}|$ ,  $t_{OSHL} = |t_{PHLm} - t_{PHLn}|$ )

2) Parameter guaranteed by design


(\*) Voltage range is  $3.3V \pm 0.3V$

**CAPACITIVE CHARACTERISTICS**

| Symbol          | Parameter                              | Test Conditions        |                          | Value                  |      |      |              |      | Unit |
|-----------------|----------------------------------------|------------------------|--------------------------|------------------------|------|------|--------------|------|------|
|                 |                                        | V <sub>CC</sub><br>(V) |                          | T <sub>A</sub> = 25 °C |      |      | -40 to 85 °C |      |      |
|                 |                                        |                        |                          | Min.                   | Typ. | Max. | Min.         | Max. |      |
| C <sub>IN</sub> | Input Capacitance                      | 3.3                    |                          |                        | 5    |      |              |      | pF   |
| C <sub>PD</sub> | Power Dissipation Capacitance (note 1) | 3.3                    | f <sub>IN</sub> = 10 MHz |                        | 30   |      |              |      | pF   |


1)  $C_{PD}$  is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation.  $I_{CC(opr)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{cd}/8$  (per FlipFlop)



TEST CIRCUIT



$C_L = 50 \text{ pF}$  or equivalent (includes jig and probe capacitance)  
 $R_L = R_1 = 500\Omega$  or equivalent  
 $R_T = Z_{OUT}$  of pulse generator (typically  $50\Omega$ )


WAVEFORM 1: PROPAGATION DELAYS, SETUP AND HOLD TIMES, CLOCK PULSE WIDTH  
( $f=1\text{MHz}$ ; 50% duty cycle)



**WAVEFORM 2: PROPAGATION DELAYS** ( $f=1\text{MHz}$ ; 50% duty cycle)**WAVEFORM 3: RECOVERY TIME, CLEAR PULSE WIDTH** ( $f=1\text{MHz}$ ; 50% duty cycle)


SO-20 MECHANICAL DATA

| DIM. | mm        |       |       | inch  |       |       |
|------|-----------|-------|-------|-------|-------|-------|
|      | MIN.      | TYP.  | MAX.  | MIN.  | TYP.  | MAX.  |
| A    |           |       | 2.65  |       |       | 0.104 |
| a1   | 0.10      |       | 0.20  | 0.004 |       | 0.007 |
| a2   |           |       | 2.45  |       |       | 0.096 |
| b    | 0.35      |       | 0.49  | 0.013 |       | 0.019 |
| b1   | 0.23      |       | 0.32  | 0.009 |       | 0.012 |
| C    |           | 0.50  |       |       | 0.020 |       |
| c1   | 45 (typ.) |       |       |       |       |       |
| D    | 12.60     |       | 13.00 | 0.496 |       | 0.512 |
| E    | 10.00     |       | 10.65 | 0.393 |       | 0.419 |
| e    |           | 1.27  |       |       | 0.050 |       |
| e3   |           | 11.43 |       |       | 0.450 |       |
| F    | 7.40      |       | 7.60  | 0.291 |       | 0.299 |
| L    | 0.50      |       | 1.27  | 0.19  |       | 0.050 |
| M    |           |       | 0.75  |       |       | 0.029 |
| S    | 8 (max.)  |       |       |       |       |       |



## TSSOP20 MECHANICAL DATA

| DIM. | mm   |          |      | inch   |            |        |
|------|------|----------|------|--------|------------|--------|
|      | MIN. | TYP.     | MAX. | MIN.   | TYP.       | MAX.   |
| A    |      |          | 1.1  |        |            | 0.433  |
| A1   | 0.05 | 0.10     | 0.15 | 0.002  | 0.004      | 0.006  |
| A2   | 0.85 | 0.9      | 0.95 | 0.335  | 0.354      | 0.374  |
| b    | 0.19 |          | 0.30 | 0.0075 |            | 0.0118 |
| c    | 0.09 |          | 0.2  | 0.0035 |            | 0.0079 |
| D    | 6.4  | 6.5      | 6.6  | 0.252  | 0.256      | 0.260  |
| E    | 6.25 | 6.4      | 6.5  | 0.246  | 0.252      | 0.256  |
| E1   | 4.3  | 4.4      | 4.48 | 0.169  | 0.173      | 0.176  |
| e    |      | 0.65 BSC |      |        | 0.0256 BSC |        |
| K    | 0°   | 4°       | 8°   | 0°     | 4°         | 8°     |
| L    | 0.50 | 0.60     | 0.70 | 0.020  | 0.024      | 0.028  |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 1999 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Italy - Japan - Korea - Malaysia - Malta - Mexico - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.

<http://www.st.com>