

VSX60xD35

60 Watt Dual Output Quarter Brick DC/DC Converter



- 3.3V & 5.0V Dual Output
- 2.3" x 1.5" x 0.5"
- 90% Efficiency
- Low Output Noise
- Input Filtering
- Remote On/Off, Input Side
- Output Voltage Trim, +/-10%
- -40C° to +100C° Baseplate Temp.
- Output Current Limit, Self-Start
- 1,500 Vdc Isolation, Input to Output
- UL/CUL 1950, EN60 950
- 18-36 Vdc and 36-75 Vdc Input Models
- Continuous Short Circuit Protection
- Non-latching Protection:
Input Undervoltage
Input Overvoltage
Output Overvoltage
Overtemperature
- Output Voltage Tracking at Turn-on and Turn-off
- No Minimum Load Current

APPLICATIONS

- Distributed Power Architectures
- Workstations
- EDP Equipment
- Telecommunications

OPTIONS

- Choice of Remote On/Off Logic Configuration
- Heatsink Available for Extended Operation

ADDITIONAL INFORMATION

- See Application Note DCAN-40 at www.cdpowerelectronics.com

The VSX60 Series are dual output converters with 18-36V and 36-75V input models with 3.3Vdc and 5Vdc outputs. The industry quarter-pak size of 2.3" x 1.5" x 0.5" coupled with 90% efficiency is an industry high-density breakthrough.

These converters utilize Vx high density technology. This technology has been featured in our highly efficient VKP and VKA series now successfully in use worldwide. The very high 90%

efficiency minimizes the requirement for heat-sinking and the low output ripple minimizes the need for additional filtering. For maximum flexibility, power can be traded between outputs as required. The VSX60 series feature virtually all of the options required by design engineers but not at the competition's typical additional price for each option. This multitude of features are standard on the VSX60 series.

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Input Voltage:				
VSX60LD35	Vi		100	Vdc
VSX60MD35	Vi	36	75	Vdc
I/O Isolation Voltage			1500	Vdc
I/P to case			1500	Vdc
O/P to case			200	Vdc
Operating Case Temperature	T	-40	100	°C

SPECIFICATIONS, ALL MODELS

Specifications are at $T_{CASE} = +40^{\circ}\text{C}$ nominal input voltage unless otherwise specified.

INPUT	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
	Operating Input Voltage					
	VSX60LD	V_i	18	24	36	VDC
	VSX60MD	V_i	36	48	75	VDC
	Maximum Input Current ($V_i=0\text{V}$ to V_i max, $I_o=I_o$ max)					
	VSX60LD	I_i max			5.0	A
	VSX60MD	I_i max			2.25	A
	I/P Reflected Ripple Current				400	mA p-p
	No Load Input Current	I_{iNL}		50		mA
	On/Off Activated Input Current	I_{iQ}		17		mA



OUTPUT Under any conditions, the voltage of V1 will always be greater or equal to that of V2.	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
	Output voltage					
	Over all conditions of I/P voltage, load and temperature)					
	3.3 Vout (V2)	3.3 V_o	3.2	—	3.4	Vdc
	5.0 Vout (V1)	5.0 V_o	4.8	—	5.2	Vdc
	Output Voltage Setpoint ($V_i=48$, $I_{o3}=9\text{A}$, $I_{o5}=6\text{A}$, $T_c=25^{\circ}\text{C}$)					
	3.3 Vout (V2)	3.3 $V_{o,set}$	3.26	3.30	3.34	Vdc
	5.0 Vout (V1)	5.0 $V_{o,set}$	4.96	5.02	5.08	Vdc
	Output Ripple and Noise Voltage (peak-to-peak, 100 MHz BW)					
	3.3 Vout (V2)	—	—	—	60	mv p-p
	5.0 Vout (V1)	—	—	—	80	mv p-p
	Output Current (Total module O/P power should not exceed 60 Watts)					
	3.3 Vout (V2)	I_{o3}	—	—	15	A
	5.0 Vout (V1)	I_{o5}	—	—	12	A
	Output Current Limit Inception ($V_o=95\%$ of V_o nom)					
	3.3 Vout (V2)	$I_{o3,cli}$	19.0	21.0	23.0	A
	5.0 Vout (V1)	$I_{o5,cli}$	12.5	13.5	15.0	A
	Output Short Ckt Current (Max impedance across short circuit = $65\text{m}\Omega$)					
	3.3 V_o		16	19	22	A
	5.0 V_o		11	14	17	A
	Efficiency ($V_i=48\text{V}$, $I_{o3}=9\text{A}$, $I_{o5}=6\text{A}$, $T_c=70^{\circ}\text{C}$)	η	89	90	—	%
	Dynamic Response ($\Delta I_o/\Delta t=0.2\text{A}/\mu\text{sec}$. $V_i=48\text{V}$, $T_c=25^{\circ}\text{C}$, either O/P) Load change of 50% I_o max; at any operating load up to $I_{o,max}$ or $P_{o,max}$ Peak Deviation outside settling point	—	—	2	—	% V_o nom

GENERAL	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
	Isolation Specifications					
	Isolation Capacitance	—	—	1000	—	pF
	Isolation Resistance	—	10	—	—	MΩ
	Remote On/Off (open collector equivalent, signal referenced to -Vin terminal)					
	VSx60xD35 Preferred Logic (negative)					
	Logic Low - Module On					
	Logic High - Module Off					
	VSX60xD35-1 - Optional Logic (positive)					
	Logic Low - Module Off					
	Logic High - Module On					
	Logic Low: At Von/off = 0V	Von/off	0	—	70	Vdc
		Ion/off	—	—	200	μA
	Turn On Time (Vo within 1% of steady state)					
	From Application of Vin	—	—	7	10	mSecs
	From Remote On/Off Activation)	—	—	3	4	mSecs
	Input Undervoltage Lockout (Turn Off & Turn On Voltages Track)					
	Turn On (VSX60LD35)		15	16.5	18	Vdc
	Turn On (VSX60MD35)	—	30	33	36	Vdc
	Turn Off (VSX60LD35)		13.5	15	16.5	Vdc
	Turn Off (VSX60MD35)	—	27	30	33	Vdc
	Input Overvoltage Lockout (Turn Off & Turn On Voltages Track)					
	Turn On (VSX60LD35)		37	38.5	40	Vdc
	Turn Off (VSX60MD35)	—	76	80	84	Vdc
	Turn On (VSX60LD35)		36	38.5	41	Vdc
	Turn On (VSX60MD35)	—	74.5	78.5	82.5	Vdc
	Output Overvoltage Set Point (Non-latching independent control loop)					
	3.3 Vo	VO3OV clamp	3.8	4.0	4.3	Vdc
	5.0 Vo	VO3OV clamp	5.85	6.1	6.35	Vdc
	Overtemperature Limiting	Tc	105	115	125	°C
	Weight					
	VSX60xD35, VSX60xD35-1			67		Grams
	VSX60xD35-U, VSX60xD35-1U			44		Grams
	Output Trim					
	Tie Trim to +3.3 Vo for trim down 3.3 Vo	VO ₃ td	—	-10	—	%
	5.0 Vo	VO ₅ td	—	-10	—	%
	Tie Trim to O/P RTN for trim up 3.3 Vo	VO ₃ td	—	10	—	%
	5.0 Vo	VO ₅ td	—	10	—	%

MECHANICAL

Tolerances: x.xx in. + 0.02 in.

x.xxx in. +0.01 in.



Pinout Key	
1	+Vin
2	On/Off
3	-Vin
4	+3.3 Vout
5	O/P RTN
6	Trim
7	+5.0 Vout

NOTES:

1. Marked with: specific model ordered, date code, job code.

2. MATERIAL: Units are encapsulated in a low thermal resistance molding compound which has excellent chemical resistance and electrical properties in high humidity environments and over a wide operating temperature range. The encapsulant and outer shell of the unit have UL94V-0 ratings. Lead material is solder plated to allow ease of solderability.

3. IMPORTANT: When utilizing the PEM nuts for board mounting, it is required to follow guidelines in application note DCAN-40 available on the web at www.cdpowerelectronics.com.

ORDERING INFORMATION

To Find Model Number

Device Family _____ VSX60 xD35 - 1 U

VSX60MD23 (Quarter Brick, 60 Watt DC/DC)

Where X is Input Range _____

L = 18-36Vdc; M = 36-75 Vdc

Logic: No Number = Preferred Logic (Negative); _____

1 = Optional Logic (Positive)

Package _____

No Letter = Encapsulated; U = Unencapsulated

Model Numbers

Model Numbers
VSX60LD35
VSX60LD35-1
VSX60MD35
VSX60MD35-U
VSX60MD35-1
VSX60MD35-1U

Power Electronics Division, United States
3400 E Britannia Drive, Tucson, Arizona 85706
Tel: 800.547.2537 Fax: 520.295.4160

C&D Technologies, (NCL)
Milton Keynes MK14 5BU UK
Tel: +44 (0)1908 615232 Fax: +44 (0)1908 617545

Any data, prices, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application. C&D Technologies, Inc. does not warrant or recommend that any of its products be used in any life support or aviation or aerospace applications.