



Electronics

a vital part of your world

Find Answers:

Sunday, 6 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter  
**SUBSCRIBE NOW!**  
 click here

Circuit Breakers

↳ Thermal Circuit Breakers



**W51-A122B1-20** [Active](#)

[Not ELV or RoHS Compliant](#)

**(Tyco Electronics P/N: 1-1423673-4)**

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li><a href="#">General Info</a></li> <li><a href="#">Sales Info</a></li> </ul>	<ul style="list-style-type: none"> <li><a href="#">Pricing</a></li> <li><a href="#">Product Availability</a></li> </ul>	<ul style="list-style-type: none"> <li><a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

<a href="#">Product Photo</a>	<a href="#">Schematic</a>	<a href="#">Panel Cutout</a>
-------------------------------	---------------------------	------------------------------

Searchable Features:

<b>Brand:</b>	Potter & Brumfield
<b>RoHS/ELV Compliance:</b>	Not ELV/RoHS compliant
<b>Lead Free Solder Processes:</b>	Not relevant for lead free process
<b>Series:</b>	W51
<b>Actuator Style:</b>	Rocker
<b>Number of Poles:</b>	1
<b>Current Rating (Amps.):</b>	20
<b>Rocker Color:</b>	Red (Translucent)
<b>Circuit Function:</b>	Trip Free - Switchable
<b>Operating Voltage, Max.:</b>	250 VAC
<b>Illuminated:</b>	Yes
<b>Trip Time at 200%:</b>	4 to 40 Seconds
<b>Interrupt Capacity:</b>	1,000 A @ 250 VAC

Other Properties:

<b>Panel Thickness (mm [in]):</b>	0.75 – 3.00 [0.030 – 0.118]
<b>Panel Cutout:</b>	28.5 mm x 13.5 mm [1.122 x .531]
<b>RESET/OFF Marking:</b>	RESET/OFF Printed

**Termination Type:**

6.35 [.250] Straight Quick  
Connect Tab

[Copyright and Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]