



OK Industries · Division of Jonard Industries Corp.

Our Products

Wire Wrap & Unwrap Tools
ImpactPlus Punch Down Tools
Application & Technology Notes
Circuit Assembly Tools

Distributors & Representatives

About OK Industries


What's New
Catalog/Information Request
Trade Shows
Career Opportunities
Comments / Email

OK Industries · Division of

JONARD
Industries Corp.

Wire Wrapping Bits and Sleeves - AWG/Inches

- [AWG/Inches](#)
- [Metric](#)



Fully compatible with any make or model wire wrapping tool.

Bits and Sleeves Chart (AWG) Inches

Wire Gauge (AWG)	Type	Bit Part No.	Sleeve Part No.	a) Maximum Insulations Diameter b) Minimum Terminal Diagonal c) Maximum Terminal Diagonal d) Terminal Hole Depth e) Effective Radius f) Terminal Hole Diameter (All measurements in Inches)					
				a	b	c	d	e	f
18	Regular	KB18	P194	-	.060	.73	1.0	.150	.075
20	Modified	WB20M	P194LN	.059	.042	.073	1.000	.123	.075
20-22	Regular	KB2075	P2224	-	.042	.073	1.000	.123	.075
22	Regular	KB22	P2224	-	.054	.073	.750	.117	.075
22	Modified	WB2275M	P2224	.052	.049	.074	1.000	.132	.075
22-24	Regular	KB224LH	P2224	-	.061	.085	1.000	.117	.086

22-24	Regular	KB224-1	P2224	-	.054	.073	1.000	.111	.075
22-24	Regular	KB224	P2224	-	.054	.073	.807	.111	.075
22-24	Modified	WB224M	P2224	.050	.049	.074	1.250	.121	.075
24	Regular	*KB2444	P3032LN	-	.024	.043	1.000	.083	.044
24	Regular	KB24DH	P2426	-	.055	.074	1.500	.100	.075
24	Modified	WB24DH	P2224	.046	.054	.073	1.750	.117	.075
24	Regular	KB24	P2426	-	.055	.074	.750	.100	.075
24	Modified	*WB24SM	P3032LN	.044	.024	.043	.750	.098	.044
24	Modified	WB24DHM	P2224	.050	.049	.068	1.125	.118	.069
24-26	Regular	OK2426	P2426	-	.058	.073	.750	.100	.075
24-26	Modified	WB2426M	P2224	.046	.054	.073	.750	.118	.075
24-26	Regular	KB2466	OK8519	-	.054	.065	1.000	.098	.066
26	Regular	*KB2639	P26LN	-	.023	.038	.750	.068	.040
26	Regular	KB26	P2426	-	.058	.073	1.000	.100	.075
26	Modified	*WB26SM	P3032	.031	.023	.038	.750	.075	.040
26	Modified	WB26M	P2224	.046	.054	.073	1.000	.118	.075
26	Modified	*WB2644M	P3032LN	.046	.024	.043	.750	.098	.044
26	Modified	WB2669M	P2426	.041	.053	.068	1.00	.109	.069
28	Modified	WB2870M	P2426	.034	.053	.068	1.00	.103	.070
28-29	Modified	*WB2829M	P3032L	.036	.033	.038	.750	.091	.040
30	Modified	*SB30MSH-B	P3032	.027	.031	.035	.750	.064	.036
30	Modified	*SB30MMK	P3032	.023	.031	.035	.750	.064	.036
30-32	Modified	*WB3032M	P3032	.027	.034	.038	.750	.064	.040

* These tools recommended for .025" square terminals on .100 centers

[\[Back to the Top\]](#)
