

YG911S3R

(300V / 5A TO-220F15)

LOW LOSS SUPER HIGH SPEED DIODE

Features

- Low V_F
- Super high speed switching.
- High reliability by planer design.

Applications

- High speed power switching.

Maximum Ratings and Characteristics

- Absolute Maximum Ratings

Item	Symbol	Conditions	Rating	Unit
Repetitive peak reverse voltage	V_{RRM}		300	V
Repetitive peak surge reverse voltage	V_{RSM}		300	V
Isolation voltage	V_{iso}	Terminals to Case, AC, 1min.	1500	V
Average output current	I_O	duty=1/2, $T_c=128^{\circ}\text{C}$ Rectangl wave	5	A
Surge current	I_{FSM}	Sine wave 10ms	40	A
Operating junction temperature	T_j		-40 to +150	$^{\circ}\text{C}$
Storage temperature	T_{stg}		-40 to +150	$^{\circ}\text{C}$


- Electrical Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Conditions	Max.	Unit
Forward voltage Drop	V_F	$I_F=5.0\text{A}$	1.2	V
Reverse current	I_R	$V_R=V_{RRM}$	100	μA
Reverse recovery time	t_{rr}	$I_F=0.1\text{A}, I_R=0.2\text{A}, I_{rec}=0.05\text{A}$	35	ns
Thermal resistance	$R_{th(j-c)}$	Junction to case	3.5	$^{\circ}\text{C/W}$

- Mechanical Characteristics






Mounting torque	Recommended torque	0.3 to 0.5	N · m
-----------------	--------------------	------------	-------

Outline Drawings



Connection Diagram



■ Characteristics

Junction Capacitance Characteristic (typ.)

