

FLEXIBLE PACKAGING 查物 200-002 供应商

Sensitive devices require protection from electrostatic fields and electrostatic discharges whenever they are outside an ESD Protected Area. Such protection is achieved by enveloping the device in a material with a conductive layer. It is generally felt that to provide an adequate shield the conductive layer must have a surface resistance of 1×10^5 ohm or less. Often, an ESD packaging material will also provide mechanical protection or protection against contamination by dust or humidity.

EN 100015-1 defines three levels of packaging: Intimate, Proximity and Secondary.

The following definitions are also included in the draft:

Antistatic: Packaging which minimizes charge generation by separation or rubbing with other materials.

Electrostatic discharge shielding: A barrier or enclosure that limits the passage of current and attenuates the energy resulting from an electrostatic discharge of 1000V to ≤ 50 nanojoules.

Electrostatic conductive: Packaging with a surface resistance $\geq 1 \times 10^3$ ohm and $< 1 \times 10^6$ ohm.

Electrostatic dissipative: Packaging with a surface resistance $\geq 1 \times 10^6$ ohm and $< 1 \times 10^{12}$ ohm.

Insulative: Packaging with a surface resistance $\geq 1 \times 10^{12}$ ohm.

The draft of the revision of EN 100 015 includes the following table of requirements:

INSIDE EPA		OUTSIDE EPA		
	Intimate	Proximity	Intimate	Proximity
ESDS	Either astatic and electrostatic conductive or astatic and electrostatic dissipative (for powered ESDS only astatic and electrostatic dissipative above 10 ⁹ shall be used)	Astatic and electrostatic shielding or Astatic and electrostatic conductive or dissipative	As for inside EPA	Electrostatic shielding
Non ESDS	Dissipative or astatic		No requirements	
NOTE: Where surface resistance > 10 ¹⁰ ohms is used, the material shall be procured with a T ₁₀₀₀ < 2sec				

INDEX TO FLEXIBLE PACKAGING SECTION

Antistatic pink tubing and bags	Page 41
Antistatic clear tubing and bags	Page 42
Conductive black tubing zip closure	Page 43
Metallised shielding bags	Page 44
Metallised shielding bags with zip closure	Page 44
Cushioned metallised bags	Page 45
Antistatic pink bubble rolls and bags	Page 45
Conductive black bubble rolls and bags	Page 45
Conductive foams	Page 46
Labels	Page 47
Adhesive tapes	Page 47

Note to film thickness:

1 micron = $10^{-6}\text{m} = 0.001\text{mm}$


100 gauge = 0.025mm therefore 300 gauge = 0.075mm or 75micron

100 gauge 1 thou = 1 mil (USA)

Note to bag dimension variations: Thickness variations may reach $\pm 6\%$ e.g. a 75micron film will vary between 70 and 80micron though in a large sample the average thickness will be between 73 and 77micron. Bag width and length variations $+ 20\text{mm} - 0\text{mm}$ to the normal metric dimension are tolerated. Tubing length variations may reach $\pm 3\%$.

Note to bag sizes: First dimension is bag width, second is bag length.

ANTISTATIC PINK TUBING AND BAGS



BQ3KL

- Suitable for use in EPA to hold non-ESD sensitive items
- Made of polyethylene, 0.075mm thick
- Amine free, humidity dependent additive
- Tough, puncture resistant
- $R_s < 10^{11}$, $T_{1000} < 2\text{sec}$ at 50% rH
- Bags are printed in black with ESD logo and text to EN 100 015, in bundles of 100
- Available as tubing unprinted on rolls up to 500m long and 825mm wide

