

POWER TVS COMPONENT

APPLICATIONS

- ✓ Relay Drives
- ✓ Motor (Start/Stop) Back EMF Protection
- ✓ Module Lightning Protection
- ✓ Secondary Lightning Protection for AC/DC

IEC COMPATIBILITY (EN61000-4)


- ✓ 61000-4-5 (Surge): 48A, 8/20 μ s - L3 (Line-Gnd), L4 (Line-Line) & L1 (Power)

FEATURES


- ✓ 15,000 Watts Peak Pulse Power per Line (tp=10/1000 μ s)
- ✓ Unidirectional & Bidirectional Configurations
- ✓ Easy Mounting to Printed Circuit Board
- ✓ Available in Multiple Voltage Types Ranging From: 17V to 220V
- ✓ RoHS Compliant in Lead-Free Versions (Exemption #7)

MECHANICAL CHARACTERISTICS

- ✓ Molded Case
- ✓ Weight 5 grams (Approximate)
- ✓ Flammability Rating UL 94V-0
- ✓ Available in Tin-Lead or Lead-Free Pure-Tin Plating(Annealed)
- ✓ Solder Reflow Temperature:
 - Tin-Lead - Sn/Pb, 85/15: 240-245°C
 - Pure-Tin - Sn, 100: 260-270°C
- ✓ Marking: Logo, Part Number & Date Code
- ✓ Positive Terminal Marked with Band - *Unidirectional Only*



APPLICATION



DEVICE CHARACTERISTICS

| MAXIMUM RATINGS @ 25°C Unless Otherwise Specified | | | |
|---|------------------|-------------|-------|
| PARAMETER | SYMBOL | VALUE | UNITS |
| Peak Pulse Power (tp =10/1000µs) - See Fig. 1 | P _{PP} | 15000 | Watts |
| Forward Surge Rating (1/20 seconds) - See Note 2 | I _F | 200 | Amps |
| Steady State Power Dissipation | P _D | 1.0 | Watts |
| Storage Temperature | T _{STG} | -55 to +150 | °C |
| Operating Temperature | T _J | -55 to +150 | °C |

| ELECTRICAL CHARACTERISTICS @ 25°C Unless Otherwise Specified | | | | | | |
|--|---|--------------------------------|-----------------------|---|---|---|
| PART NUMBER (Notes 1 & 2) | RATED STAND-OFF VOLTAGE V _{WM} VOLTS | BREAKDOWN VOLTAGE | | MAXIMUM LEAKAGE CURRENT @V _{WM} I _D µA | MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @ 10/1000µs V _C @ I _{PP} | TEMPERATURE COEFFICIENT OF V _(BR) qV _(BR) mV/°C |
| | | MIN V _(BR) VOLTS | @I _T mA | | | |
| 15KPA17 | 17.0 | 18.9 | 50 | 5000 | 32.3V @ 464.0A | 19 |
| 15KPA17A | 17.0 | 18.9 | 50 | 5000 | 29.3V @ 512.0A | 17 |
| 15KPA18 | 18.0 | 20.0 | 50 | 5000 | 34.2V @ 439.0A | 20 |
| 15KPA18A | 18.0 | 20.0 | 50 | 5000 | 30.9V @ 485.0A | 18 |
| 15KPA20 | 20.0 | 22.2 | 20 | 1500 | 37.9V @ 396.0A | 24 |
| 15KPA20A | 20.0 | 22.2 | 20 | 1500 | 34.3V @ 437.0A | 21 |
| 15KPA22 | 22.0 | 24.4 | 10 | 500 | 41.1V @ 365.0A | 27 |
| 15KPA22A | 22.0 | 24.4 | 10 | 500 | 37.1V @ 404.0A | 24 |
| 15KPA24 | 24.0 | 26.7 | 5 | 150 | 45.0V @ 333.0A | 30 |
| 15KPA24A | 24.0 | 26.7 | 5 | 150 | 40.7V @ 369.0A | 27 |
| 15KPA26 | 26.0 | 28.9 | 5 | 50 | 48.7V @ 308.0A | 32 |
| 15KPA26A | 26.0 | 28.9 | 5 | 50 | 44.0V @ 341.0A | 29 |
| 15KPA28 | 28.0 | 31.1 | 5 | 25 | 52.4V @ 286.0A | 35 |
| 15KPA28A | 28.0 | 31.1 | 5 | 25 | 47.5V @ 316.0A | 31 |
| 15KPA30 | 30.0 | 33.3 | 5 | 15 | 56.2V @ 267.0A | 27 |
| 15KPA30A | 30.0 | 33.3 | 5 | 15 | 50.7V @ 296.0A | 34 |
| 15KPA33 | 33.0 | 36.7 | 5 | 10 | 60.6V @ 248.0A | 42 |
| 15KPA33A | 33.0 | 36.7 | 5 | 10 | 54.8V @ 274.0A | 38 |
| 15KPA36 | 36.0 | 40.0 | 5 | 10 | 66.0V @ 227.0A | 46 |
| 15KPA36A | 36.0 | 40.0 | 5 | 10 | 59.7V @ 251.0A | 41 |
| 15KPA40 | 40.0 | 44.4 | 5 | 10 | 72.8V @ 206.0A | 51 |
| 15KPA40A | 40.0 | 44.4 | 5 | 10 | 65.8V @ 228.0A | 46 |
| 15KPA43 | 43.0 | 47.8 | 5 | 10 | 77.1V @ 195.0A | 55 |
| 15KPA43A | 43.0 | 47.8 | 5 | 10 | 69.7V @ 215.0A | 50 |
| 15KPA45 | 45.0 | 50.0 | 5 | 10 | 80.7V @ 186.0A | 57 |
| 15KPA45A | 45.0 | 50.0 | 5 | 10 | 73.0V @ 205.0A | 52 |
| 15KPA48 | 48.0 | 53.3 | 5 | 10 | 85.9V @ 175.0A | 62 |
| 15KPA48A | 48.0 | 53.3 | 5 | 10 | 77.7V @ 193.0A | 56 |
| 15KPA51 | 51.0 | 56.7 | 5 | 10 | 91.5V @ 164.0A | 66 |
| 15KPA51A | 51.0 | 56.7 | 5 | 10 | 82.8V @ 181.0A | 60 |
| 15KPA54 | 54.0 | 60.0 | 5 | 10 | 96.8V @ 155.0A | 70 |
| 15KPA54A | 54.0 | 60.0 | 5 | 10 | 87.5V @ 171.0A | 63 |
| 15KPA58 | 58.0 | 64.4 | 5 | 10 | 104.0V @ 144.0A | 76 |
| 15KPA58A | 58.0 | 64.4 | 5 | 10 | 94.0V @ 160.0A | 68 |
| 15KPA60 | 60.0 | 66.7 | 5 | 10 | 107.0V @ 140.0A | 78 |
| 15KPA60A | 60.0 | 66.7 | 5 | 10 | 97.3V @ 154.0A | 71 |
| 15KPA64 | 64.0 | 71.1 | 5 | 10 | 115.0V @ 130.0A | 84 |
| 15KPA64A | 64.0 | 71.1 | 5 | 10 | 104.0V @ 144.0A | 76 |
| 15KPA70 | 70.0 | 77.8 | 5 | 10 | 126.0V @ 119.0A | 92 |
| 15KPA70A | 70.0 | 77.8 | 5 | 10 | 114.0V @ 132.0A | 83 |

ELECTRICAL CHARACTERISTICS @ 25°C Unless Otherwise Specified


| PART NUMBER (Notes 1 & 2) | RATED STAND-OFF VOLTAGE V_{WM} VOLTS | BREAKDOWN VOLTAGE | | MAXIMUM LEAKAGE CURRENT I_D @ V_{WM} μA | MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @ 10/1000 μs V_C @ I_{PP} | TEMPERATURE COEFFICIENT OF $V_{(BR)}$ $qV_{(BR)}$ mV/ $^{\circ}C$ |
|------------------------------|--|-------------------------|---------------|---|---|---|
| | | MIN $V_{(BR)}$ VOLTS | @ I_T mA | | | |
| 15KPA75 | 75.0 | 83.3 | 5 | 10 | 135.0V @ 111.0A | 100 |
| 15KPA75A | 75.0 | 83.3 | 5 | 10 | 122.0V @ 123.0A | 89 |
| 15KPA78 | 78.0 | 86.7 | 5 | 10 | 140.0V @ 107.0A | 104 |
| 15KPA78A | 78.0 | 86.7 | 5 | 10 | 126.0V @ 119.0A | 93 |
| 15KPA85 | 85.0 | 94.4 | 5 | 10 | 152.0V @ 99.0A | 113 |
| 15KPA85A | 85.0 | 94.4 | 5 | 10 | 137.0V @ 109.0A | 102 |
| 15KPA90 | 90.0 | 100.0 | 5 | 10 | 160.0V @ 94.0A | 120 |
| 15KPA90A | 90.0 | 100.0 | 5 | 10 | 146.0V @ 103.0A | 109 |
| 15KPA100 | 100.0 | 111.0 | 5 | 10 | 179.0V @ 84.0A | 134 |
| 15KPA100A | 100.0 | 111.0 | 5 | 10 | 162.0V @ 93.0A | 121 |
| 15KPA110 | 110.0 | 122.0 | 5 | 10 | 196.0V @ 77.0A | 147 |
| 15KPA110A | 110.0 | 122.0 | 5 | 10 | 178.0V @ 84.0A | 133 |
| 15KPA120 | 120.0 | 133.0 | 5 | 10 | 214.0V @ 70.0A | 161 |
| 15KPA120A | 120.0 | 133.0 | 5 | 10 | 193.0V @ 78.0A | 145 |
| 15KPA130 | 130.0 | 144.0 | 5 | 10 | 231.0V @ 65.0A | 174 |
| 15KPA130A | 130.0 | 144.0 | 5 | 10 | 209.0V @ 72.0A | 157 |
| 15KPA150 | 150.0 | 167.0 | 5 | 10 | 268.0V @ 56.0A | 202 |
| 15KPA150A | 150.0 | 167.0 | 5 | 10 | 243.0V @ 62.0A | 183 |
| 15KPA160 | 160.0 | 178.0 | 5 | 10 | 287.0V @ 52.0A | 216 |
| 15KPA160A | 160.0 | 178.0 | 5 | 10 | 259.0V @ 58.0A | 195 |
| 15KPA170 | 170.0 | 189.0 | 5 | 10 | 304.0V @ 49.0A | 229 |
| 15KPA170A | 170.0 | 189.0 | 5 | 10 | 275.0V @ 55.0A | 207 |
| 15KPA180 | 180.0 | 200.0 | 5 | 10 | 321.0V @ 47.0A | 242 |
| 15KPA180A | 180.0 | 200.0 | 5 | 10 | 291.0V @ 52.0A | 219 |
| 15KPA200 | 200.0 | 222.0 | 5 | 10 | 356.0V @ 42.0A | 269 |
| 15KPA200A | 200.0 | 222.0 | 5 | 10 | 322.0V @ 47.0A | 243 |
| 15KPA220 | 220.0 | 245.0 | 5 | 10 | 393.0V @ 38.0A | 297 |
| 15KPA220A | 220.0 | 245.0 | 5 | 10 | 356.0V @ 42.0A | 269 |
| 15KPA240 | 240.0 | 267.0 | 5 | 10 | 428.0V @ 35.0A | 324 |
| 15KPA240A | 240.0 | 267.0 | 5 | 10 | 388.0V @ 39.0A | 293 |
| 15KPA260 | 260.0 | 289.0 | 5 | 10 | 464.0V @ 32.0A | 352 |
| 15KPA260A | 260.0 | 289.0 | 5 | 10 | 419.0V @ 36.0A | 317 |
| 15KPA280 | 280.0 | 311.0 | 5 | 10 | 500.0V @ 30.0A | 378 |
| 15KPA280A | 280.0 | 311.0 | 5 | 10 | 452.0V @ 33.0A | 342 |

Note 1: Part numbers shown are unidirectional devices. Add a "CA" suffix to specify bidirectional devices, such as 15KPA20CA.


Note 2: $V_F = 7.5$ Volts @ 200A, 8.3ms (1/2 Sine Wave) - unidirectional devices only.

GRAPHS


**FIGURE 1
PEAK PULSE POWER VS PULSE TIME**





**FIGURE 2
PULSE WAVEFORM**



**FIGURE 3
POWER DERATING CURVE**



PACKAGE OUTLINE & DIMENSIONS

| PACKAGE OUTLINE | | AXIAL LEAD | | | |
|--|-------------|---|-----------|-----------|--|
|  | |  | | | |
| PACKAGE DIMENSIONS | | | | | |
| DIM | MILLIMETERS | | INCHES | | |
| | MIN | MAX | MIN | MAX | |
| A | 24.5 | - | 1.00 | - | |
| B | 8.60 | 9.10 | 0.34 | 0.36 | |
| C | 24.5 | - | 1.00 | - | |
| D | 1.20 DIA | 1.30 DIA | 0.048 DIA | 0.052 DIA | |
| E | 8.60 | 9.10 | 0.34 | 0.36 | |
| NOTES | | | | | |
| 1. Dimensions are exclusive of mold flash and metal burrs. 2. Suffix - LF = Lead-Free, Pure-Tin Plating, i.e., 15KPA90A-LF. | | | | | |
| Outline & Dimensions: Rev 0 - 12/01, 06028 | | | | | |

COPYRIGHT © ProTek Devices 2005

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices
 2929 South Fair Lane, Tempe, AZ 85282
 Tel: 602-431-8101 Fax: 602-431-2288
 E-Mail: sales@protekdevices.com
 Web Site: www.protekdevices.com