

FEATURES AND SPECIFICATIONS

[查询"19286-0117"供应商](#)

Features and Benefits

- Multiple crimping dies available for a wide wire range, which provides production flexibility
- Crimping dies are easily and quickly interchanged to reduce production downtime
- Lightweight system that allows the tool to be moved and stored easily

Specifications

Pneumatic: Supply Pressure —100 PSI
Air Pressure —125 PSI max.
Cycle Time: 15 seconds



Application Tooling Manual PPHLS

19286-0117

Putt Pump Hydraulic Head Crimper for Insulated and Non-Insulated Terminals and Splices



ORDERING INFORMATION

Order No.	Wire Gauge (AWG)	Die Set for the PPDH 19286-0117	
		VersaKrimp™ Terminals and Splices	NylaKrimp™/InsulKrimp™ Terminals and Splices
19286-0117	8	19290-0001	19289-0001
19286-0117	6	19290-0004	19289-0004
19286-0117	4	19290-0007	19289-0007
19286-0117	2	19290-0010	19289-0010
19286-0117	1		
19286-0117	1/0	19290-0011	19289-0011
19286-0117	2/0	19290-0012	19289-0025
19286-0117	3/0	19290-0028	19289-0028
19286-0117	4/0	19290-0031	19289-0031



Bringing People & Technology Together, WorldwideSM

Americas Headquarters
Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Far East North Headquarters
Yamato, Kanagawa, Japan
81-462-65-2324
feninfo@molex.com

Far East South Headquarters
Jurong, Singapore
65-6-268-6868
fesinfo@molex.com
Visit our website at www.molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
630-969-4550
Fax: 630-969-1352