



Led Signalleuchten Einbaudurchmesser 8 mm
Led Signalleuchten Body diameter 8 mm

Superflach, Abstrahlwinkel 80°
Superflat, viewing angle 80°

[查询"19010250"供应商](#)

Bestell-Nr.	Farbe	V _{OP} +10%	I _{OP max.}	V _F	I _{V typ} (mcd)	I _{F max.}	Abb.	Abmessungen, siehe Zeichnungsnr.			
Part No.	Colour	(V)	(mA)	(V)	*I _F = 20mA	(mA)	Illu.	Dimensions, see Drawing No.	19010-A		
19010000	Rot Red			1,6/2,0	*1,0	50	A				
19010001	Grün Green			2,4/3,0	*8,0	30	A				
19010002	Gelb Yellow			2,4/3,0	*8,0	30	A				
19010003	Super rot Super red			2,4/3,0	*8,0	30	A				
19010050	Rot Red			1,6/2,0	*1,0	50	C				
19010051	Grün Green			2,4/3,0	*8,5	30	C				
19010052	Gelb Yellow			2,4/3,0	*8,5	30	C				
19010053	Super rot Super red			2,4/3,0	*8,0	30	C				
19010150	Rot Red	6	30		1,3		B	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19010-B		
19010151	Grün Green	6	30		13,5		B				
19010152	Gelb Yellow	6	30		12,5		B				
19010153	Super rot Super red	6	30		14,5		B				
19010250	Rot Red	12	30		1,3		B				
19010251	Grün Green	12	30		13,5		B				
19010252	Gelb Yellow	12	30		12,5		B				
19010253	Super rot Super red	12	30		14,5		B				
19010350	Rot Red	24	22		1,2		B				
19010351	Grün Green	24	22		10,0		B				
19010352	Gelb Yellow	24	22		9,0		B			19010050 - 19010053, wird als verkürzte Ausführung mit Steckkontakten geliefert, siehe Zeichnung Nr. 19010-C 19010050 - 19010053, short version with tabs, see drawing no. 19010-C	
19010353	Super rot Super red	24	22		11,0		B				

Arbeitstemperatur (T_{OP}): -55°C - +70°C
Lagertemperatur (T_{STG}): -55°C - +100°C

Nur in Glanzchrom lieferbar

Operating temperature (T_{OP}): -55°C - +70°C
Storage temperature (T_{STG}): -55°C - +100°C

Available in bright chrome only

Led Signalleuchten mit anderen Spannungen auf Anfrage
Technische Änderungen vorbehalten

Led Indicators with other voltages upon request
Specification subject to change without notice