


## ENERGIZER NO. 1209



Industry Standard Dimensions in mm (inches)



THIS BATTERY WILL PASS FREELY THROUGH A CYLINDRICAL TUBE 82.6 DIAMETER x 101.6 LONG.

**6V**

**SUPER HEAVY DUTY**

**Chemical System:** Zinc-Manganese Dioxide (Zn/MnO<sub>2</sub>)  
(No Added Mercury or Cadmium)

**Designation:** ANSI-908D, IEC-4R25  
**Battery Voltage:** 6.0 Volts  
**Operating Temp:** -18°C to 55°C (0°F to 130°F)  
**Average Weight:** 600 grams (21.2 oz.)  
**Volume:** 492 cubic centimeters (30 cubic inch)  
**Average Capacity:** 11 Ah to 0.8 volts / cell  
(Rated at 25mA continuous at 21°C)

**Cell:** Four No. 60 (size "F") in series  
**Jacket:** Plastic  
**Terminal:** Coil Spring


### INTERNAL RESISTANCE VS. TEMPERATURE

The measurement is an approximation of the battery's actual internal resistance. It is sensitive to the loads and operator technique.


**Schedule:** Background Load 600 ohms  
 Pulse Load 10 ohms  
 Pulse Duration 1 second

Temperature	Typical Ri (ohms)
45°C (113°F)	0.7
21°C (70°F)	0.9
0°C (32°F)	1.0
-21°C (-4°F)	10.0

**CONSTANT RESISTANCE PERFORMANCE**  
Typical Service



**CONSTANT CURRENT DISCHARGE**  
Typical Service




### Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.  
**Contents herein do not constitute a warranty.**


## ENERGIZER NO. 1209

### Typical Applications


**BARRICADE STEADY BURN**  
110 ohm - 12 HOURS/DAY




**BARRICADE FLASHER**  
110 ohms 100 millisc/sec - 24 hours/day




**PORTABLE LIGHT**  
8.2 ohm - 30 min/day



**LIGHTING**  
9.1 ohm - 30 min/on 30min/off 8 hr/day



**PORTABLE LIGHT**  
33 ohms 30 min/hour - 8 hours/day



### Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.  
Contents herein do not constitute a warranty.