

[查询“CS1213BJF260”供应商](#)

SPECIFICATIONS

| | |
|-----------------------|------------------------------|
| Electrical Ratings | 50mA @ 50VDC |
| Electrical Life | 200,000 cycles typical |
| Contact Resistance | < 50 mΩ initial |
| Actuation Force | 160 +/- 50gF 260 +/- 50gF |
| Actuator Travel | .15 +/- .05mm |
| Dielectric Strength | 250Vrms min |
| Insulation Resistance | > 100MΩ min |
| Operating Temperature | -40°C to 85°C |
| Storage Temperature | -40°C to 85°C |




MATERIALS ←RoHS COMPLIANT

| | |
|-----------|--------------------------------|
| Actuator | 4/6 Nylon |
| Housing | 4/6 Nylon |
| Cover | Stainless Steel |
| Contacts | Stainless Steel, Silver Plated |
| Terminals | Brass, Silver Plated |


ORDERING INFORMATION

| | | | | |
|--|---------------------------|----------|----------|-------------|
| 1. Series: | CS1213 | A | J | F160 |
| CS1213 | | | | |
| 2. Locating Boss Option: | | | | |
| A = Without Boss | | | | |
| B = With Boss | | | | |
| 3. Terminal Option: | | | | |
| G = Gull Wing | | | | |
| J = J Lead | | | | |
| L = 4 terminal Gull Wing | | | | |
| LE = 4 terminal Gull Wing, with earth ground | **Not available with boss | | | |
| 4. Actuation Force: | | | | |
| F160 = 160gF | | | | |
| F260 = 260gF | | | | |

DIMENSIONS



CS1213AG




CS1213AJ

SCHEMATIC & PC LAYOUTS




DIMENSIONS




SCHEMATIC & PC LAYOUTS






CS1213BG






CS1213BJ



CS1213AL



CS1213ALE



CS1213BL

