

SPECIFICATION SHEET.

Description:	Wrist Band.
Colour:	Light Blue.
Coating:	Polyurethane Based Polymer Oven Baked Epoxy. Non-Peeling And Non-Rusting Tested. MIL STD 202 Method 101.
Covering:	Sides, Top And Bottom Insulated.
Fastening:	10mm
Band Construction:	Stainless Steel. Expandable Link Band Consisting Of Two Layers. Non-Rusting Tested to MIL STD. 202 Meth. 101 Thickness: 3.5mm Average Weight: 33 grams
Conductivity:	Inner Band: Conductive 150 ohms. Outer Band: Insulated at 500v per unit mil Polyurethane-bases polymer on oven-baked epoxy. Non-peeling/non-rusting when tested under Mil Std. 202, Meth 101.
Connector Types:	10mm with full 360o rotation.
Expansion Ratio:	1.5 to 1
Standards:	Made and tested in accordance with: DOD-HDBK-263 DOD-STD-1686 UK DEF STD 5 9-98 EOS/ESD DS No. 1

Inner Band Is Conductive 150 OHM, The Outer Coating Is Insulated Also Around The Edges Tested To 500v MIL.

SIZE BANDS AVAILABLE ARE:

<u>OK PART NO.</u>	<u>FEC PART NO.</u>	<u>SIZE.</u>
23-0563	178-436	Small 130mm
23-0562	178-437	Medium 150mm
23-0561	178-438	Large 170mm