


Thin Film 0303 Size Resistor on Alumina



Product may not
be to scale

FEATURES

- Wire bondable
- Chip size: 0.030 inches square
- Resistance range: 25 Ω to 38 k Ω
- Alumina substrate
- Low stray capacitance: < 0.2 pF
- Resistor material: Nichrome
- Resistor passivation coat optional
- Tolerances to 0.05 %

The CC2 series single-value resistor chips offer a relatively small size, low shunt capacitance and solder pad option. The CC2s nichrome resistor material offers excellent stability.

The CC2s are manufactured using Vishay Electro Films (EFI) sophisticated thin film equipment and manufacturing technology. The CC2s are 100 % electrically tested and visually inspected to MIL-STD-883.


APPLICATIONS

Vishay EFI CC2 chip resistors provide excellent high-frequency response and are ideally suited for prototyping. Typical application areas are:

- Amplifiers
- Oscillators
- Attenuators
- Couplers
- Filters

Recommended for hermetic environments where die is not exposed to moisture.


TEMPERATURE COEFFICIENT OF RESISTANCE, VALUES AND TOLERANCES



STANDARD ELECTRICAL SPECIFICATIONS

PARAMETER	
Noise, MIL-STD-202, Method 308	- 20 dB typ.
Moisture Resistance, MIL-STD-202 Method 106 - Hermetic Applications	± 0.2 % max. $\Delta R/R$
Stability, 1000 h, + 125 °C, 100 mW	± 0.1 % max. $\Delta R/R$
Operating Temperature Range	- 55 °C to + 125 °C
Thermal Shock, MIL-STD-202, Method 107, Test Condition F	± 0.25 % max. $\Delta R/R$
High Temperature Exposure, + 150 °C, 100 h	± 0.1 % max. $\Delta R/R$
Dielectric Voltage Breakdown	400 V
Insulation Resistance	10^{12} min.
Operating Voltage	100 V
DC Power Rating at + 125 °C (Derated to Zero at + 150 °C)	100 mW max.
5 x Rated Power Short-Time Overload, + 25 °C, 5 s	± 0.25 % max. $\Delta R/R$

DIMENSIONS in inches



SCHEMATIC



MECHANICAL SPECIFICATIONS in inches

PARAMETER	
Chip Size	0.030 x 0.030 ± 0.003 (1.27 mm x 1.27 mm ± 0.076 mm)
Chip Thickness	0.010 ± 0.002 (0.25 mm ± 0.05 mm)
Chip Substrate Material	99.6 % alumina, 2 microinches to 4 microinches finish
Resistor Material	Nichrome
Bonding Pad Size	0.004 x 0.006 (0.100 mm x 0.15 mm) minimum
Number of Pads	2
Pad Material	25 kÅ minimum gold standard
Backing	None

GLOBAL PART NUMBER INFORMATION

Global Part Number: CC2-12500KKSSNHWS

Global Part Number Description: CC2- 1.25K 10 %, 100 ppm/°C, std trim, SnPb terminations, no back metal, class H, WS

C C 2 - 1 2 5 0 0 K K S S N H W S

MODEL	RESISTANCE	RES. MULTIPLIER CODE	TOL. CODE (%)	TCR (ppm/°C)	TRIM STYLE	TERMINATION	BACK METAL	VISUAL CLASS	PACKAGING CODE
CC2-	First 4 digits are significant figures of resistance	B = 0.01 A = 0.1 0 = 1 1 = 10	A = 0.05 B = 0.1 C = 0.25 D = 0.5 F = 1.0 G = 2.0 J = 5.0 K = 10	E = ± 25 C = ± 50 K = ± 100	E = Edg S = Std U = Usr	G = Au S = SnPb A = Al T = Lead (Pb)-free (e1)	G = Au N = None	H = Class H K = Class K	WS = Waffle pack 100 min, 1 mult

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.