


# Cermet Trimmers, 15 Turns


## FEATURES

- General use type
- Wide resistance range from 10Ω to 5MΩ




## DIMENSIONS in millimeters


### CT-20P Side Adjustment



### CT-20X Side Adjustment



### CT-20PB



## ELECTRICAL SPECIFICATIONS

Nominal Resistance Range	10Ω ~ 5MΩ
Nominal Resistance Tolerance	± 10 %
Power Ratings	0.5 W (70 °C) 0 W (120 °C)
Resistance Law	Linear law (B)
Maximum Input Voltage	DC300 V or power rating, whichever is smaller
Maximum Wiper Current	100 mA or power rating, whichever is smaller
Effective Electrical Turn	12 turns
End Resistance	1 % or 2 Ω, whichever is greater
C.R.V.	1 % or 3 Ω, whichever is greater
Operating Temperature Range	- 55 ~ + 120 °C
Temperature Coefficient	10 Ω, 20 Ω, 5 MΩ: ± 250 10 <sup>-6</sup> /°C maximum 50 Ω ~ 2 MΩ: ± 100 10 <sup>-6</sup> /°C maximum
Insulation Resistance	1000 MΩ minimum (DC500 V)
Dielectric Strength	AC600 V, 60 s
Net Weight	Approx. 1.08 g (CT-20P, X) Approx. 3.7 g (CT-20PB)

**MECHANICAL SPECIFICATIONS**

<b>Mechanical Turn</b>	15 turns
<b>Operating Torque</b>	35 mN·m {357 gf·cm} maximum
<b>Mechanical Stop</b>	Clutch action
<b>Rotational Life</b>	200 cycles 10Ω ~ 200Ω [ΔR/R ≤ ± (0.5 Ω + 3 %)] 500 Ω ~ 5 MΩ [ΔR/R ≤ ± (0.5 Ω + 2 %)]
<b>Terminal Strength</b>	9 N {917 gf} minimum (Tensile strength)
<b>Thrust To Rotor</b>	10 N {1.02 kgf} minimum
<b>Solderability</b>	235 °C, 2 s


STANDARD RESISTANCE TABLE			
NOMINAL RESISTANCE VALUES (Ω)	RESISTANCE CODE	MAXIMUM INPUT VOLTAGE (V)	MAXIMUM WIPER CURRENT (mA)
10*	100	1.00	100
20*	200	2.00	100
50	500	5.00	100
100	101	7.07	70.7
200	201	10.0	50.0
500	501	15.8	31.6
1 k	102	22.4	22.4
2 k	202	31.6	15.8
5 k	502	50.0	10.0
10 k	103	70.7	7.07
20 k	203	100	5.00
50 k	503	158	3.16
100 k	104	224	2.24
200 k	204	300	1.50
500 k	504	300	0.60
1 M	105	300	0.30
2 M	205	300	0.15
5 M*	505	300	0.06

\*Manufactured upon receipt of order basis.

**ENVIRONMENTAL SPECIFICATIONS**

<b>Thermal Shock</b>	-65 ~ 125 °C (0.5 h), 5 cycles	[ΔR/R ≤ 1 %] [S.S. ≤ 1 %]
<b>Humidity</b>	-10 ~ 65 °C (Relative humidity 80 ~ 98 %), 10 cycles, 240 h	[ΔR/R ≤ 1 %]
<b>Shock</b>	981 m/s <sup>2</sup> , 6 ms 6 directions for 3 times each	
<b>Vibration</b>	Amplitude 1.52 mm or Acceleration 196 m/s <sup>2</sup> , 10 ~ 2000Hz, 3 directions, 12 times each	[ΔR/R ≤ 1 %] [S.S. ≤ 1 %]
<b>Load Life</b>	70 °C, 0.5 W, 1000 h	[ΔR/R ≤ 2 %] [S.S. ≤ 1 %]
<b>Low Temperature Operation</b>	-55 °C, 2 h	[ΔR/R ≤ 1 %] [S.S. ≤ 2 %]
<b>High Temperature Exposure</b>	120 °C, 250 h	[ΔR/R ≤ 2 %] [S.S. ≤ 2 %]
<b>Immersion Seal</b>	85 °C, 60 s	No leaks (No continuous bubbles)
<b>Soldering Heat</b>	350 °C, 3 s	[ΔR/R ≤ 1 %]

ΔR/R: Change in total resistance  
S.S.: Setting stability






CONSTRUCTION			
	PART NAME	MATERIAL	FLAMMABILITY
1	Shaft	Brass, Nickel-plated	-
2	Housing	Polybutyleneterephthalate	UL-94V-0
3	Terminal pin	Copper, Solder-plated	-
4	Adhesive	Epoxy	UL-94V-0
5	Base element	Ceramic	-
6	Wiper	Multi metal alloy	UL-94HB
7	Resistive element	RuO <sub>2</sub> cermet	
8	Slider block	Polybutyleneterephthalate	-
9	Rubber cushion	Silicone rubber	
10	Electrode	Ag-Pd cermet	

CFCs, Halon, Carbon tetrachloride and designated bromic flame retardant PBBs and PBBs are not used in our products.

**PACKAGING SPECIFICATIONS**

**Vinyl bag packaging specifications**

- Unit of bulk in vinyl bag packaging is 50 pcs. (CT-20PB is 25 pcs.) per pack.
- Boxing of bulk in vinyl bags is performed with 100 pcs. (CT-20PB is 50 pcs.) per box.

<b>LIST OF PART NUMBERS</b>			
ADJUSTMENT POSITION	SHAPE OF TERMINAL (TOP VIEW)	FORM OF PACKAGING	PIECES IN PACKAGE
		VINYL BAG	
Side adjustment (Adjustment direction)		CT-20P	50 pcs./pack
		CT-20X	
		CT-20PB	25 pcs./pack

<b>NOMINAL RESISTANCE VALUES</b>								
10 Ω*	20 Ω*	50 Ω	100 Ω	200 Ω	500 Ω	1 kΩ	2 kΩ	5 kΩ
10 kΩ	20 kΩ	50 kΩ	100 kΩ	200 kΩ	500 kΩ	1 MΩ	2 MΩ	5 MΩ*

- The above part numbers are all available with the respective combination of <Nominal resistance values>.
  - Verify the above part numbers when placing orders.
- \*Manufactured upon receipt of order basis.

<b>ORDERING INFORMATION</b>			
<b>CT20</b> SERIES	<b>TERMINAL PIN</b> Blank: Sn-Pb E: Sn (Lead-free)	<b>P</b> PRODUCT SHAPE P: Side adjustment X: Side adjustment PB: Panel mount	<b>204</b> RESISTANCE CODE

This product is manufactured by Copal Electronics Co. Ltd. of Tokyo, Japan and is distributed by Vishay in North and South America only.  
 This product is not available from Vishay outside of North or South America.

## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.