



查询"1321040-16"供应商



PIN OUT

P1	P2	P1	P2	P1	P2
1 WHITE	1	6 WHITE	6	C1 RED	C1
2 ORANGE	2	7 YELLOW	7	C5 GREEN	C5
3 DRAIN	3	17 WHITE	17	C2 GREEN	C2
4 DRAIN	4	18 YELLOW	18	C5 BLUE	C5
5 BROWN	5	19 DRAIN	19	C3 BLUE	C3
		20 DRAIN	20	C5 YELLOW	C5
9 WHITE	9	21 WHITE	21	C4 YELLOW	C4
10 BLACK	10	22 GREEN	22	8 BLUE	8
11 DRAIN	11			14 RED	14
12 DRAIN	12			15 BLACK	15
13 WHITE	13			16 BROWN	16
				SHELL BRAID SHELL	

NOTES:

- CABLE: UL20276
[(28AWGx1P+DW+FOIL)x7+(28AWG+SP+FOIL)x3+28AWGx5C+28AWGx1P+MYLAR+FOIL+BD]x1
OUTER JACKET: BEIGE, OD: 9.5 ± 0.3mm
PRINTING: "E166307" AWM 20276 28AWG 80°C 30V VW-1
LOW VOLTAGE COMPUTER CABLE
- CONNECTORS: DVI (24+5)P/M - DVI (24-5)P/M
- HOOD: ASS'Y TYPE. COLOR: BEIGE
- CABLE ELECTRICAL TEST:
<1>.100% OPEN SHORT & MISS WIRE TEST
<2>.INSULATION RESISTANCE: DC400V 10M ohm MIN.
<3>.CONDUCTOR RESISTANCE: 1 ohm MAX.
- PACKING: 1PC/POLYBAG

REVISION			
REV.	DESCRIPTION	DATE	APPROVED

No.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARKS
①	DVI (24+5)P/M - CONTACT	BRONZE/GOLD PLATED SOLDER TYPE	58	
②	DVI (24+5)P/M - INSULATOR	THERMOPLASTIC/BLACK UL94V-0	2	
③	DVI (24+5)P/M - SHELL	GOLD PLATED	2	
④	DVI (24+5)P/M - CAN	STEEL TIN PLATED	2	
⑤	COPPER FOIL	WIDTH: 15mm	2	
⑥	DVI (24+5)P/M - COVER	45P PVC/COLOR: BEIGE	2	
⑦	THUMB SCREW	#4-40 2.8x45, GOLD PLATED	4	
⑧	SCREW - MOLD	35P PVC / COLOR: BEIGE	4	
⑨	CABLE DVI 24+5 UL20276	KL03009ABK01A	1	
⑩	MINI TIE	PE/BLACK	2	
⑪	POLYBAG	PE/0.08x240x280mm	1	

Dim range (mm)	Tolerance +/- (mm)	Qualtek Electronics Corp. WCI DIVISION		
		Part Number: 1321040-16		RoHS Compliant
0-1	0.15	Description: DVI (24+5)P/M - DVI (24-5)P/M		
1-6	0.20			
6-18	0.30			
18-50	0.50			
50-120	0.70	Drawn / Date	Checked / Date	Approved / Date
120-250	0.90	B.Grubb 03-12-07	03-12-07	JJH / 03-12-07
250-500	1.20			