



5962-E218

1. SCOPE

1.2 Part number. The complete part number shall be as shown in the following example:

5962-87808

Drawing number

01

Device type
(1.2.1)

E

Case outline
(1.2.2)

x

Lead finish per
MIL-M-38510

Device type

Generic number

Circuit function

01

54HC192

Counter, decade, up/down, 4-bit synchronous
with asynchronous reset

Outline letter

Case outline

E
2

D-2 (16-lead, 1/4" x 7/8"), dual-in-line package
C-2 (20-terminal, .350" x .350"), square chip carrier package

Supply voltage range	- - - - -	-0.5 V dc to +7.0 V dc
DC input voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
DC output voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
Clamp diode current	- - - - -	± 20 mA
DC output current (per pin)	- - - - -	± 25 mA
DC V_{CC} or GND current (per pin)	- - - - -	± 50 mA
Storage temperature range	- - - - -	-65°C to $+150^{\circ}\text{C}$
Maximum power dissipation (P_D)	2/ - - - - -	500 mW
Lead temperature (soldering, 10 seconds)	- - - - -	$+260^{\circ}\text{C}$
Thermal resistance, junction-to-case (θ_{JC}):		
Case R	- - - - -	See MIL-M-38510, appendix C
Case 2	- - - - -	60°C/W 3/
Junction temperature (T_J)	- - - - -	$+175^{\circ}\text{C}$

2/ For $T_C = +100^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, derate linearly at $12\text{ mW}/^{\circ}\text{C}$.

3/ When a thermal resistance for this case is published in MIL-M-38510, appendix C, that value shall supersede the value indicated herein.

1.4 Recommended operating conditions.

Supply voltage (V_{CC})	- - - - -	+2.0 V dc to +6.0 V dc
Case operating temperature range (T_C)	- - - - -	-55°C to +125°C
Input rise or fall time:		
$V_{CC} = 2.0$ V	- - - - -	0 to 1000 ns
$V_{CC} = 4.5$ V	- - - - -	0 to 500 ns
$V_{CC} = 6.0$ V	- - - - -	0 to 400 ns
Minimum setup time, data to load (t_S):		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	110 ns
$V_{CC} = 4.5$ V	- - - - -	22 ns
$V_{CC} = 6.0$ V	- - - - -	19 ns
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	165 ns
$V_{CC} = 4.5$ V	- - - - -	33 ns
$V_{CC} = 6.0$ V	- - - - -	28 ns
Minimum hold time, data to load (t_H):		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	5 ns
$V_{CC} = 4.5$ V	- - - - -	5 ns
$V_{CC} = 6.0$ V	- - - - -	5 ns
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	5 ns
$V_{CC} = 4.5$ V	- - - - -	5 ns
$V_{CC} = 6.0$ V	- - - - -	5 ns
Minimum clear/load pulse width (t_W):		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	260 ns
$V_{CC} = 4.5$ V	- - - - -	52 ns
$V_{CC} = 6.0$ V	- - - - -	45 ns
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	390 ns
$V_{CC} = 4.5$ V	- - - - -	78 ns
$V_{CC} = 6.0$ V	- - - - -	68 ns
Minimum count up/down pulse width (t_W)		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	125 ns
$V_{CC} = 4.5$ V	- - - - -	25 ns
$V_{CC} = 6.0$ V	- - - - -	21 ns
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	190 ns
$V_{CC} = 4.5$ V	- - - - -	38 ns
$V_{CC} = 6.0$ V	- - - - -	32 ns
Minimum recovery time, clear to clock (t_{REC})		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	50 ns
$V_{CC} = 4.5$ V	- - - - -	10 ns
$V_{CC} = 6.0$ V	- - - - -	9 ns
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	75 ns
$V_{CC} = 4.5$ V	- - - - -	15 ns
$V_{CC} = 6.0$ V	- - - - -	13 ns
Maximum frequency, count up/down (f_{MAX})		
$T_C = +25^\circ\text{C}$:		
$V_{CC} = 2.0$ V	- - - - -	3 MHz
$V_{CC} = 4.5$ V	- - - - -	18 MHz
$V_{CC} = 6.0$ V	- - - - -	20 MHz
$T_C = -55^\circ\text{C}$ to +125°C:		
$V_{CC} = 2.0$ V	- - - - -	2 MHz
$V_{CC} = 4.5$ V	- - - - -	11 MHz
$V_{CC} = 6.0$ V	- - - - -	12 MHz

MILITARY DRAWING

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO

SIZE

A

CODE IDENT. NO.

14933

DWG NO.

5962-87808

REV

PAGE

3

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Logic diagram. The logic diagram shall be as specified on figure 3.

3.2.4 Case outline. The case outline shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full recommended case operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_C \leq +125^{\circ}\text{C}$ 1/		Group A subgroups	Limits		Unit
					Min	Max	
High level output voltage	V_{OH}	$V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_O \leq 20 \mu\text{A}$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	1,2,3	1.9 4.4 5.9		V
		$ I_O \leq 4.0 \text{ mA}$	$V_{CC} = 4.5 \text{ V}$		3.7		
		$ I_O \leq 5.2 \text{ mA}$	$V_{CC} = 6.0 \text{ V}$		5.2		
Low level output voltage	V_{OL}	$V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_O \leq 20 \mu\text{A}$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	1,2,3		0.1 0.1 0.1	V
		$ I_O \leq 4.0 \text{ mA}$	$V_{CC} = 4.5 \text{ V}$			0.4	
		$ I_O \leq 5.2 \text{ mA}$	$V_{CC} = 6.0 \text{ V}$			0.4	
High level input voltage	V_{IH}	2/	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	1,2,3	1.5 3.15 4.2		V
Low level input voltage	V_{IL}	2/	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	1,2,3		0.3 0.9 1.2	V
Input capacitance	C_{IN}	$V_{IN} = 0 \text{ V}$, $T_C = +25^{\circ}\text{C}$ see 4.3.1c		4		10	pF
Quiescent current	I_{CC}	$V_{CC} = 6.0 \text{ V}$; $V_{IN} = V_{CC} \text{ or GND}$		1,2,3		160	μA
Input leakage current	I_{IN}	$V_{CC} = 6.0 \text{ V}$; $V_{IN} = V_{CC} \text{ or GND}$		1,2,3		± 1	μA
Functional tests		see 4.3.1d		7			

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 5

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_C \leq +125^{\circ}\text{C}$ 1/		Group A subgroups	Limits		Unit
					Min	Max	
Propagation delay time clear to Q 3/	t _{PHL1}	$T_C = +25^{\circ}\text{C},$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	9		265 53 45	ns
See figure 4		$T_C = -55^{\circ}\text{C}, +125^{\circ}\text{C}$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	10,11		398 80 68	ns
Propagation delay time load to Q 3/	t _{PHL2} , t _{PLH2}	$T_C = +25^{\circ}\text{C},$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	9		290 58 49	ns
See figure 4		$T_C = -55^{\circ}\text{C}, +125^{\circ}\text{C}$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	10,11		435 87 74	ns
Propagation delay time count up/down to Q 3/	t _{PHL3} , t _{PLH3}	$T_C = +25^{\circ}\text{C},$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	9		275 55 47	ns
See figure 4		$T_C = -55^{\circ}\text{C}, +125^{\circ}\text{C}$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	10,11		413 83 71	ns
Propagation delay time count down to borrow or count up to carry 3/	t _{PHL4} , t _{PLH4}	$T_C = +25^{\circ}\text{C},$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	9		165 33 28	ns
See figure 4		$T_C = -55^{\circ}\text{C}, +125^{\circ}\text{C}$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$ $V_{CC} = 4.5 \text{ V}$ $V_{CC} = 6.0 \text{ V}$	10,11		250 50 43	ns

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 6

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_C \leq +125^{\circ}\text{C}$ 1/		Group A subgroups	Limits		Unit
					Min	Max	
Transition time 4/	t_{THL} , t_{TLH}	$T_C = +25^{\circ}\text{C}$, $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$	9		75	ns
			$V_{CC} = 4.5 \text{ V}$			15	
			$V_{CC} = 6.0 \text{ V}$			13	
See figure 4		$T_C = -55^{\circ}\text{C}, +125^{\circ}\text{C}$ $C_L = 50 \text{ pF} \pm 10\%$	$V_{CC} = 2.0 \text{ V}$	10,11		110	ns
			$V_{CC} = 4.5 \text{ V}$			22	
			$V_{CC} = 6.0 \text{ V}$			19	

- 1/ For a power supply of $5 \text{ V} \pm 10$ percent the worst case output voltage (V_{OH} and V_{OL}) occur for HC at 4.5 V . Thus the 4.5 V values should be used when designing with this supply. Worst case V_{IH} and V_{IL} occur at $V_{CC} = 5.5 \text{ V}$ and 4.5 V respectively. (The V_{IH} value at 5.5 V is 3.85 V). The worst case leakage current (I_{IN} , I_{CC} , and I_{OZ}) occur for CMOS at the higher voltage and so the 6.0 V values should be used. Power dissipation capacitance (C_{PD}), typically 100 pF , determines the no load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$, and the no load dynamic current consumption, $I_S = C_{PD} V_{CC} f + I_{CC}$.
- 2/ Test not required if applied as a forcing function for V_{OH} or V_{OL} .
- 3/ AC testing at $V_{CC} = 2.0 \text{ V}$ and $V_{CC} = 6.0 \text{ V}$ shall be guaranteed, if not tested, to the specified parameters.
- 4/ Transition time (t_{TLH} , t_{THL}), if not tested, shall be guaranteed to the specified parameters.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 7

DESC FORM 193A
FEB 86





FIGURE 1. Terminal connections.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
	REV		PAGE 8

Count				
Up	Down	Clear	Load	Function
↑	H	L	H	Count up
H	↑	L	H	Count down
X	X	H	X	Clear
X	X	L	L	Load

H = High level
 L = Low level
 ↑ = Transition from low to high
 X = Don't care

FIGURE 2. Truth table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 9

DESC FORM 193A
FEB 86




FIGURE 3. Logic diagram.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 10

DESC FORM 193A
FEB 86




FIGURE 4. Switching waveforms.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 11

DESC FORM 193A
FEB 86




FIGURE 4. Switching waveforms - Continued.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
	REV		PAGE 12

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test (method 1015 of MIL-STD-883).

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 5, 6, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

c. Subgroup 4 (C_{IN} measurement) shall be measured only for the initial test and after process or design changes which may affect input capacitance.

d. Subgroup 7 shall be tested sufficiently to verify truth table.

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test (method 1005 of MIL-STD-883) conditions:

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

(3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 13

DESC FORM 193A
FEB 86

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*,2,3,9
Group A test requirements (method 5005)	1,2,3,4,7,9,10,11
Groups C and D end-point electrical parameters (method 5005)	1,2,3,9
Additional electrical subgroups for group C periodic inspections	---

*PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Replaceability is determined as follows:

- Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.
- When a QPL source is established, the part numbered device specified in this drawing will be replaced by the microcircuit identified as part number M38510/66306.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-87808
		REV	PAGE 14

DESC FORM 193A
FEB 86

查询"5962-87808012X"供应商

6.4 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed herein have agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number 1/ 2	Replacement military specification part number
5962-8780801EX	27014 18714	MM54HC192J/883 CD54HC192F/3A	M38510/663068EX
5962-87808012X	27014	MM54HC192E/883	M38510/6630682X

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

27014

18714

Vendor name
and address

National Semiconductor Corp.
2900 Semiconductor Drive
Santa Clara, CA 95051

RCA Solid State Division
Route 202
Somerville, NJ 08876

MILITARY DRAWING

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO

SIZE
A

CODE IDENT. NO.
14933

DWG NO.
5962-87808

REV

PAGE 15

DESC FORM 193A
FEB 86