ELWIS FLUORESCENT HANDLAMPS			
8 watt fluorescent handlamp fitted with	Voltage	Ref. No.	+45-350/52
electronic starter and ballast. IP67 rating	240 v, AC	19E008	
and complies to BS4533. Resistant to oil	110 v AC	19E110	
and petrol. Fitted with 6m of flexible cable.	24 v AC or DC	19E024	u W
END ELLICRESCENT HANDLAARS			
EHB FLUORESCENT HANDLAMPS (all fitted			
SINGLE TUBE HANDLAMP	Voltage	Ref. No.	
Veatherproof	240v	R54	
watt/360 lumens. Double insulated IP54	110v	R53	
rotection. Handle is neoprene with polycarbonate	50v	K55	
outer tu <mark>be. Cho</mark> ke housed in neoprene. Cable length s 5.8 metres.	24v	K52	
mmersion Proof	240v	WH1082	
watt/360 lumens, as weatherproof unit but with	110v	WH1081	
he lamp protected to IP67. Will work at depth of	50v	WH1085	
100 metres. Temps of -10°C to 60°C.	24v	WH1084	
ransformers available on request			
TWIN TUBE HANDLAMP	100		
Veatherproof Neatherproof	240v	R57	
16 watt/720 lumens. Double insulated IP54	110v	R56	
protection. Handle is neoprene with polycarbonate	50v	M55	
outer tube. Choke housed in neoprene. Cable length	24v	M52	The same with 15
is 5.8 metres.			
Immersion Proof	240v	WH2082	
16 watt/720 lumens as weatherproof unit but with	110v	WH2081	
the lamp protected to IP67. Will work at depth of	50v	WH2085	
100 metres, temps of -10°C to 60°C.	24v	WH2084	
Transformers available on request			
BARREL HANDLAMP - Weatherproof	240v	R52	
8 watt/360 lumens. Double insulated IP54	110v	R51	
protection. Handle is neoprene with polycarbonate	50v	L55	
outer tube. Choke housed in neoprene. Cable length	24v	L52	
is 5.8 metres. Lamp length - 1000mm, diam 25mm.			17.113
Transformers available on request			GG.GOM
CASK HANDLAMP - Weatherproof	240v	LH1082	ALM MICO.
8 watt/360 lumens. Double insulated IP54	110v	LH1081	
protection. Handle is neoprene with polycarbonate	50v	LH1085	
outer tube. Choke housed in neoprene. Cable length	24v	LH1084	
is 5.8 metres. Lamp length - 480mm, diam 25mm.	14		
Transformers available on request			63
D.C. OPERATED HANDLAMP - Weatherproof	49	D40	-
	12v 24v	R12 R24	
8 watt/360 lumens. IP54 protection. Neoprene handle. Polycarbonate outer tube. Cable length is 6 metres.	24V	RZ4	
Torycarbonate outer tube. Cable length is o meties.			
BRITICENT FLUORESCENT HANDLAMPS	CAVIA :		
20 watt	Voltage	Ref. No.	A
Electronic IP67 Fluorescent 20 watt double	voitage 240v	EHL20	
insulated handlamp for 240 volt operation.	a. ⊤V ₹	L. 1220	
Polycarbonate 54mm outer tube with rubber			
handle. Complete with 20 watt plc tube and 5			
metres cable.			
36 watt			
IP65 Fluorescent double insulated 36 watt	24v AC	6336/24	
handlamp. Polycarbonate outer tube. Complete with	110v AC	6336/110	
integral ballast and 5 metres cable. Length 800mm,	240v AC	6336/240	5
Dameter 63mm			
			→ *

pdf.dzsc.com 11