



FlexPlane™ Optical Circuitry

- 106401** Standard
- 106404** Flame-Retardant
- 106406** 3D Compact Substrates

High-density FlexPlane Optical Circuitry provides high-density optical routing on PCBs or backplanes


Molex's FlexPlane optical flex circuitry provides one of the highest density and versatile interconnect systems on the market today. For high fiber-count interconnects in backplanes and cross-connect systems, Molex's FlexPlane provides a manageable means of fiber routing from card-to-card or shelf-to-shelf. Designed for versatility, the standard FlexPlane (Series 106401) provides high-density routing on a flexible, flame-resistant substrate. Additional options are now available including flame-retardant assemblies and 3D versions.

As the industry requirements for flammability have become more stringent, Molex developed a custom flame-retardant FlexPlane assembly. The flame-retardant FlexPlane assembly (Series 106404) meets the UL Optical Branching Device Flammability requirements.


The 3D FlexPlane (Series 106406) provides almost a 50% substrate size reduction compared to the standard FlexPlane. This is critical, as board space and air flow continue to become a stringent part of OEM design requirements. Traditional FlexPlane flex circuits are routed on a single substrate. The 3D FlexPlane routes the fiber on multiple stacked substrates to achieve a compact routing area.

A variety of interconnects, including Blind Mate MTP (BMT™), High Density Blind Mate MT (HBMT™), Blind Mate LC (BLC™) and Blind Mate SC (BSC™) can be used to connect the optical flex circuits to individual cards in a shelf. Available in any routing scheme, fiber can be routed point-to-point, in a shuffle, or in a logical pattern to meet specific requirements. Direct or fusion-spliced terminations are available.


Packaging alternatives include standard bare flexible substrate, sandwiched in FR-4 or custom laminating. Each FlexPlane circuit can be fully tested down to the per port insertion loss and return loss. For more information on Molex's FlexPlane offering, visit: www.molex.com/fiber/flexplane.html.



Standard FlexPlane (Series 106401)



Flame-Retardant FlexPlane (Series 106404)



3D FlexPlane (Series 106406)

FEATURES AND SPECIFICATIONS

[查询"106404"供应商](#)



FlexPlane™ Optical Circuitry

106401 Standard
106404 Flame-Retardant
106406 3D Compact
Substrates

Features and Benefits

- Diverse substrate size, shape and packaging provides efficient and manageable solutions to high-fiber count systems
- Compatible with mass and discrete-fiber terminations to ensure customized solutions
- Available in virtually any routing scheme to provide a variety of design alternatives
- Direct or fusion splice terminations available to eliminate additional insertion loss
- Compatible with MT ferrules, an ideal solution for high-density applications using Molex's backplane HBMT and BMTP interconnect systems
- Singlemode, multimode or hybrid versions provide a variety of options
- Entire circuit is 100% insertion loss (IL) and continuity tested to ensure correct pin-out prior to shipment

SPECIFICATIONS

Reference Information

Packaging: Packaged flat in a box

Flame Retardant FlexPlane (Series 106404):

Meets UL Optical Fiber Branching Device
(File # E236312)

Mates With-Terminate with:

MT based connectors (MTP, HBMT™, BMTP™)

Single-fiber connectors (Series LC, SC, BLC™, BSC™)

Optical

Insertion Loss (IL): Dependant on terminated
connector type

Fiber Type:

Singlemode – 9/125µm

Multimode – 50/125µm

Multimode – 62.5/125µm

Physical

Substrate: Kapton*

Thickness: Typical is less than 1.50mm (.059") per layer


Mounting: Mounting holes or devices are designed to
customer requirements

*Kapton is a registered trademark of DuPont

APPLICATIONS

Telecommunication

- Hubs
- Servers
- Routers
- Switches






FlexPlane™ Optical Circuitry

106401 Standard

106404 Flame-Retardant

106406 3D Compact
Substrates

Key Design Properties



CROSS SECTION ILLUSTRATION


[查询"106404"供应商](#)



FlexPlane™
Optical Circuitry

106401 Standard
106404 Flame-Retardant
106406 3D Compact
Substrates

Cross Section of a Typical FlexPlane Layer with Single Fiber Crossing



ORDERING INFORMATION

Order No.	Description	Substrate Width	Substrate Length	Substrate Height
106401-0000 [†]	Standard Routing 8-by-8 Perfect Shuffle	74.00mm (2.93")	137.00mm (5.394")	1.50mm (.059")
106404 [†]	Flame-Retardant Standard Shuffle Series	Standard or 3D versions are also available as Flame-Retardant FlexPlane assemblies		
106406-0000 [†]	3D Routing 8-by-8 Perfect Shuffle	32.00mm (1.260")	71.00mm (2.795")	3.00mm (.118")
106404 [†]	Flame-Retardant 3D Shuffle Series	Standard or 3D versions are also available as Flame-Retardant FlexPlane assemblies		

[†] Only sold as terminated assemblies. Part numbers and sales drawings will be established based on specific customers design requirements.

www.molex.com/fiber/flexplane.html

Molex Fiber Optics
5224 Katrine Avenue
Downers Grove, IL 60515
amerinfo@molex.com

Asia Pacific North Headquarters
Yamato, Kanagawa, Japan
81-46-265-2325
apninfo@molex.com

Asia Pacific South Headquarters
Jurong, Singapore
65-6268-6868
fesinfo@molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
P: 630-969-4550 F: 630-969-1352