

DESIGNED TO IEC STANDARD

5 x 20 mm Fast-Acting Type



- Designed to International (IEC) Standards for use globally.
- Meets the IEC 127-2, Sheet 1 specification for Fast Acting Fuses.
- Available in Cartridge and Axial Lead Form.
- Available in ratings of 0.050 to 10 amperes.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
150%	.05–3.15	60 minutes, Minimum
	4–6.3	60 minutes, Minimum
210%	.05–3.15	30 minutes, Maximum
	4–6.3	30 minutes, Maximum
275%	.05–3.15	0.01 sec., Min. ; 2 sec. Max.
	4–6.3	0.01 sec., Min. ; 3 sec. Max.
400%	.05–3.15	.003 sec., Min. ; 0.3 sec. Max.
	4–6.3	.003 sec., Min. ; 0.3 sec. Max.
1000%	.05–3.15	.02 seconds, Maximum
	4–6.3	.02 seconds, Maximum

AGENCY APPROVALS: Sheet I IEC 127-2:* SEMKO approved thru 6.3 amps. Recognized under the Components Program of Underwriters Laboratories and recognized by CSA.KEMA approved to 6.3A. BSI approved 1A to 6.3A. VDE approved .05–.2, .315–6.3.

INTERRUPTING RATING: 1500 amperes.

ORDERING INFORMATION:

Cartridge Catalog Number	Axial Lead Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² t A ² Sec.
216.050	226.050	.050	250	15.90	0.00019
216.063	226.063	.063	250	10.45	0.00055
216.080	226.080	.080	250	7.89	0.00086
216.100	226.100	.100	250	5.42	0.0033
216.125	226.125	.125	250	3.68	0.0056
216.160	226.160	.160	250	5.20	0.0018
216.200	226.200	.200	250	3.35	0.0045
216.250	226.250	.250	250	2.35	0.0092
216.315	226.315	.315	250	1.85	0.015
216.400	226.400	.400	250	1.67	0.028
216.500	226.500	.500	250	1.20	0.045
216.630	226.630	.630	250	0.790	0.097
216.800	226.800	.800	250	0.588	0.18
216.001	226.001	1	250	0.228	0.19
216 1.25	226 1.25	1.25	250	0.153	0.49
216 01.6	226 01.6	1.6	250	0.108	1.04
216 002	226 002	2	250	0.0770	1.92
216 02.5	226 02.5	2.5	250	0.0575	2.77
216 3.15	226 3.15	3.15	250	0.0333	7.85
216 004	226 004	4	250	0.0243	15.4
216 005	226 005	5	250	0.0168	28.2
216 06.3	226 06.3	6.3	250	0.0125	57.9
216 008	226 008	8*	250	0.0120	66.1
216 010	226 010	10*	250	0.00775	158.5

*IEC Standards for 5 x 20mm fuses do not include ratings above 6.3 amperes.

