



0.80mm (.031") Pitch Board-to-Board MDC Connector

FEATURES AND SPECIFICATIONS

[查询"48233-1201"供应商](#)

Molex offers the MDC connectors for mobile personal computer audio and modem codec solutions.

The Azalia mobile daughter card (MDC) specification provides a mobile form-factor modules and interface for audio or modem or audio/modem codec solutions. The MDC specification is open to the industry to facilitate IHV validation on Azalia based codec designs.

There are 2 system interface connector for the MDC. They are the MDC 1.0 and MDC 1.5. The MDC 1.0 can apply to audio, modem, or audio and modem codec solutions and the MDC 1.5 applies to modem or audio codec solutions only. The MDC 1.0 and MDC 1.5 comes in a 30 circuits and 12 circuits configuration respectively.

Molex offers the complete range of MDC connectors which covers the mated height of 3mm to 5.5 mm.

48126 SMT Plug



48168, 48210, 48211, 48243, 48233

SMT Receptacle



48168



48210



48211



48233



48243



48120



48168



48211



48243



48233



48126

Features

- Multiple stack heights
- Cantilever-type gold contact
- High Temp housing material
- Embossed tape packaging
- RoHS compliant

Benefits

- Offers design flexibility
- Reliability under severe shock and vibration
- Withstands high-temperature SMT soldering process
- Automated pick & place
- Compliant with environmental requirements

SPECIFICATIONS

Reference Information

Packaging: Tape & Reel

UL File No.:

CSA File No.:

Mates : 48168 / 48210 / 48211 mates with 48126

Designed In: mm

Electrical

Voltage: 50V

Current: 0.5A

Contact Resistance: 40 Milliohms Max.

Dielectric Withstanding Voltage: 250V AC

Insulation Resistance: 1000 Megohms min.

Mechanical

Mating Force: 0.69N max.

Unmating Force: 0.12N min.

Durability: 50 cycles

Physical

Housing: High Temperature, Thermoplastic, Glass-filled

Contact: Copper Alloy

Plating: Tin (Sn)

Under plating: 1.27 um Nickel (Ni)

Operating Temperature: -40 °C to +85 °C.



MARKETS AND APPLICATIONS

[查询"48233-1201"供应商](#)

- **Notebook Industry**



**0.80mm (.031") Pitch
Board-to-Board
MDC Connector**

**48126
SMT Plug**

**48168, 48210, 48211,
48243, 48233
SMT Receptacle**

ORDERING INFORMATION

Description	Lead-Free Order Number	Circuit size	Carrier Tape Width	Packaging Quantity (pcs/reel)
MDC 0.80mm (.031") pitch, Board-to-board Plug, SMT, 3.50mm (.138") mated height	48126-1201	12	16.00mm	1500
	48126-3001	30	24.00mm	
MDC 0.80mm (.031") pitch, Board-to-board Receptacle, SMT, 3.00mm (.118") mated height	48210-1201	12	16.00mm	1500
	48210-3001	30	24.00mm	
MDC 0.80mm (.031") pitch, Board-to-board Receptacle, SMT, 3.50mm (.138") mated height	48168-1201	12	24.00mm	1400
	48168-3001	30		
MDC 0.80mm (.031") pitch, Board-to-board Receptacle, SMT, 4.20mm (.165") mated height	48211-1201	12	16.00mm	1200
MDC 0.80mm (.031") pitch, Board-to-board Receptacle, SMT, 5.00mm (.197") mated height	48243-1201	12	16.00mm	1000
MDC 0.80mm (.031") pitch, Board-to-Board Receptacle, SMT, 5.50mm (.217") Mated height	48233-1201	12	16.00mm	600



Bringing People & Technology Together, WorldwideSM

Americas Headquarters
2222 Wellington Ct.
Lisle, Illinois 60532 USA
1-800-78MOLEX
amerinfo@molex.com

Far East North Headquarters
Yamato, Kanagawa, Japan
81-462-65-2324
feninfo@molex.com

Far East South Headquarters
Jurong, Singapore
65-6-268-6868
fesinfo@molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, Illinois 60532 USA
630-969-4550

Visit our Web site at <http://www.molex.com>