

HDSL2 TRANSFORMER

For Level One Chipset



- Matched to Level One SK70740/SK70741/SK70742 HDSL2 Chipset
- Excellent THD performance
- Maximum height .500" (12,70 mm)





Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	Turns Ratio Chip-Line (±2%)	OCL @ 10 KHz, 100 mV (1-5) with (2-4) shorted	Longitudinal Balance	THD (10 KHz @ 4.95 Vrms)	DC Resistance (7-9), (4-1), (5-2)	Isolation Voltage (Vrms)
B1019	1:2	1.76 mH (±10%)	>50 dB @ 20 KHz to 600 KHz	77 dB MIN	0.60 Ω MAX	2000
B1042	1:2.3	1.76 mH (±10%)	>43 dB @ 20 KHz to 400 KHz	77 dB MIN	0.60 Ω MAX	2000

Mechanical

Schematic

B1019/B1042



Weight.....14.0 grams
Tray45/tray

Dimensions: Inches
mm
Unless otherwise specified,
all tolerances are ± .010
0,25

For More Information :

UNITED STATES (Worldwide)

12220 World Trade Drive
San Diego, CA 92128
U.S.A.
<http://www.pulseeng.com>
TEL: 858 674 8100
FAX: 858 674 8262

UNITED KINGDOM (Northern Europe)

1 & 2 Huxley Road
The Surrey Research Park
Guildford, Surrey GU2 5RE
United Kingdom
TEL: 44 1483 401700
FAX: 44 1483 401701

FRANCE (Southern Europe)

Zone Industrielle
F-39270
Orgelet
France
TEL: 33 3 84 35 04 04
FAX: 33 3 84 25 46 41

SINGAPORE (Southern Asia)

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324
TEL: 65 287 8998
FAX: 65 280 0080

TAIWAN, R.O.C. (Northern Asia)

3F-4, No. 81, Sec. 1
HsinTai Wu Road
Hsi-Chih, Taipei Hsien
Taiwan, R.O.C.
Tel: 886 2 2698 0228
FAX: 886 2 2698 0948

DISTRIBUTOR

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

Printed on recycled paper. ©2000, Pulse Engineering, Inc.

PRELIMINARY B921.P (6/00)

