

LED Signalleuchten

Einbaudurchmesser 14mm

mit weiß diffusen Linsen



LED Indicators

Body diameter 14mm

with white diffuse lenses

[查询"192B1351"供应商](#)

Bestell-Nr. Part No.	Farbe Colour	V _{OP} +10% [V] AC/DC	I _{OP typ.} [mA] AC/DC	**I _{V typ.} [mcd]	V _R [V]	Elektrische und optische Daten sind bei T _U = 25°C gemessen. Electrical and optical data are measured at T _A = 25°C.
192B*250	Red	12	9 / 17	60	80	
192B*251	Green	12	9 / 17	40	80	
192B*252	Yellow	12	9 / 17	40	80	
192B*350	Red	24	9 / 17	60	80	
192B*351	Green	24	9 / 17	40	80	
192B*352	Yellow	24	9 / 17	40	80	
192B*450	Red	28	9 / 17	60	80	
192B*451	Green	28	9 / 17	40	80	
192B*452	Yellow	28	9 / 17	40	80	
				</		

[查询"192B1/51"供应商](#)



Hinweise zur Anwendung Instruction for application



Anschluß:

Die Anzeigen mit Flachsteckanschlüssen sind **nicht** für Lötanschluß geeignet.

Chemikalienbeständigkeit:

Der Kunststoff (Polycarbonat) ist nur bedingt chemikalienbeständig.
Weitere Angaben auf Anfrage.

Die Auswahl und der technisch richtige Einbau unserer Produkte nach den entsprechenden Vorschriften (z.B. VDE 0100 und VDE 0160), obliegen dem Anwender.

Connection:

The indicators with tabconnection are **not** qualified for soldering.

Resistancy against chemicals

The plastic (polycarbonate) is limited resistant against chemicals.
Further information upon request.

The selection and technical correct installation of our products, conforming for the relevant standards (e.g. VDE 0100 and VDE 0160) is incumbent on the user.