

查询"1N6364"快过商

Microsemi Corp.

The diode experts

SANTA ANA, CA

SCOTTSDALE, AZ

For more information call:
(602) 941-6300

1N6356 thru
1N6372
and
MPT-5 thru
MPT-45C

FEATURES

- DESIGNED TO PROTECT BIPOLAR AND MOS MICROPROCESSOR BASED SYSTEMS.
- VOLTAGE RANGE OF 5.0 TO 45 VOLTS
- LOW CLAMPING RATIO

MAXIMUM RATINGS

1500 Watts of Peak Pulse Power dissipation at 25°C at 10/1000 μ s

$t_{clamping}$ (0 volts to $V_{(BR)}$ min): Unidirectional — Less than 1×10^{-12} seconds
Bidirectional — Less than 5×10^{-9} seconds

Operating and Storage temperatures: -65° to $+175^{\circ}$ C

Forward surge rating: 200 amps, 1/120 second at 25°C

(Applies to Unipolar or single direction only for 1N6356-1N6364)

Steady State power dissipation: 1.0 watt

Repetition rate (duty cycle): .01%

ELECTRICAL CHARACTERISTICS

Clamping Factor: 1.33 @ Full rated power
1.20 @ 50% rated power

Clamping Factor: The ratio of the actual V_C (Clamping Voltage) to the actual $V_{(BR)}$ (Breakdown Voltage) as measured on a specific device.





FIGURE 1
PEAK PULSE POWER VS. PULSE TIME

TRANSIENT ABSORPTION ZENER



MECHANICAL CHARACTERISTICS

CASE: DO-13 welded, hermetically sealed, metal and glass.

FINISH: All external surfaces are corrosion resistant and leads solderable.

POLARITY: Cathode connected to case and marked. Bidirectional not marked.

WEIGHT: 1.4 grams (Appx.)

MOUNTING POSITION: Any.

1N6356 thru 1N6372 and MPT-5 thru MPT-45C

ELECTRICAL CHARACTERISTICS @ 25°C

MICROSEMI PART NUMBER	STAND-OFF VOLTAGE (NOTE 1) V_{WM} VOLTS	MAXIMUM REVERSE LEAKAGE @ V_{WM} I_D μA	MINIMUM* BREAKDOWN VOLTAGE @ 1.0 mA V_{BR} (min) VOLTS	MAXIMUM CLAMPING VOLTAGE (Fig. 2) $I_{PP1} = 1A$ V_C VOLTS	MAXIMUM CLAMPING VOLTAGE (Fig. 2) @ $I_{PP2} = 10A$ V_C VOLTS	MAXIMUM PEAK PULSE CURRENT I_{PP3} A
1N6356 MPT-5	5.0	300	6.0	7.1	7.5	160
1N6357 MPT-8	8.0	25	9.4	11.3	11.5	100
1N6358 MPT-10	10.0	2	11.7	13.7	14.1	90
1N6359 MPT-12	12.0	2	14.1	16.1	16.5	70
1N6360 MPT-15	15.0	2	17.6	20.1	20.6	60
1N6361 MPT-18	18.0	2	21.2	24.2	25.2	50
1N6362 MPT-22	22.0	2	25.9	29.8	32.0	40
1N6363 MPT-36	36.0	2	42.4	50.6	54.3	23
1N6364 MPT-45	45.0	2	52.9	63.3	70.0	19

V_f at 100 amps peak, 8.3 msec sine wave equals 3.5 volts maximum

ELECTRICAL CHARACTERISTICS @ 25°C (Test Both Polarities)

1N6365 MPT-5C	5.0	300	6.0	7.1	7.5	160
1N6366 MPT-8C	8.0	25	9.4	11.4	11.6	100
1N6368 MPT-10C	10.0	2	11.7	14.1	14.5	90
1N6367 MPT-12C	12.0	2	14.1	16.7	17.1	70
1N6368 MPT-15C	15.0	2	17.6	20.8	21.4	60
1N6369 MPT-18C	18.0	2	21.2	24.8	25.5	50
1N6370 MPT-22C	22.0	2	25.9	30.8	32.0	40
1N6371 MPT-36C	36.0	2	42.4	50.6	54.3	23
1N6372 MPT-45C	45.0	2	52.9	63.3	70.0	19

C Suffix indicates Bidirectional

NOTE 1 TAZ are normally selected according to the reverse "Stand Off Voltage" (V_{WM}) which should be equal to or greater than the DC or continuous peak operating voltage level.

*The minimum breakdown voltage as shown takes into consideration the ± 1 volt tolerance normally specified for power supply regulation on most integrated circuit manufacturers data sheets. Similar devices are available with reduced clamping voltages where tighter regulated power supply voltages are employed.






FIGURE 2



Typical Capacitance vs. Breakdown Voltage
(Unidirectional Types)



Typical Capacitance vs. Breakdown Voltage
(Bidirectional Types)