

7158221

[查询"1415220"供应商](#)

TradesMarc 151

The expertise gained in the design and manufacture of high quality industrial arc welding equipment has now been used to produce the latest light duty MIG welder from Murex.

The Murex TradesMarc 151 is the ultimate in light duty MIG composites, designed for users looking for a quality MIG welder for less complex welding applications, but who still require a quality result. In this area the Murex TradesMarc stands out from the crowd. With features normally associated with equipment of a much higher specification yet having the flexibility of operating from a 240V domestic supply, the TradesMarc is the ideal machine for many quality DIY, vehicle repair, farming and general repair applications.

- Robust yet compact design
- Run "gas-less" Migwires
- Thermal overload protection
- Complete with undergear and cylinder carrier (for V/W cylinders)
- Simple two knob control
- CE Approved



Consumables

2302064600	Bostrand LW1	0.6mm	5kg
2302062500	Bostrand LW1	0.6mm	15kg
2302084600	Bostrand LW1	0.8mm	5kg
2302082500	Bostrand LW1	0.8mm	15kg
2903082480	Bostrand 308Lsi	0.8mm	12.5kg
2020082480	Bostrand 309Lsi	0.8mm	12.5kg



TradesMarc 151 Accessories

5kg Reel Adaptor	1415221
0.6/0.8 Feed Roll Kit	469517880
Feed Rolls 1mm	469517881
Gas Nozzle	469518881
Contact Tips 1mm	469518883
Teflon Liner and 1mm Contact Tips	469518883
Spot Weld Nozzle	469518886
Contact Tips 0.8mm (Pk of 10)	469518896
Contact Tips 0.8mm (Pk of 10)	469518895

TradesMarc151 Package Part No. 1415220

Package contents:

- Composite power source with wire lead unit complete with primary cable
- Gas hose, fitted work return lead and PSG 14V MIG torch
- Cylinder carrier and undergear
- Instruction manual

Technical Specifications

Output		Duty 8% (10min)	Duty 20%	Duty 60%	OCV DC	Voltage Steps
Range		150A	100A	55A	16-28V DC	7
30-150A						
Mains Supply						
240V	Fuse	Mains Cable	Wire Speed	Gas Cylinder		
1(1) Phase, 50Hz	13A	3 x 1.5mm ²	2.5-15m/min	V/X or T/Y		
Enclosure Class: IP21						
Dimensions				Wire Diameters		
Width	Height	Length	Weight (net)	0.6-0.8 mm	0.9 mm	1.0 mm
430mm	530mm	780mm	40Kg	Mild/Stainless	Gasless FCW	Al 5% mg