查询"1590R1FL"供应商

NOTES

Parts: Enclosure base, lid and either 4, 6, or 8 (6-32X0.5") nickel plated machine screws. Painted boxes come with coror matching screws. Replacement screws are available, see catalog for details.

Options: Water resistant silicone seal by adding the letter "W" after 1590 in the part number. Silicone temperature range (-62 C to 232 C, "-80 F to 450 F")

Finish: Unfinished (no suffix), Black powder ("BK" suffix), Gray Powder ("GY" suffix)



BOX



LID

For the best fit print on legal size paper.

THIS DRAWING IS PROPRIETARY INFORMATION OF HAMMOND MFG.CO.LTD. NOT TO BE USED WITHOUT EXPRESSED WRITTEN PERMISSION OF HAMMOND MFG.CO.LTD.

Rev	ECN	Description		Date	By
A	N/A	RELEASE	----	06 13 02	MJM

Unless otherwise spec'd dimensions are in inches
Tolerances are.
.X ± .1
.XX ± .05
.XXX ± .030
.XXXX ± .0050
Holes ± .0050
Angles ± .5°

Dwn	M. MERCER
Date	06 13 02
Chk	---
Mat'l	Die-casted Aluminum alloy 413(13)
Sheet	1 of 1

HAMMOND MANUFACTURING CO. LTD.
Electronics Group, Waterloo, Ont. - Cheektowaga, NY

HAMMOND 1590 SERIES DIE-CASTED ENCLOSURE

Part#: 1590R1FL

Dwg: 1590R1FL/A

找PDF 维库一下 pdf.dzsc.com